

A-151 Solvent/Degreaser

Supercedes: 08/18/04

Revision Date 11/15/07

Section 1 • Product and Company Identification

Product Name: A-151 Solvent/Degreaser

Revision 4

Part Number: 04320,04328,04305,04355, C04320,C04328,C04305,C04355

Chemical Name: Petroleum Hydrocarbons

Product Use: A spray degreaser designed for removing heavy residues from metal and other hard surfaces

where reduced flammability, toxicity and environmental impact are concerns.

Manufacturer Information:

LPS Laboratories, 4647 Hugh Howell Rd., Tucker, GA, USA 30084

TEL: 1 770-243-8800

FAX: 1 770-243-8899

PLAIN LANGUAGE HAZARD SUM MARY

Material Safety Data Sheets can be confusing. Federal and State laws require us to include a great deal of technical information that probably wond help the non-professional. LPS includes this %RLAIN LANGUAGE HAZARD SUMMARY+to address the questions and concerns of the average worker. If you have additional health, safety or product questions, dond hesitate to call us at 800/241-8334.

Worker Toxicity

A-151 Solvent/Degreaser is an industrial chemical. It is a high strength cleaning solvent designed to remove oils, resins, grease and grime. It contains petroleum distillates and special ‰oating solvents+that can be irritating to skin. Avoid extended exposure to unprotected skin. If the product soaks clothing (and even shoes), remove the affected clothing and launder it before wearing it again. THROW AWAY SOAKED SHOES! Dond get the solvent in your eyes (it stings), or breath the vapor (especially if working on hot surfaces or with heated tanks). Vapors from heated A-151 Solvent/Degreaser can make you dizzy and even sick. For more exposure and first aid information, refer to MSDS Sections 2, 3, 8 and 11.

Flammability

A-151 Solvent/Degreaser is combustible having a flash point above 170°F and an autoignition temperature over 375° F. Under normal use conditions flammability isnot a concern, but donot apply the product onto red-hot metal surfaces or near sparks.

Disposal

If you spill A-151 Solvent/Degreaser, notify the proper environmental or safety department at your company right away. If A-151 Solvent/Degreaser becomes contaminated with another substance and is rendered unusable for cleaning, the resulting mixture will fall under at least one hazardous classification. See section 13 for more details.

Notice to LPS customers

Due to phase-out of the Exxate® line of alkyl acetate solvents by Exxon/Mobil, we reformulated our product in 2004, LPS A-151 Degreaser effective August 18, 2004 (date stamp %231+). The new formulation was evaluated by an independent aerospace materials testing facility and continues to conform to the Douglas CSD#1 and Boeing D6-17487P specifications. In addition, LPS A-151 Degreaser is now %LO.C. compliant+for all cleaning and degreasing applications throughout the United States. This document is the Safety Data Sheet for the current formulation. If there is a need for a safety data sheet for the formulation dated before August 18, 2004 (date stamp %231+), please contact us.



A-151 Solvent/Degreaser

Revision Date 11/15/07

Supercedes: 08/18/04

Section 2 • Hazards Identification

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Emergency Overview Aerosol: DANGER: Flammable Aerosol. Aerosol contents under pressure. Harmful or Fatal if

Swallowed.

Emergency Overview Bulk: CAUTION: Combustible liquid. Harmful or fatal if swallowed.

Primary route(s) of entry: Skin and Eye contact. Inhalation.

Revision 4

Potential Acute Health Effects:

Eyes: Irritating to eyes

Skin: Repeated exposure may cause skin dryness or cracking.

Inhalation: High vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney

effects. Aspiration into lungs may cause pneumonia or death.

Ingestion: If swallowed, call a physician immediately. ONLY induce vomiting at the instruction of a physician.

Never give anything by mouth to an unconscious person.

Potential Chronic Health Effects:

Carcinogenic Effects: NTP: No OSHA: No ACGIH: No

Mutagenic Effects: None

Teratogenic Effects: None

Target Organs: None

Medical conditions aggravated by exposure: None known at this time.

Signs and Symptoms:

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects.

Section 3 • Composition /Information on Ingredients

INGREDIENT NAME	CASRN	Weight Percent
Distillates (Petroleum), Hydrotreated Light	64742-47-8	60 . 70%
Dipropylene glycol methyl ether acetate	88917-22-0	10 . 20%
Dipropylene glycol mono butyl ether	29911-28-2	10 . 20%
Carbon Dioxide Propellant (Aerosol only)	124-38-9	1 - 5 %



A-151 Solvent/Degreaser

Revision Date 11/15/07

Supercedes: 08/18/04

Section 4 • First Aid Measures

Eyes: Check for and remove contact lenses. If irritation or redness develops, flush eyes with cool, clean, low

pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid

tissue. Do not use eye ointment. Seek medical attention immediately.

Skin: Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. Do not

use ointments. Seek medical attention if irritation persists.

Inhalation: Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If heart

has stopped, immediately begin cardiopulmonary resuscitation (CPR). If breathing is difficult, seek medical

attention immediately.

Revision 4

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an

unconscious person. If spontaneous vomiting is about to occur, place victims head below knees. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended. Seek medical

attention immediately.

Section 5 • Fire Fighting Measures

Flash point: TCC CLOSED CUP: 79.4° to 81°C (174.9°F to 177°F) bulk liquid

Flammable limits: LOWER: 0.6% UPPER: 20.4% Auto ignition Temperature: 194°C (381°F)

Products of Combustion: Carbon monoxide and carbon dioxide.

Firefighting media: SMALL FIRE: Use DRY chemical powder.

cleanup.

LARGE FIRE: Use water spray, fog or foam. Cool containing vessels with water jet in order to

prevent pressure build-up, auto ignition or explosions.

Sensitivity to Impact: None.

Sensitivity to Static Discharge: None

Protection Clothing (Fire): Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Evacuate area and fight the fire from a maximum distance or use unmanned hose holders or monitor nozzles.

Special Remarks on Explosion Hazards: Intense heat created by fire will cause aerosols to burst.

Section 6 • Accidental Release Measures				
Containment Procedures	Small Spill and Leak:	Eliminate all ignition sources. Absorb with an inert material and dispose of properly.		
	Large Spill and Leak:	Ventilate area by opening windows and doors. Eliminate all ignition sources. Block the path of any flowing material using soil, gravel, or other readily available material. Absorb with dry earth, sand or other non-combustible material and dispose of properly.		
Clean-Up Procedures	Recover free product and place in suitable container for disposal.			
Evacuation Procedures	Ventilate area of leak or spill. Keep unnecessary and unprotected people away.			
Special Procedures	Remove all sources of ignition. Ventilate area. Wear appropriate protective equipment during			



A-151 Solvent/Degreaser

Revision Date 11/15/07

Supercedes: 08/18/04

Section 7 • Handling and Storage

Handling: DO NOT spray into or around ignition sources. After handling, always wash hands thoroughly with soap and water. Use only with adequate ventilation. Avoid breathing vapors or spray mists. Avoid contact with eyes, skin, and clothing.

Storage: Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F.

Precautions to be taken in handling and storage: Store all materials in dry, well-ventilated area. Avoid breathing vapors. Ground and bond containers before transferring materials.

Section 8 • Exposure Controls / Personal Protection

Exposure Guidelines:

Component	CASRN	OSHA TWA-PEL	OSHA STEL	ACGIH TLV	ACGIH STEL	OTHER LIMTS
Distillates (Petroleum), Hydrotreated Light	64742-47-8	500 ppm	Not Established	100 ppm	Not Established	100 ppm*
Dipropylene glycol methyl ether acetate	88917-22-0	100 ppm	Not Established	Not Established	Not Established	Not Established
Dipropylene glycol mono butyl ether	29911-28-2	Not Established	Not Established	Not Established	Not Established	10mg/m³ aerosol*
Carbon Dioxide	124-38-9	5000 ppm	Not Established	5000 pm	30000 ppm	5000 CANADA TWA

^{*}Note: Exposure guidelines provided by supplier.

Revision 4

Engineering Controls: Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Personal Protection:

Eyes: Safety glasses with side shields conforming to appropriate regulations. Eye wash fountain

and emergency shower facilities are recommended.

Respiratory: Typical use of this product under normal conditions does not require the use of respiratory

protection. If extended spraying of product will be made under poor ventilation, use

appropriate organic vapor filtering respirators.

Hands: Normally no hand protection is required; however, if product will be sprayed for an extended

period, % verspray+onto skin may occur. If so, use protective gloves conforming to appropriate regulations. Please observe the instructions regarding permeability and

breakthrough time that are provided by the supplier of the gloves. Take into consideration the

specific local conditions under which the product is used, such as the danger of cuts,

abrasion and the contact time.

General Hygiene Considerations: Wash thoroughly after handling. Have eye-wash facilities immediately available.



A-151 Solvent/Degreaser

Revision Date 11/15/07

Supercedes: 08/18/04

Section 9 • Physical and Chemical Properties

Appearance: Liquid. Colour: Clear, water-white

Odour/Taste: Characteristic. Vapour Pressure: < 7 Pascals @ 20 °C

Solubility Description: Not soluble in water. Evaporation Rate: <0.1(BuAc=1)

Boiling Point (°C): 195 @ 101 kPa Flash Point (°C): 70°C (minimum)

Specific Gravity (Water=1): 0.84-0.86 @ 20 °C Flash Point Method: Tag-Closed Cup.

Vapour Density (air=1): 6.1 Auto Ignition 7 Temperature (°C): >194°C

V.O.C. Content: 0 g/L (per C.A.R.B. / Partition Coefficient >1

V.O.C. Content: 0 9/L (per C.A.R.B. / Faithful Coefficient >1

Flammable limits (estimated): LOWER: 0.6% Viscosity: <3 mm²/second @ 25°C UPPER: 20.4%

pH: Not applicable Odour threshold Not Determined

Melting Point <-50°C Volatiles: 100% (at 100 °C/1 hr.)

Decomposition Not Determined Temperature

Revision 4

Section 10 • Stability and Reactivity

Chemical Stability: Product is stable under recommended storage conditions.

Conditions to Avoid: Keep away from heat and ignition sources.

Incompatibility: Reactive or incompatible with oxidizing agents.

Hazardous Combustion will generate smoke, possibly thick and choking, resulting in zero visibility

Decomposition: and combustion products include carbon monoxide and carbon dioxide.

Hazardous Will not occur.

Polymerization:

Section 11 • Toxicological Information

Acute and Chronic Toxicity

A: General Product Information

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.



A-151 Solvent/Degreaser

Revision Date 11/15/07

Revision 4 Supercedes: 08/18/04

B: Component Analysis

Ingredients	CASRN	LC-50	LD-50	Carcinogenicity (IARC, NTP, OSHA)	Neurotoxicity	Reproductive Toxicity
Distillates (Petroleum), Hydrotreated Light	64742-47-8	>6.8 mg/L (Supplier Data)	>5 g/kg (Supplier Data)	Not listed.	No Data Available	No Data Available
Dipropylene glycol methyl ether acetate	88917-22-0	Not Established	>5 g/kg	Not listed.	No Data Available	No Data Available
Dipropylene glycol mono butyl ether	29911-28-2	>2.04 mg/L /4 hrs./rat	>3 g/kg	Not listed.	No Data Available	No Data Available
Carbon Dioxide	124-38-9	Not established	Not established	Not listed.	No Data Available	No Data Available

Section 12 • Ecological Information

Semi-volatile. Readily absorbed **Mobility:**

into soil.

Persistence and degradability:

Only slightly biodegradable.

Bioaccumulative potential:

No bioaccumulation potential

Other adverse effects:

None known.

Ecotoxicity:

Effect on Organisms	Component	CASRN	Test	Species	Results	
Acute Toxicity on Fishes	Distillates (Petroleum), Hydrotreated Light	64742-47-8	LC ₅₀	Oncorhynchus mykiss	3200 ug/L	
Acute Toxicity on Daphnia	No Data Available					
Bacterial inhibition						
Growth inhibition of algae						
Bioaccumulation in fish						

Section 13 • Disposal Considerations

Waste Status: Aerosol product: If depressurized and emptied to less than 2.5 cm of fluid contents are classified as

non-hazardous waste under 40 CFR 261.7 (U.S.). If disposed of in its received form, this item carries

waste code D003. (U.S.)

Bulk product: If discarded in its purchased form, this product is not a RCRA hazardous waste. Reevaluation of the product may be required by the user at the time of disposal, since the product uses,

transformations, and mixtures may change the classification.

Disposal: Waste must be disposed of in accordance with federal, state, provincial, and local environmental

control regulations.

Note: Chemical additions to, processing of, or otherwise altering this material may make this waste

management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and

local waste disposal requirements may be more restrictive than federal laws and regulations.



Revision 4

SAFETY DATA SHEET

A-151 Solvent/Degreaser

Revision Date 11/15/07

Supercedes: 08/18/04

Section 14 • Transport Information

<u>Aerosol</u>

	Shipping Name:	Consumer Commodity	UN Number:	NA
D.O.T. Ground	Hazard Class:	ORM-D	Technical Name:	NA
	Subclass:	NA	Hazard Label:	ORM-D
	UN no:	1950	ADR Class:	2
Road/Rail -	Classification code:	5F	Shipping name:	AEROSOLS, flammable
ADR/RID :	Labelling:	2.1	Packing Group:	NA
	UN no:	1950	Class:	2
IMDG-IMO	Shipping Name:	AEROSOLS	Packing Group:	NA
	EmS:	F-D, S-U	Packing Instructions:	P003
	UN no:	1950	Class:	2.1
IATA-ICAO:	Proper Shipping Name:	Aerosols, flammable	Labeling:	Flammable Gas
	Packing Group:	NA	Technical Name:	NA

<u>Bulk</u>

The bulk versions of this product are not regulated under any mode of transportation.

Section 15 – Regulatory Information

U.S. Federal Regulations

RCRA Hazardous Waste No.: D003 (Aerosol only)

Comprehensive Environmental Response and Liability Act of 1980 (CERCLA): This product contains no Reportable Quantity (RQ) Substances.

Toxic Substances Control Act (TSCA):

All components of this product are TSCA inventory listed and/or are exempt.

Superfund Amendments and Reauthorization Act (SARA) Title III SARA Section 311/312 (40 CFR 370) Hazard Categories:

Sudden Release of Pressure (aerosols only), Fire Hazard, Immediate (Acute) Health Hazard

This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372): None

Section 112 Hazardous Air Pollutants (HAPs): None



A-151 Solvent/Degreaser

Revision Date 11/15/07

Supercedes: 08/18/04

State Regulations

California: This product does <u>not</u> contain chemical(s) known to the State of California to cause cancer, birth defects or reproductive harm.

New Jersey Right to Know:

Distillates (Petroleum), Hydrotreated Light
Dipropylene glycol methyl ether acetate

Dipropylene glycol mono butyl ether

Carbon Dioxide (aerosol only)

64742-47-8
88917-22-0
29911-28-2
124-38-9

Revision 4

International Regulations

Canadian Environmental Protection Act: All of the components of this product are included on the Canadian Domestic Substances list (DSL).

Canadian Workplace Hazardous Materials Information System WHMIS:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Classification:

Aerosol: Class A, Class B5, Class D2B



Bulk: Class B3, Class D2B



Other Regulations

Montreal Protocol listed ingredients:
Stockholm Convention listed ingredients:
Rotterdam Convention listed ingredients:
RoHS Compliant:

None.
Yes.



A-151 Solvent/Degreaser

Revision Date 11/15/07

Supercedes: 08/18/04

Section 16 • Other Information

MSDS#14320 Responsible Name: Clea Johnson Regulatory Affairs Coordinator	HMIS 1996		HMIS III		NFPA Flammability	
	Health:	1	Health:	[/]1	3	
	Flammability:	3	Flammability:	3	Health 1 0 Reactivity	
	Reactivity:	0	Physical Hazard aerosol: bulk:	2 0		

Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Clea L Johnson, Regulatory Affairs Coordinator LPS Laboratories A division of Illinois Tool Works

Revision 4

Form #3541