LPS

SAFETY DATA SHEET

1. Identification

Product identifier LPS® PF® Solvent

Other means of identification

Part Number 61420

Recommended use A solvent agent designed for removing grease, oil and other residues from metal, power cable and

fiber optic cable surfaces.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer

Company name ITW Pro Brands

Address 4647 Hugh Howell Rd.

Tucker, GA 30084

Country (U.S.A.)

Tel: +1 770-243-8800

In Case of Emergency 1-800-424-9300 (inside U.S.)

+001 703-527-3887 (outside U.S.)

Website www.lpslabs.com

E-mail lpssds@itwprobrands.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Compressed gas

Health hazards Sensitization, skin Category 1

Aspiration hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if

swallowed and enters airways. May cause an allergic skin reaction.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Contaminated work clothing must not be allowed out of the workplace. Wear

protective gloves.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash

with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash

contaminated clothing before reuse.

Storage Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to

temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: LPS® PF® Solvent 61420 Version #: 01 Issue date: 07-18-2016 SDS US

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Naphtha Petroleum, Hydrotreated Heavy	I	64742-48-9	80 - 90
d-Limonene		5989-27-5	1 - 10
Carbon Dioxide		124-38-9	1 - 5

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

In case of eczema or other skin disorders: Seek medical attention and take along these Skin contact

instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Not likely, due to the form of the product. Ingestion

Most important

symptoms/effects, acute and delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Water spray. Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without

risk. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with

water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes. Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
		5000 ppm	
US. ACGIH Threshold Limit Val	ues		
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
US. NIOSH: Pocket Guide to Ch	emical Hazards		
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove Hand protection

supplier.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation,

be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Gas.
Form Aerosol.

Color Clear water-white.

Odor Orange.

Odor threshold Not available.

pH Not applicable

Melting point/freezing point Not available.

Initial boiling point and boiling

range

365 °F (185 °C) @760 mm Hg

Flash point > 141.8 °F (> 61.0 °C) Tag Closed Cup

Evaporation rate < 0.1 BuAc = 1Flammability (solid, gas) Flammable gas.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.7 %

5.3 %

Not available.

(%)

Flammability limit - upper

Explosive limit - upper (%)

(%)

Explosive limit - lower (%) Not available.

Vapor pressure 0.48 mm Hg @ 20°C

Vapor density > 1 (air = 1)

Relative density Not available.

Solubility(ies)

Solubility (water) Negligible

Partition coefficient Not Determined

(n-octanol/water)

Auto-ignition temperature635 °F (335 °C)Decomposition temperatureNot available.Viscosity1.5 cSt @ 25°C

Other information

Percent volatile 100 %

Specific gravity 0.74 - 0.78 @20°C

VOC 100 % per US State and Federal Consumer Product Regulations

CARB

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

Hazardous polymerization does not occur.

reactions

Conditions to avoid Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition Carbon oxides.

products

11. Toxicological information

Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.

Eve contact Direct contact with eyes may cause temporary irritation.

Material name: LPS® PF® Solvent

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Symptoms related to the

physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause an allergic skin reaction.

5600 - 6600 mg/kg

Dermatitis. Rash.

Information on toxicological effects

May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Acute toxicity

Test Results Components **Species**

d-Limonene (CAS 5989-27-5)

Acute Oral

LD50 Mouse

> Rat > 2000 mg/kg

Naphtha Petroleum, Hydrotreated Heavy (CAS 64742-48-9)

Acute

Dermal

LD50 Rabbit > 1900 mg/kg, 24 Hours

Inhalation

Vapor

LC50 Rat > 5000 mg/m3, 4 Hours

Oral

LD50 Rat 4820 mg/kg

Skin corrosion/irritation Serious eve damage/eve

irritation

Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause sensitization by skin contact.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

d-Limonene (CAS 5989-27-5) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ

toxicity - repeated

exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Chronic effects Prolonged inhalation may be harmful.

Further information Symptoms may be delayed.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Material name: LPS® PF® Solvent SDS US 61420 Version #: 01 Issue date: 07-18-2016

Components Species Test Results

d-Limonene (CAS 5989-27-5)

Aquatic

Crustacea EC50 Water flea (Daphnia pulex) 69.6 mg/l, 48 hours

Fish LC50 Fathead minnow (Pimephales promelas) 0.619 - 0.796 mg/l, 96 hours

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

d-Limonene 4.232

Mobility in soilNo data available.Other adverse effectsNone known.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

D003: Waste Reactive material

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82
Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Allowed with restrictions.

Other information

Passenger and cargo

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN1950 **UN number**

UN proper shipping name Aerosols, flammable, MARINE POLLUTANT

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s)

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes **EmS** F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Naphtha Petroleum, Hydrotreated Heavy (CAS 64742-48-9)

US. Massachusetts RTK - Substance List

Carbon Dioxide (CAS 124-38-9)

US. New Jersey Worker and Community Right-to-Know Act

Carbon Dioxide (CAS 124-38-9)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon Dioxide (CAS 124-38-9)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Material name: LPS® PF® Solvent

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Vac

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 07-18-2016

Version # 01

Disclaimer ITW Pro Brands cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless

specified in the text.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: LPS® PF® Solvent SDS US

61420 Version #: 01 Issue date: 07-18-2016