



Screw-On, Straight, Liquidtight Fitting



Non-Insulated



Insulated



Features

- No disassembly required for installation of LTQ (sizes 3/8" - 2")
- Tapered threaded male hub - NPT
- Compact, slim diameter
- Liquidtight/Raintight/Oiltight
- Suitable for wet locations
- Long ferrule prevents pullout and tight bend conduit pop-out
- RoHS compliant
- Use with Liquidtight Flexible Metal Conduit

Standard Materials

- Malleable Iron
- Nylon
- Steel ferrule
- Steel locknut

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: 514B
- Fed. Spec. A-A-50553
- NEMA: FB-1
- UL Listed File # E207875
- Suitable for use in the following hazardous locations under NEC, Class I, Division 2; Class II, Division 1 and 2; and Class III, Division 1 and 2

U.S. Patent No. 7.914.048

Catalog Number	Trade Size (in)	Dim A (in)	Dim B (in)	Dim C (in)	Master Pack	Weight Per C (lb)
Non-Insulated						
LTQ38KON	3/8	1.13	0.50	1.13	25	15.4
LTQ50KON	1/2	1.25	0.50	1.25	25	17.6
LTQ75KON	3/4	1.25	0.50	1.56	25	28.7
LTQ100KON	1	1.44	0.63	1.81	5	39.7
LTQ125KON	1 1/4	1.50	0.69	2.25	5	55.1
LTQ150KON	1 1/2	1.63	0.75	2.44	2	70.5
LTQ200KON	2	1.75	0.75	3.00	1	99.2
LT250KON*	2 1/2	2.19	1.06	4.06	5	363.8
LT300KON*	3	2.50	1.13	4.88	5	456.4
LT350KON*	3 1/2	2.69	1.19	5.44	5	668
LT400KON*	4	3.00	1.25	6.06	5	789.2
Insulated						
LTQ38-ICKON	3/8	1.13	0.56	1.13	25	15.6
LTQ50-ICKON	1/2	1.25	0.56	1.25	25	17.8
LTQ75-ICKON	3/4	1.25	0.56	1.56	25	28.9
LTQ100-ICKON	1	1.44	0.69	1.81	5	40.1
LTQ125-ICKON	1 1/4	1.50	0.75	2.25	5	55.7
LTQ150-ICKON	1 1/2	1.63	0.81	2.44	2	71.2
LTQ200-ICKON	2	1.75	0.81	3.00	1	100.2
LT250-ICKON*	2 1/2	2.19	1.06	4.06	5	367.4
LT300-ICKON*	3	2.50	1.25	4.88	5	460.9
LT350-ICKON*	3 1/2	2.69	1.31	5.44	5	674.7
LT400-ICKON*	4	3.00	1.38	6.06	5	797.1

* Note: Standard Liquidtight Fitting

