



## GA4030

### 4" ANGLE GRINDER Small Diameter Barrel Grip (Only 2-1/4")

- Powerful 6.0 AMP motor delivers 11,000 RPM
- Compact design at only 3.7 lbs.
- Labyrinth construction seals and protects motor and bearings
- Slide switch design with lock-on
- Ideal for welders, fabricators, masons, maintenance/repair and more

**Model GA4030 Includes:** 4" X3/16" Grinding Wheel, Bulk (741402-B), 4" Wheel Guard (125885-4), Lock Nut (194608-1), Lock Nut Wrench (782420-7), Side Handle (153504-2), Inner Flange (224377-1)

Grinding Wheel or Sanding Disc	4"
Wire Cup Brush	3"
No Load Speed	11,000 RPM
Spindle Thread	M10 x 1.25
AMPS	6
Lock-On: Yes	Lock-Off: No
Overall Length	10-1/2"
Net Weight	3.7 lbs.
Shipping Weight	6 lbs.



## GA4530

### 4-1/2" ANGLE GRINDER Small Diameter Barrel Grip (Only 2-1/4")

- Powerful 6.0 AMP motor delivers 11,000 RPM
- Compact design at only 4.0 lbs.
- Labyrinth construction seals and protects motor and bearings
- Slide switch design with lock-on

**Model GA4530 Includes:** 4 1/2" Grinding Wheel (741423-B), 4-1/2" Wheel Guard (122886-3), Lock Nut (194608-1), Lock Nut Wrench (782420-7), Inner Flange (224377-1), Side Handle (153504-2)

Grinding Wheel or Sanding Disc	4-1/2"
Wire Cup Brush	3-1/2"
No Load Speed	11,000 RPM
Spindle Thread	5/8" - 11 UNC
AMPS	6
Lock-On: Yes	Lock-Off: No
Overall Length	10-1/2"
Net Weight	4 lbs.
Shipping Weight	6 lbs.



## GA4534 AC/DC

### 4-1/2" PADDLE SWITCH ANGLE GRINDER Small Diameter Barrel Grip (Only 2-1/4")

- Powerful 6.0 AMP motor delivers 11,000 RPM
- Compact design at only 4.2 lbs.
- Labyrinth construction seals and protects motor and bearings
- Paddle switch with no lock-on
- AC/DC switch for use with alternative power sources

**Model GA4534 Includes:** 4 1/2" Grinding Wheel (741423-B), 4-1/2" Wheel Guard (122886-3), Lock Nut Wrench (782424-9), Side Handle (153504-2), Inner Flange (224399-1), Lock Nut (224568-4)

Grinding Wheel or Sanding Disc	4-1/2"
Wire Cup Brush	3-1/2"
No Load Speed	11,000 RPM
Spindle Thread	5/8" - 11 UNC
AMPS	6
Lock-On: No	Lock-Off: Yes
Overall Length	10-3/8"
Net Weight	4.2 lbs.
Shipping Weight	7.2 lbs.



## 9557NB AC/DC

### 4-1/2" ANGLE GRINDER AC/DC Switch for Use with Alternative Power Source

- 7.5 AMP motor delivers 10,000 RPM
- Labyrinth construction seals and protects motor and bearings from contamination
- Spindle lock for easy wheel changes
- Switch is located on side of the motor housing for operator convenience
- Small diameter barrel grip (only 2-1/2") for added comfort

**Model 9557NB Includes:** 4-1/2" x 7/8" x 1/4" Grinding Wheel, 36 Grit, General Purpose Metal (741424-8-1), 4-1/2" Wheel Guard (125273-5), Lock Nut (193465-4), Lock Nut Wrench (782422-3), Inner Flange (224399-1), Side Handle (153489-2)

Grinding Wheel or Sanding Disc	4-1/2"
Wire Cup Brush	3-1/2"
No Load Speed	10,000 RPM
Spindle Thread	5/8" - 11 UNC
AMPS	7.5
Lock-On: Yes	Lock-Off: No
Overall Length	10-5/8"
Net Weight	4.5 lbs.
Shipping Weight	6.3 lbs.



## 9557PB AC/DC

### 4-1/2" PADDLE SWITCH ANGLE GRINDER Large Flush-Mount Paddle Switch for Comfortable Operation

- Powerful 7.5 AMP motor for heavy professional grinding applications
- Small diameter barrel grip for added comfort
- Labyrinth construction seals and protects motor and bearings from contamination
- Lock-on/off feature for continuous operation
- AC/DC Switch for use with alternative power sources

**Model 9557PB Includes:** 4-1/2" x 7/8" x 1/4" Grinding Wheel, 36 Grit, General Purpose Metal (741424-8-1), 4-1/2" Wheel Guard (125273-5), Lock Nut (193465-4), Lock Nut Wrench (782422-3), Side Handle (153489-2), Inner Flange (224399-1)

Grinding Wheel or Sanding Disc	4-1/2"
Wire Cup Brush	3-1/2"
No Load Speed	10,000 RPM
Spindle Thread	5/8" - 11 UNC
AMPS	7.5
Lock-On: Yes	Lock-Off: Yes
Overall Length	10-3/4"
Net Weight	4.5 lbs.
Shipping Weight	6.5 lbs.

# PERFORMANCE DRIVEN



## COMFORT

Flush mount paddle switch



## 9564PC HIGH POWER 13 AMP

### 4-1/2" SJS™ PADDLE SWITCH ANGLE GRINDER Electronic Controller

- SJS™ technology is a mechanical clutch system that helps prevent motor and gear damage by allowing the drive shaft to slip
- Constant speed control automatically applies additional power to the motor to maintain speed under load
- Soft start suppresses start-up reaction for smooth start-ups and longer gear life
- Electronic current limiter helps protect the motor from overload

**Model 9564PC Includes:** 4-1/2" x 7/8" x 1/4" Grinding Wheel, 24 Grit, General Purpose Metal (741423-0-1), Side Handle (153489-2), "Tool-less" Wheel Guard (135107-4), Inner Flange (224399-1), Lock Nut (193465-4), Lock Nut Wrench (782424-9)

Grinding Wheel or Sanding Disc	4-1/2"
Wire Cup Brush	3-1/2"
No Load Speed	10,500 RPM
Spindle Thread	5/8" - 11 UNC
AMPS	13
Lock-On: No	Lock-Off: Yes
Overall Length	12-1/8"
Net Weight	5.3 lbs.
Shipping Weight	7.2 lbs.



## 9564P

### 4-1/2" SJS™ PADDLE SWITCH ANGLE GRINDER SJS™ Mechanical Clutch System Helps Prevent Motor and Gear Damage

- Powerful 10.0 AMP motor delivers more output and 10,500 RPM
- SJS™ technology is a mechanical clutch system that helps prevent motor and gear damage by allowing the drive shaft to slip
- Larger cooling fan and blades pull more air through the motor to help maintain lower operating temperature

**Model 9564P Includes:** Side Handle (153489-2), "Tool-less" Wheel Guard (135107-4), Inner Flange (224399-1), Lock Nut (193465-4), Lock Nut Wrench (782424-9)

Grinding Wheel or Sanding Disc	4-1/2"
Wire Cup Brush	3-1/2"
No Load Speed	10,500 RPM
Spindle Thread	5/8" - 11 UNC
AMPS	10
Lock-On: No	Lock-Off: Yes
Overall Length	12-1/8"
Net Weight	5.1 lbs.
Shipping Weight	6.5 lbs.