

## MB5A10C2

Article Number: 151-28529

Adhesive Bases, .35" Max tie width, .19" Hole Dia., 1.49" Length/Width, PA66, White, 100/pkg



### Base Data

Local Order Number MB5A10C2

Type MB5A

Color White (WH)

- Features and Benefits**
- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
  - Secures with rubber based adhesive backing and/or two or four screws.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Fixation Method (FF)** Screw Mounting and Adhesive

**Short Description** Adhesive Bases, .35" Max tie width, .19" Hole Dia., 1.49" Length/Width, PA66, White, 100/pkg

### Product Dimensions

Length L (imperial) 1.49 "

Length L (metric) 37.7 mm

Width W (imperial) 1.49 "

Width W (metric) 37.7 mm

Cable Tie Width Max (imperial) 0.35 "

Cable Tie Width max. (metric) 8.9 mm

Height H (imperial) 0.28 "

Height H (metric) 7.1 mm

Mounting Hole Diameter D (imperial) 0.19 "

Mounting Hole Diameter D (metric) 4.8 mm

Mounting Hole Centers (imperial) 1.0 "

Thickness of Adhesive TA (imperial) 0.031 "

Mounting Hole Centers (metric) 25.3 mm

Thickness of Adhesive TA (metric) 0.8 mm

### Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 1000 Pieces

Weight (Metric) 1.8 kg

### Material and Specifications

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Adhesive</b>	Synthetic rubber with base of polyethylene foam
<b>Shortcut Adhesive</b>	Synthetic rubber
<b>Adhesive Operating Temperature</b>	-4 °F to +122 °F (-20°C to +50°C)
<b>CSA Certified</b>	No
<b>Flammability</b>	UL94 V2 (excluding adhesive)
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes