



MDC (M12) Series Field Wireable Plugs

4, 5 & 8 Conductor MDC Series Field Wireable Plugs, 18-24/20-24AWG



Field Wireable Plugs | PG7 & PG9 Threads | IP67 Rating



# of Poles	Male Faceview	Wire AWG Rating	Cable O.D. Range	Male plugs		Female Plugs	
				Straight	Right Angle	Straight	Right Angle
4	 M12 x 1	18-24 AWG 250V 4A	3-6.5 mm	MDC-4MP-FW07	MDC-4MP-FW07-R	MDC-4FP-FW07	MDC-4FP-FW07-R
		18-24 AWG 250V 4A	4-8 mm	MDC-4MP-FW09	MDC-4MP-FW09-R	MDC-4FP-FW09	MDC-4FP-FW09-R
5	 M12 x 1	18-24 AWG 125V 4A	3-6.5 mm	MDC-5MP-FW07	MDC-5MP-FW07-R	MDC-5FP-FW07	MDC-5FP-FW07-R
		18-24 AWG 125V 4A	4-8 mm	MDC-5MP-FW09	MDC-5MP-FW09-R	MDC-5FP-FW09	MDC-5FP-FW09-R
8	 M12 x 1	20-24 AWG 60V 2A	3-6.5 mm	MDC-8MP-FW07	MDC-8MP-FW07-R	MDC-8FP-FW07	MDC-8FP-FW07-R
		20-24 AWG 60V 2A	4-8 mm	MDC-8MP-FW09	MDC-8MP-FW09-R	MDC-8FP-FW09	MDC-8FP-FW09-R

These connectors are easily wired by inserting the individual wires into the screw terminal contacts.

The connectors are water tight to IP67 and are fully mate-able with other M12 style connectors.

H


Micro-DC (M12) Series Cordsets

Male Field Wireable Plugs

Female Field Wireable Plugs



Male Straight



Male Right Angle



Female Straight



Female Right Angle

Specifications:

- Body: Black Polyamide
- Insulator: Black Polyamide
- Contacts: Copper Alloy with Gold Plating
- Coupling Nut: Nickel Plated Brass
- Seal: NBR
- Temperature: -25°C to +85°C (-13°F to +185°F)