

PN7c Multipin Plugs & Receptacles – 20A

UL/CSA Ratings

- **Voltage**
600 VAC Max/130 VDC*
- **Amperage Rating**
15A Current Interrupting
20A Non-Current Interrupting
! Capable of handling 4-20mA low current applications
- **Environmental Ratings**
IP66/IP67* (Poly/Metal)
- **Temperature Range**
Min -40°F/Max 140°F
See pg 253 for temps below -15°F.
- **Wiring Capacity**
Min 18 AWG Max 10 AWG
- **Certifications**
UL*, CSA*, CE*+
* Contact Customer Service
+ Poly/metal versions only

Receptacle (female)



Inlet (male)



! Don't forget to add installation accessories to your order

North American UL/CSA Configurations

Voltage	Polarity	Part #			Part #		
		Poly	Metal	Stainless Steel	Poly	Metal	Stainless Steel
600V	4P+G	01-P4041	09-P4041	09-P4041-SS	01-P8041	09-P8041	09-P8041-SS
600V	5P+G	01-P4051	09-P4051	09-P4051-SS	01-P8051	09-P8051	09-P8051-SS
600V	6P+G	01-P4061	09-P4061	09-P4061-SS	01-P8061	09-P8061	09-P8061-SS

For international configurations and ratings (IEC,CE) visit meltric.com/international-catalog or contact customer service at 800.433.7642.

Main Options



Reverse Interiors



Flush Mount
(replaces female casing)



Locking Pawl

Receptacle Options

Suffix

Inlet Options

Suffix

Reverse Interiors

Recept # - 001

Reverse Interiors

Inlet # - 001

With Flush Mount (poly only)

Recept # - 142

Locking Pawl

Recept # - 824-300

! See pages 230-239 for detailed information on these options

Order Example: 600V PN7c + Reverse Interiors
PN7c Receptacle 5P+G = 01-P4051-**001**