

DS100C Switch-Rated Plugs & Receptacles – 100A

UL/CSA Ratings

- Max Amperage & Voltage**
100A, 600 VAC
- Switch-Ratings (AC Only)**
Branch Circuit & Motor Circuit
Disconnect Switching
- Horsepower Ratings**

120V	1Ø	5 hp
240V	1Ø	10 hp
208V	3Ø	20 hp
240V	3Ø	20 hp
480V	3Ø	50 hp
600V	3Ø	50 hp
- Short Circuit Rating**
100kA Close & Withstand
Tested with RK1 current limiting fuses sized at 400% of the highest full load motor ampacity.
- Environmental Ratings**
Type 3R (Standard)
Type 4X (Optional)
- Temperature Range**
Min -40°F/Max 140°F
See pg 253 for temps below -15°F.
- Wiring Capacity**
Min 10 AWG Max 2 AWG
Aux Contacts - Max 14 AWG
Based on THHN wire sizes
- Certifications**
UL 2682, UL 1682, CSA 182.1

Receptacle (female)



Inlet (male)



! Don't forget to add installation accessories to your order

North American UL/CSA Configurations

Voltage	Polarity	Part #		Part #	
		Poly	Metal	Poly	Metal
120V	1P+N+G	33-64235-C-K16	37-64235-C-K16	33-68235-C-K16	37-68235-C-K16
120 208V	3P+N+G	33-64237-C-K16	37-64237-C-K16	33-68237-C-K16	37-68237-C-K16
125V	1P+N+G	33-64175-C-K07	37-64175-C-K07	33-68175-C-K07	37-68175-C-K07
125 250V	2P+N+G	33-64176-C-K07	37-64176-C-K07	33-68176-C-K07	37-68176-C-K07
208V	2P+G	33-64232-C-K16	37-64232-C-K16	33-68232-C-K16	37-68232-C-K16
208V	3P+G	33-64233-C-K16	37-64233-C-K16	33-68233-C-K16	37-68233-C-K16
250V	2P+G	33-64172-C-K07	37-64172-C-K07	33-68172-C-K07	37-68172-C-K07
250V	3P+G	33-64173-C-K07	37-64173-C-K07	33-68173-C-K07	37-68173-C-K07
277V	1P+N+G	33-64245-C-K04	37-64245-C-K04	33-68245-C-K04	37-68245-C-K04
277 480V	3P+N+G	33-64247-C-K04	37-64247-C-K04	33-68247-C-K04	37-68247-C-K04
347 600V	3P+N+G	33-64187-C-K14	37-64187-C-K14	33-68187-C-K14	37-68187-C-K14
480V	2P+G	33-64242-C-K04	37-64242-C-K04	33-68242-C-K04	37-68242-C-K04
480V	3P+G	33-64243-C-K04	37-64243-C-K04	33-68243-C-K04	37-68243-C-K04
600V	2P+G	33-64182-C-K14	37-64182-C-K14	33-68182-C-K14	37-68182-C-K14
600V	3P+G	33-64183-C-K14	37-64183-C-K14	33-68183-C-K14	37-68183-C-K14

For international configurations and ratings (IEC, CE) visit meltric.com/international-catalog or contact customer service at 800.433.7642.

Main Options



Auxiliary/Pilot Contacts



Mushroom Pawl



Padlock Pawl



Closed Lid Configuration
Recommended for cord applications to keep lid tucked in to avoid damage.

Receptacle Options

Suffix

Inlet Options

Suffix

With 2 Auxiliary/Pilot Contacts	Recept # - 972	With 2 Auxiliary/Pilot Contacts	Inlet # - 972
With 3 Auxiliary/Pilot Contacts	Recept # - 263	With 3 Auxiliary/Pilot Contacts	Inlet # - 263
With 4 Auxiliary/Pilot Contacts	Recept # - 264	With 4 Auxiliary/Pilot Contacts	Inlet # - 264
Type 4X & closed lid configuration	Recept # - 4X	Type 4X watertightness	Inlet # - 4X
Straight Insertion	Recept # - 352	Self-Ejecting Plug Release	Inlet # - 338
Self-Ejecting Connector Release	Recept # - 354	With No Lockout Hole	Inlet # - A155
Mushroom Pawl	Recept # - 375	For Auxiliary Switch*	Inlet # - NNF
Padlock Pawl	Recept # - 843		
Padlockable Mushroom Pawl	Recept # - 375-843		
Locking Mushroom Pawl	Recept # - 845		
Metal Pawl (on poly receptacle)	Recept # - 824		
Closed Lid Configuration	Recept # - NC		
With Auxiliary Switch	Recept # - 270+		
180° Opening Lid (metal only)	Recept # - 180++		

Notes: * Order inlet with P+N+G configuration and receptacle with P+G configuration.

! See pages 230-239 for detailed information on these options

Notes: * Not UL/CSA listed.
++ Required when mating to rigid mounted male inlet.

Order Example: 480V DS100C + 2 auxiliary contacts
DS100C Poly inlet 3P+G = 33-68243-C-K04-972