INSTALLATION ACCESSORIES - SIZE 1

v
ш
Z
⋖
I

HANDLE w/N	PT	Part # Poly	Part # Metal
5	1/2"	511P0N05	591P0N05
	3/4"	511P0N07	591P0N07
	1"	511P0N10	591P0N10
9			

HANDLE w/CORD GRIP Cable Range		Poly	Metal
	.438500"	711P0BP3	791P0BS3
	.500562"	711P0BP4	791P0BS4
	.562625"	711P0BP5	791P0BS5
	.625750"	711P0CP4	791P0CS4

.357

511P0D18

Finger draw plates are recommended for easier connector closure on cord to cord

1	
0	1

.20 - .82" 511P0D21



.35 - .70"

511P6D18

For available cord grips, see pg 178.



Cable Range	NPT	
.312625	1/2"	NPT sizes are determined by the cab diameter and third party cord grip.
.438812	3/4"	
.660 - 1.000	1"	

ANGLES

30° for MB Box 511M3 0° 591M0 * Base measures approximately 4.2" x 2.7". Due to the variation in sizes of FS boxes, FS/FD Box 30° 791M3FS please verify that your FS box matches our dimensions, if not call Customer Service for other solutions. 45° 591M4

BOXES

POLY CONDUIT	ENTRY w/NP		art#	
	30°	1/2"	511B3N05	
* 6.7 in ³	30°	3/4"	511B3N07	* Interior volume with receptacle installed.
POLY WALL BO	X w/NPT			
	70°	1/2" - 1 1/4"	511C7000	70° poly boxes are
* 84.0 in ³				not drilled. Contact customer service if factory drilled is required.
04.0 III				* Interior volume with receptacle installed.
POLY ANGLE WITH ALUMINUM WALL BOX w/NPT				
	70°	1/2"	711C7N05	
	70°	3/4"	711C7N07	
	70°	1"	711C7N10	* Interior volume with receptacle installed.

70°

70°



* 75.0 in³

7T1F0N05	1/2"	0°
7T1F0N07	3/4"	0°
7T1F0N10	1"	0°
7T1F0N12	1 1/4"	0°

1 1/4"

1 1/2"



30°	1/2"	711C3N05	
30°	3/4"	711C3N07	
30°	1"	711C3N10	
30°	1 1/4"	711C3N12	

* Interior volume with receptacle installed.

NPT on top or bottom (if rotated). For other NPT configurations, contact customer service.

ISCELLANEOUS ACCESSORIES



61-1A346

Set of Two (2) Recommended for cord to cord assembly applications, for easier connector closure.

711C7N12

711C7N15



61-1A426 For Male Devices Only.



For Male Devices Only. 61-1A826



SD18

Klein 608-3 1/8" cabinet with 3" round shank.



see pg 175

Mount to existing boxes.



LP-843

Requires Padlockable Pawl option (-843) on receptacle.