

WEPBA 17-150 Quick DS (600553420) Angle grinder
Cardboard box

Order no. 600553420
EAN 4007430318152



Representative picture



- Maximum productivity: 1,700 watt angle grinder with the power of a large grinder and the compactness of a small one for quickest material removal for industrial applications
- Steel ring for carabiner to secure the angle grinder from falling when working at great heights
- Longer service life, more drive: the Metabo LongLife Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Tacho-Constamatic (TC)-Full Wave Electronics: fast work progress by means of constant speed under load
- Quick disc change at the push of a button without tools, with the Metabo M-Quick System
- Tool-free adjustable guard; twist-proof
- Low vibration side handle Metabo VibraTech (MVT)
- Best anti-vibration system: integrated autobalancer for up to 50% less hand-arm vibrations, longer service life of the machine and up to twice the service life of the grinding discs
- Paddle switch with dead-man function: safe to operate due to an ergonomically integrated non-slip switch
- Fastest brake system for the highest user protection: patented, mechanical disc brake stops the disc after switching off within 2 seconds, even in the event of a power cut
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly - for maximum user protection and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor
- Steel eye for carabiner to secure the angle grinder from falling when working at great heights

Technical values

Parameters

| | |
|------------------------------|---------------|
| Amps | 14.5 AMPS |
| Grinding wheel Ø | 6 " |
| Output power | 1000 W |
| No-load speed | 9600 RPM |
| Revolutions at rated load | 9600 RPM |
| Torque | 38 in-lbs |
| Spindle thread | 5/8" - 11 UNC |
| Weight (without power cable) | 6.2 lbs |
| Cable length | 8 ft |

Vibration

| | |
|------------------------------|----------------------|
| Surface grinding | 4.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Grinding with sandpaper | 4.2 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|-----------|
| Sound pressure level | 93 dB(A) |
| Sound power level (LwA) | 104 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Guard
Clip-on Cutting Wheel Guard
Inner support flange
M-Quick flange nut
Side handle Metabo VibraTech (MVT)