

MIZFUEL 1/4" Hex 2-Speed Screwdriver Kit 2402-22 (2402-20 Tool-Only)

Specifications: Peak Torque 325 in-lbs RPM 0-450/0-1,700

Chuck Type 1/4" Hex Quick Change 6-5/8" Length Weight 2.3 lbs

Includes: (2) M12[™] REDLITHIUM[™] 2.0 Compact Battery Packs, Belt Clip, Charger, Carrying Case

M12[™] 1/4[¶] Hex **Screwdriver Kit**

2401-22 (2401-20 Tool-Only) Specifications:

		WARRANT
Peak Torque	175 in-lbs	
RPM	0 – 500	
Chuck Type	1/4" Hex Quick Change	
Length	6-1/2"	
Weight	2.0 lbs	

Includes: (2) M12[™] REDLITHIUM[™] Compact Battery Packs, Belt Clip, Charger, Soft Carrying Case



M12 FUEL 1/2" Hamme 2404-22 (2404-20 Tool Specifications:		
Peak Torque	350 in-lbs	
RPM	0 - 450 / 0 - 1,700	
BPM	0 – 25,500	
Chuck Type	1/2" Metal Single Sleeve	
Length	7-3/4"	
Weight	3.0 lbs	

Includes: (1) M12[™] REDLITHIUM[™] XC4.0 Extended Capacity Battery Pack, (1) M12[™] REDLITHIUM[™] 2.0 Compact Battery Pack, Belt Clip, Charger, Carrying Case

M12[™] 3/8[¶] Right Angle **Drill/Driver Kit**

2415-21 (2415-20 Tool-Only) Specifications:

specifications	
Peak Torque	100 in-lbs
RPM	0 – 800
Clutch Settings	11 Settings plus Drill Mo
Chuck Type	3/8" Single Sleeve
Head Profile	3-3/4"
Weight	2.4 lbs

Includes: (1) M12[™] REDLITHIUM[™] Compact Battery Pack, 11 Charger, Soft Carrying Case



Specifications:

Peak Torque	275 in-lbs	WARF
RPM	0 - 400 / 0 - 1,500	
Chuck Type	1/4" Hex Quick Change	
Length	6-3/4"	
Weight	2.2 lbs	

Includes: (2) M12[™] REDLITHIUM[™] Compact Battery Packs, Belt Clip, Charger, Soft Carrying Case

M12 [™] 3/8" Drill/Drive	er Kit
2407-22 (2407-20 T Specificatio	
Peak Torque	275 in-lbs
RPM	0 - 400 / 0 - 1,500
Chuck Type	3/8" Metal Single Slee
Length	7-3/8"
Weight	2.5 lbs

Includes: (2) M12[™] REDLITHIUM[™] Compact Battery Packs, Belt Clip, Charger, Carrying Case

03-22 (2403-20	Γool-Only)	TOOL BATTERY BATTERY
Specificatio	ns:	532 Vear Vear Vear
Peak Torque	350 in-lbs	WARRANTY
RPM	0-450/0-1,	700
Chuck Type	1/2" Metal Sing	le Sleeve
Length	7-3/4"	
Weight	2.9 lbs	

	M12™ 3/8" Hammer Drill/Driver Kit		
240	8-22 (2408-20 Tool-0	Only)	1
Sp	ecifications:	075	2
Pe	eak Torque	275 in-lbs	ī
RF	PM	0 - 400 / 0 - 1,500	
BF	PM	0 - 22,500	
Ch	nuck Type	3/8" Metal Single Sleeve	
Le	ength	7-1/2"	
We	eight	2.7 lbs	

Belt Clip, Charger, Carrying Case



M2 FUEL

RPM (2 Modes)

Chuck Type

Lenath

Weight

1/4" Hex Impact Driver Kit 2453-22 (2453-20 Tool-Only)

•	• ·
Specifications:	
Fastening Torque (2 Modes)	175 / 1,200 ir
IPM	0 - 3.550



Includes: (2) M12[™] REDLITHIUM[™] 2.0 Compact Battery Packs, Belt Clip, Charger, Carrying Case

2.3 lbs

6"



M12 FUEL 1/4" Impact 2452-22 (2452-20 Tool- Specifications:		TOOL BATTERY
- Fastening Torque (2 Mod	es) 10 / 42 ft-lbs	WARRANTY
IPM	0 - 4,000	
RPM (2 Modes)	0 - 1,200 / 0 - 2,650	
Anvil	1/4" Friction Ring	
Length	5-3/4"	
Weight	2.1 lbs	

Includes: (2) M12[™] REDLITHIUM[™] 2.0 Compact Battery Packs, Belt Clip, Charger, Carrying Case

M12 FUEL		
3/8" Impact	Wrench Kit	
2454-22 (2454-20 Tool	-Only)	TOOL
Specifications:		
Fastening Torque (2 Mod	des) 17 / 117 ft-lbs	WARRA
IPM	0 – 3,500	
RPM (2 Modes)	0 - 1,200 / 0 - 2,650	
Anvil	3/8" Friction Ring	
Length	6-1/2"	
Weight	2.4 lbs	

Includes: (2) M12[™] REDLITHIUM[™] 2.0 Compact Battery Packs, Belt Clip, Charger, Carrying Case

M12[™] 1/4[¶] Ratchet Kit

Weight

2456-21 (2456-20 Tool-Only) **Specifications:** Fastening Torque 30 ft-lbs RPM 0 - 250 1/4" Ball Detent Anvil 3/4" Head Profile Length 10-3/4"



1.9 lbs Includes: (1) M12[™] REDLITHIUM[™] Compact Battery Pack, Charger, Soft Carrying Case



eve

2" Drill/Driv 03-22 (2403-20 Tool-(pecifications:	_	DOL BATTERY BATTERY BATTERY BATTERY BATTERY BATTERY BATTERY BATTERY
eak Torque	350 in-lbs	WARRANTY
PM	0 - 450 / 0 - 1,700	
huck Type	1/2" Metal Single Slee	eve
ength	7-3/4"	
/eight	2.9 lbs	
Cludes: (1) M12 [™] REDLITHIUM [™] XC4.0 Extended Capacit ttery Pack, (1) M12 [™] REDLITHIUM [™] 2.0 Compact Battery Pac It Clip, Charger, Carrying Case		

112 [™] 3/8" Hammer Drill/Driver Kit		
08-22 (2408-20 Tool-0 pecifications:	Only)	
Peak Torque	275 in-lbs	
RPM	0 - 400 / 0 - 1,500	
BPM	0 - 22,500	
Chuck Type	3/8" Metal Single Sleeve	
_ength	7-1/2"	

Includes: (2) M12[™] REDLITHIUM[™] Compact Battery Packs,









M12[™] 1/4[¶] Hex Impact **Driver Kit**



2462-22 (2462-20 Tool-Only) **Specifications:**

Fastening Torque	1,000 in-lbs
IPM	0 - 3,300
RPM	0 - 2,500
Chuck Type	1/4"
Length	6-1/2"
Weight	2.3 lbs

Includes: (2) M12[™] REDLITHIUM[™] Compact Battery Packs, Belt Clip, Charger, Carrying Case


M12[™] 1/4[¶] Impact Wrench Kit

2461-22 (2461-20 Tool-Only)	
Specifications:	

•		
Fastening Torque	38 ft-lbs	
IPM	0 - 3,800	
RPM	0 – 2,500	
Anvil	1/4" Friction Ring	
Length	6"	
Weight	2.1 lbs	

Includes: (2) M12[™] REDLITHIUM[™] Compact Battery Packs, Belt Clip, Charger, Carrying Case

M12[™] 3/8["] **Impact Wrench Kit**



Fastening Torque (2 Modes) 1,200 in-lbs / 100 ft-lbs IPM 0 - 3,300 RPM 0 - 2,500 Chuck Type 3/8" Friction Ring 6-1/2" Length



2.3 lbs Includes: (2) M12[™] REDLITHIUM[™] Compact Battery Packs, Belt Clip, Charger, Carrying Case

M12[™] 3/8[∥] Ratchet Kit

2457-21 (2457-20 Tool-Only) Specifications:

	-	
Fastening Torque	35 ft-lbs	
RPM	0 – 250	Ū
Anvil	3/8" Ball Detent	
Head Profile	3/4"	
Length	10-3/4"	
Weight	1.9 lbs	





Includes: (1) M12[™] REDLITHIUM[™] Compact Battery Pack, (1) 3/8" to 1/4" Adapter, Charger, Soft Carrying Case





Weight