

## M18FUEL

# **1/4" Hex Impact Driver Kit**

2653-22, 2653-22CT (265	3-20 Tool-Only)	DOL BATTERY BATTERY	
Specifications:			1
Fastening Torque (3 Modes)	200 / 700 / 1,600 in-lbs	WARRANTY	
IPM	0 - 3,600		
RPM (3 Modes)	0-850/0-2,100/0-2	2,900	-1
Chuck Type	1/4" Hex Quick Change		
Length	5-1/2"		
Weight (CT / XC Pack)	3.0 lbs / 3.6 lbs		

Includes: 2653-22 (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC4.0 Extended Capacity Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case; 2653-22CT Includes (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> 2.0 Compact Battery Packs

### M18FUEL 3/8" Impact Wrench Kit

3/0"	mpac	LANIG	
2654-22.	2654-22CT	(2654-20	Tool-Only)

Specifications:
-----------------

-	1-44
Fastening Torque (3 Modes)	30 / 75 / 200 ft-lbs
IPM	0 – 3,100
RPM (3 Modes)	0-900/0-1,600/0-2,400
Anvil	3/8" Friction Ring
Length	6"
Weight (CT / XC Pack)	3.2 lbs / 3.8 lbs

Includes: 2654-22 (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC4.0 Extended Capacity Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case; 2654-22CT Includes (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> 2.0 Compact Battery Packs

### M18 FUEL Www.web.Kid

1/2" impact wrench	NIT
2655-22 (2655-20 Tool-Only)	
Specifications:	

specifications.	
Fastening Torque (3 Modes)	80 / 120 / 210 ft-lbs
IPM	0 - 3,100
RPM (3 Modes)	0-1,700/0-2,000/0-2,400
Anvil	1/2" Pin Detent
Length	6"
Weight	3.9 lbs

Includes: (2) M18™ REDLITHIUM™ XC4.0 Extended Capacity Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

# M18 FUEL

1/2"	Imp	bact	Wrench	Kit
2655B-2	22 (265	55B-20 T	ool-Only)	

### **Specifications:**

Fastening Torque (3 Modes)	80 / 120 / 210 ft-lbs
IPM	0 – 3,100
RPM (3 Modes)	0-1,700/0-2,000/0-2,400
Anvil	1/2" Ball Detent
Length	6"
Weight	3.9 lbs

Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC4.0 Extended Capacity Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

### M18<sup>™</sup> Right Angle **Impact Driver Kit** 2667-22 2667-21CT (2667-20 Tool-Only)

2667-22, 2667-21C1 (2667-20 100I-0
Specifications:
Fastaning Targue (0 Madee) 050 / 675

Fastening Torque (2 Modes)	350 / 675 in-lbs
IPM	0 - 2,400 / 0 - 3,400
RPM	0 - 1,500 / 0 - 2,250
Chuck Type	1/4" Hex
Length (CT / XC Pack)	13-1/4" / 14-1/8"
Weight (CT / XC Pack)	3.3 lbs / 3.9 lbs

Includes: 2667-22 (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC Extended Capacity Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case; 31 2667-21CT Includes (1) M18™ REDLITHIUM™ Compact Battery Pack

### M18<sup>™</sup> 1/4<sup>¶</sup> 2-Speed **Impact Driver Kit**

2657-22, 2657-22CT (2657-20 Tool-Only) **Specifications** 

532 YEAR YEAR YEAR

specifications.	YEAR YEAR
Fastening Torque	1,500 in-lbs
IPM	0-3,450
RPM	0 - 2,750
Chuck Type	1/4" Hex Quick Change
Length	5-1/2"
Weight (CT / XC Pack)	3.1 lbs / 3.8 lbs

Includes: 2657-22 (2) M18™ REDLITHIUM™ XC Extended Capacity Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case; 2657-22CT Includes (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> Compact Battery Packs

M18 <sup>™</sup> 3/8 <sup>™</sup> Co Impact Wrend 2658-22, 2658-22CT (265 Specifications:	ch Kit	Ē
Fastening Torque	167 ft-lbs	_
IPM	0 – 3,350	
RPM	0 - 2,450	

2658-22CT



	3/8" Friction Ring	
	6"	
/ XC Pack)	3.4 lbs / 4.1 lbs	
	M18 <sup>™</sup> REDLITHIUM <sup>™</sup> XC Ilti-Voltage Charger, Carry	
	8™ REDLITHIUM™ Compa	

M18 <sup>™</sup> 1/2" Compact Impact Wrench Kit		
2659-22 (2659-20 Tool- Specifications:	-Only)	
Fastening Torque	183 ft-lbs	WARRANTY
IPM	0 - 3,350	
RPM	0 - 2,450	
Anvil	1/2" Pin Detent	
Length	6"	
Weight	4.1 lbs	

Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC Extended Capacity Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case



M18 <sup>™</sup> Right Ang Impact Wrench 2668-22, 2668-21CT (2668- Specifications:	20 Tool-Only)
Fastening Torque (2 Modes)	30 ft-lbs / 60 ft-lbs
IPM	0 - 2,400 / 0 - 3,400
RPM	0 - 1,500 / 0 - 2,250
Chuck Type	3/8"
Length (CT / XC Pack)	13-1/4" / 14-1/4"

Weight (CT / XC Pack) 3.3 lbs / 3.9 lbs

Includes: 2668-22 (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC Extended Capacity Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case; 2668-21CT Includes (1) M18<sup>™</sup> REDLITHIUM<sup>™</sup> Compact Battery Pack



#### M18 FLIEL **1/2" High Torque Impact** Wrench w/ Pin Detent Kit 2762-22 (2762-20 Tool-Only) VEAR Specifications: Max Fastening Torque (2 Modes) 350 / 600 ft-lbs 900 ft-lbs Nut-Busting Torque IPM / RPM (2 Modes) 0-2,300; 0-1,200/0-1,700 1/2" Pin Detent Anvil 8-3/4" Lenath

Weight

Weight

Length Weight

7.0 lbs Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC4.0 Extended Capacity Battery Packs, Multi-Voltage Charger, Carrying Case

#### M18 FUEL 1/2" High Torque Impact Wrench w/ Friction Ring Kit 2763-22 (2763-20 Tool-Only) 3 Specifications: YEAR YEAR Max Fastening Torque (2 Modes) 100 / 700 ft-lbs Nut-Busting Torque 1,100 ft-lbs IPM / RPM (2 Modes) 0-2,300; 0-350/0-1,700 Anvil 1/2" Friction Ring Length Q" Weight 7.2 lbs

Includes: (2) M18™ REDLITHIUM™ XC4.0 Extended Capacity Battery Packs, Multi-Voltage Charger, Carrying Case

MTBFUEL		
3/4" High Torque Impact		
Wrench w/ Friction Ring Kit		
2764-22 (2764-20 Tool-Only)	TOOL BATTERY	
Specifications:	53	
Max Fastening Torque (2 Modes)	375 / 750 ft-lbs	
Nut-Busting Torque	1,200 ft-lbs	
IPM / RPM (2 Modes)	0-2,300; 0-1,200/0-1,700	
Anvil	3/4" Friction Ring	
Length	9"	

7.3 lbs Includes: (2) M18™ REDLITHIUM™ XC4.0 Extended Capacity Battery Packs, Multi-Voltage Charger, Carrying Case

### M18 FUEL 7/16" Hex Utility **Impacting Drill Kit** 2765-22 (2765-20 Tool-Only) Specifications: Max Fastening Torque IPM / RPM (2 Modes) Anvil

e (2 Modes)	300 / 500 ft-lbs	WARRANTY	
	0-2,300; 0-1,200	/ 0 – 1,700	
	7/16" Hex		-
	8-3/4"		
	7.1 lbs		

Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC4.0 Extended Capacity Battery Packs, AC/DC Charger, Hanger Ring, Banger Bracket, Contractor Bag

Fastening forque	TOT IL-IDS	
IPM	0 – 3,350	
RPM	0 - 2,450	
Anvil	3/8" Friction Ring	
Length	6"	
Weight (CT / XC Pack)	3.4 lbs / 4.1 lbs	
Includes: 2658-22 (2) M18 <sup>™</sup> REDLITHIUM <sup>™</sup> XC Extend Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Ca		





### M18<sup>™</sup> 1/2<sup>®</sup> High Torque **Impact Wrench** w/ Pin Detent Kit 2662-22 (2662-20 Tool-Only)

Specifications:

Fastening Torque	450 ft-lbs
Breakaway Torque	640 ft-lbs
RPM / IPM	0 - 1,900 / 0 - 2,200
Anvil	1/2" Pin Detent
Length	8-7/8"
Weight	6.7 lbs



Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC Extended Capacity Battery Packs, Multi-Voltage Charger, Carrying Case

### M18<sup>™</sup> 1/2<sup>®</sup> High Torque Impact Wrench w/ Friction Ring Kit

2663-22 (2663-20 Tool-Only) Specifications:

Fastening Torque	450 ft-lbs
Breakaway Torque	640 ft-lbs
RPM / IPM	0 - 1,900 / 0 - 2,200
Anvil	1/2" Friction Ring
Length	8-7/8"
Weight	6.7 lbs



Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC Extended Capacity Battery Packs, Multi-Voltage Charger, Carrying Case

### M18<sup>™</sup> 3/4<sup>®</sup> High Torque **Impact Wrench** w/ Friction Ring Kit 2664-22 (2664-20 Tool-Only)

### **Specifications:**

M18<sup>™</sup> 7/16<sup>∎</sup> Hex

•	
Fastening Torque	525 ft-lbs
Breakaway Torque	700 ft-lbs
RPM / IPM	0 - 1,900 / 0 - 2,200
Anvil	3/4" Friction Ring
Length	9"
Weight	6.8 lbs



Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC Extended Capacity Battery Packs, Multi-Voltage Charger, Carrying Case







Anvil

Length

Weight

### **Utility Impacting Drill Kit** 2665-22 (2665-20 Tool-Only) Specifications: Fastening Torque 350 ft-lbs 0-1,900/0-2,200 RPM / IPM



Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC Extended Capacity Battery Packs, Multi-Voltage Charger, Contractor Bag

7/16" Hex

9-1/2"

7.0 lbs





