## General-Purpose Cable Ties and Accessories

Cable Tie Mounting Bases

- ¾" and 1" mounts for use with 18# through 50# tensile cable ties

- Supplied on rubber-based adhesive

- Available in 6.6 natural nylon and 6.6 black weather-resistant nylon

- UL94V-2 flammability (clip)

Note: *See product expiration date on package. Periodically check product for adhesion and replace as needed. Product is for wire management only and is not intended for use as a primary support of wire, cable, etc.*

CAT. NO.	MOUNT METHOD	COLOR	PKG. QTY.
¾" x ¾" Sizes			
MPNY-750-9-C	Synthetic Rubber Adhesive	Natural	100
MPNY-750-9-D	Synthetic Rubber Adhesive	UV Black	500
1" x 1" Sizes			
MPNY-1000-9-C	Synthetic Rubber Adhesive	Natural	100
MPNY-1000-0-C	Synthetic Rubber Adhesive	UV Black	100

For use with 18–50 lb. Cable Ties

– Mounting Surface should be cleaned with alcohol based (IPA) cleaner before application

– Allow 15 minutes setup for maximum performance

Accepts cable ties up to 50-lb. tensile strength!

Adhesive Mounting Cradle

- Supplied on closed cell foam with synthetic rubber-based adhesive

- Use #6 self-tapping screw for added strength if desired

STD. PKG. CAT. NO.	BULK PKG. CAT. NO.	MATERIAL	H HEIGHT IN./MM	L LENGTH IN./MM	W WIDTH IN./MM	SLOT HEIGHT IN./MM	SLOT WIDTH IN./MM	MOUNT METHOD	STD. PKG. QTY.	BULK PKG. QTY.
MCNY-1250-9-C	**MCNY-1250-9-D**	Natural Nylon 6.6	.285/7.24	1.250/31.75	1.000/25.4	.090/2.29	.300/7.62	SRA Adhesive*	100	500

*Synthetic Rubber Adhesive

Note: *See product expiration date on package. Periodically check product for adhesion and replace as needed. Product is for wire management only and is not intended for use as a primary support of wire, cable, etc.*

www.tnb.com

United States
Tel: 901.252.8000
800.816.7809
Fax: 901.252.1354

Technical Services
Tel: 888.862.3289

Thomas&Betts

C-65