

# COPPER TUBE • HVACR



Streamline® Copper Tube provides the strength, precision and cleanliness needed for the demanding conditions of HVAC and refrigeration applications. Preferred throughout the industry, our products have set the benchmark for HVACR copper tube. Streamline® Nitrogenized® ACR Copper Tube is pressurized with nitrogen to provide maximum protection against the formation of harmful oxides normally formed during brazing operations. Reduction of these oxides greatly reduces system contamination. Streamline® Refrigeration Service Tube is of a consistent dead soft temper, bright, thoroughly dried/dehydrated and packed in shrink wrapping plus individual cartons for the highest level of protection.



- UL Recognized to 700 PSI (select diameters)
- Made to applicable ASTM standard B280
- Made in the USA

## Copper Tube • Refrigeration

ACR TUBE Nitrogenized® thru 3-1/8" only		
O.D. Dia.	Hard Lengths	
	Standard ACR Type L	Heavy Wall ACR Type K
3/8"	10 ft, 20 ft †	10 ft, 20 ft †
1/2"	10 ft, 20 ft †	10 ft, 20 ft †
5/8"	10 ft, 20 ft †	10 ft, 20 ft †
3/4"	10 ft, 20 ft †	10 ft, 20 ft †
7/8"	10 ft, 20 ft †	10 ft, 20 ft †
1-1/8"	10 ft, 20 ft †	10 ft, 20 ft †
1-3/8"	10 ft, 20 ft †	10 ft, 20 ft †
1-5/8"	10 ft, 20 ft	10 ft, 20 ft †
2-1/8"	10 ft, 20 ft	10 ft, 20 ft †
2-5/8"	10 ft, 20 ft	10 ft, 20 ft †
3-1/8"	10 ft, 20 ft	10 ft, 20 ft
3-5/8"	10 ft, 20 ft	10 ft, 20 ft
4-1/8"	10 ft, 20 ft	10 ft, 20 ft
5-1/8"	10 ft, 20 ft	10 ft, 20 ft
6-1/8"	10 ft, 20 ft	10 ft, 20 ft
8-1/8"	10 ft, 20 ft	10 ft, 20 ft

REFRIGERATION SERVICE TUBE	
O.D. Dia.	Soft Coils
1/8"	50 ft, 100 ft †
3/16"	50 ft, 100 ft †
1/4"	50 ft, 100 ft †
5/16"	50 ft, 100 ft †
3/8"	50 ft, 100 ft †
1/2"	50 ft, 100 ft †
5/8"	50 ft, 100 ft †
3/4"	50 ft, 100 ft †
7/8"	50 ft, 100 ft †
1-1/8"	50 ft, 100 ft †
1-3/8"	50 ft, 100 ft
1-5/8"	50 ft, 100 ft

O.D. Dia. 1/4"	Wall Thickness .025"		Wall Thickness .032"	
	Hard Lengths	Soft Lengths	Hard Lengths	Soft Lengths
	10 ft, 20 ft	10 ft, 20 ft	10 ft, 20 ft	10 ft, 20 ft

Temperature Control Tube is not recommended for forming or bending purposes.

Temperature Control Tube order quantities are in 2000 ft. per box increments.

Standard ACR Copper Tube is produced from Type L Copper Tube. Heavy Wall ACR Copper Tube produced from Type K Copper Tube is available upon request.