







ROOFING

ROOFING NAILS are used for applying roofing asphalt shingles, insulation board, and felt to wood substrates. The large head and heavier shank gauge provide greater holding power. Pro-Fit® Roofing nails come in a variety of styles to fit job requirements.

NAIL TYPE	PROFILE	APPLICATION
<p>ROOFING</p> <ul style="list-style-type: none"> • Large flat head for greater holding power • Heavy gauge, round, smooth shank provides greater resistance to bending • Available with ring shank for superior holding power and increased pull-out resistance • Diamond point • Electro Galvanized or Hot Dipped Galvanized to enhance corrosion resistance; and Stainless Steel for superior corrosion resistance 		<ul style="list-style-type: none"> • For applying asphalt shingles, insulation board and felt to wood substrates
<p>COPPER</p> <ul style="list-style-type: none"> • Large flat head for greater holding power • Round, smooth copper shank bends easier than other nails for less worry about breaking, regardless of temperature • Diamond point • Solid copper enhances corrosion resistance 		<ul style="list-style-type: none"> • For copper flashing, tile and slate roofing, gutters and downspouts, or other decorative copper roofing elements
<p>LEAD HEAD</p> <ul style="list-style-type: none"> • Head flattens out with impact making a leakproof joint when driven through a metal roof • Smooth, heavy shank provides greater resistance to bending • Diamond point • Brite finish 		<ul style="list-style-type: none"> • For use with corrugated steel roofing and siding
<p>NEO ROOF</p> <ul style="list-style-type: none"> • Large flat head for greater holding power • Neoprene washer provides an effective waterproof seal • Heavy gauge provides greater resistance to bending • Ring shank offers greater holding power and increased pull-out resistance • Diamond point • Electro Galvanized or Hot Dipped Galvanized to enhance corrosion resistance 		<ul style="list-style-type: none"> • For steel roofing, corrugated aluminum, fiberglass and plastic panel roofing and siding • Not for use with ACQ or CA
<p>WOODEN SHINGLE</p> <ul style="list-style-type: none"> • Large flat head for greater holding power • Heavy, smooth shank provides greater resistance to bending • Diamond point • Hot Dipped Galvanized to enhance corrosion resistance 		<ul style="list-style-type: none"> • For applying wood shingles; nails should be long enough to penetrate sheathing at least 3/4"
<p>TIN TABS</p> <ul style="list-style-type: none"> • Metal caps that provide a moisture barrier when fastening roofing underlayments • Brite finish 		<ul style="list-style-type: none"> • For use with fasteners to create a larger surface area for holding materials in place

ROOFING

ROOFING NAILS



- For applying asphalt shingles, insulation board and felt to wood substrates
- Large flat head
- Large gauge, round, smooth shank
- Diamond point
- Conforms to ASTM F1667

ELECTRO GALVANIZED

DESCRIPTION	SIZE	COATING	APPROX. CT./LB.	1# BOX	5# BOX	25# BOX	25# PAIL	50# BULK
Roofing Nails	1/2"	Electro Galvanized	424	-	0132015	-	-	0132012
Roofing Nails	5/8"	Electro Galvanized	382	-	0132025	-	-	0132022
Roofing Nails	3/4"	Electro Galvanized	323	0132038	0132035	-	0132039	0132032
Roofing Nails	7/8"	Electro Galvanized	288	0132048	0132045	0132043	0132049	0132042
Roofing Nails	1"	Electro Galvanized	261	0132058	0132055	0132053	0132059	0132052
Roofing Nails	1-1/4"	Electro Galvanized	209	0132078	0132075	0132073	0132079	0132072
Roofing Nails	1-1/2"	Electro Galvanized	194	0132098	0132095	0132093	0132099	0132092
Roofing Nails	1-3/4"	Electro Galvanized	155	0132118	0132115	0132113	0132119	0132112
Roofing Nails	2"	Electro Galvanized	136	0132138	0132135	0132133	0132139	0132132
Roofing Nails	2-1/2"	Electro Galvanized	109	0132158	0132155	0132153	0132159	0132152
Roofing Nails	3"	Electro Galvanized	93	0132178	0132175	0132173	0132179	0132172

HOT DIPPED GALVANIZED

Roofing Nails	3/4"	Hot Dipped Galvanized	282	0069038	0069035	0069033	-	0069032
Roofing Nails	7/8"	Hot Dipped Galvanized	261	0069048	0069045	0069043	-	0069042
Roofing Nails	1"	Hot Dipped Galvanized	254	0069058	0069055	0069053	0069059	0069052
Roofing Nails	1-1/4"	Hot Dipped Galvanized	196	0069078	0069075	0069073	0069079	0069072
Roofing Nails	1-1/2"	Hot Dipped Galvanized	163	0069098	0069095	0069093	0069099	0069092
Roofing Nails	1-3/4"	Hot Dipped Galvanized	148	0069118	0069115	0069113	0069119	0069112
Roofing Nails	2"	Hot Dipped Galvanized	120	0069138	0069135	0069133	0069139	0069132
Roofing Nails	2-1/2"	Hot Dipped Galvanized	106	0069158	0069155	0069153	0069159	0069152
Roofing Nails	3"	Hot Dipped Galvanized	90	0069178	0069175	0069173	0069179	0069172

RING SHANK (RS) ROOFING NAILS



- For applying asphalt shingles, insulation board and felt to wood substrates
- Large flat head
- Heavy gauge, ring shank
- Diamond point
- Conforms to ASTM F1667

316 STAINLESS STEEL

DESCRIPTION	SIZE	COATING	APPROX. CT./LB.	1# BOX	5# BOX	25# BOX	25# PAIL	50# BULK
RS Roofing Nails	1-1/4"	316 Stainless Steel	166	0260078S	0260075S	-	-	-
RS Roofing Nails	1-1/2"	316 Stainless Steel	139	0260098S	0260095S	-	-	-
RS Roofing Nails	1-3/4"	316 Stainless Steel	126	0260118S	0260115S	-	-	-



- HOT DIPPED GALVANIZED PRODUCTS CONFORM TO ASTM A153