SAINT-GOBAIN

SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

Product Name: MSDS Manufacturer Number: CA_All Address:

General Phone Number: Emergency Phone Number: 508-795-5000 Website: MSDS Creation Date: August 15, 2009 MSDS Revision Date: July 01, 2013

Coated Abrasive Manufacturer Name: Saint-Gobain Abrasives, Inc. 1 New Bond Street Worcester, MA 01615 508-795-5000 www.Nortonabrasives.com



SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CA S#	Ingredient Percent	EC Num.
Zirconium dioxide	1314-23-4	10 - 30 by weight	215-227-2
Calcium Silicate	13983-17-0	1 - 5 by weight	237-772-5
Cotton	No Data	1 - 5 by weight	
Aluminum Oxide, Non-fibrous	1344-28-1	60 - 100 by weight	215-691-6
Phenol formaldehyde polymer	9003-35-4	1 - 5 by weight	

SECTION 3 : HAZARDS IDENTIFICATION

Potential Health Effects:

Eye:	Dust may cause slight irritation.	
Skin:	Dust from this product may cause temporary mechanical irritation.	
Inhalation:	Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract.	
Ingestion:	Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances.	
Chronic Health Effects:	Chronic health effects are not expected as long as good hygiene and proper safety precautions are practiced.	

Phenol formaldehyde polymer

	ended use may contain trace amounts of phenol and formaldehyde which re may cause skin sensitization and airway obstruction.
--	---------------------------------------------------------------------------------------------------------------------------------

SECTION 4 : FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers.
	Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with soap and plenty of water.
	Get medical attention if irritation develops or persists.
Inhalation:	If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist, get medical attention.
Ingestion:	Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal blockage does not occur. If symptoms persist, call a physician.
Note to Physicians:	No information available.
Coated	Abrasive LIPC Number: 78072727698 CA All

SECTION 5 : FIRE FIGHTING MEASURES

Flammable Properties:	Non Flammable.
Flash Point:	Does not apply.
Auto Ignition Temperature:	Not determined.
Lower Flammable/Explosive Limit:	Not available.
Upper Flammable/Explosive Limit:	Not available.
Extinguishing Media:	Use any extinguishing media appropriate for the surrounding fires.
Unsuitable Media:	None.
Protective Equipment:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA Ratings:

NFPA Health:	1
NFPA Flammability:	0
NFPA Reactivity:	1
NFPA Other:	

SECTION 6 : ACCIDENTAL RELEASE MEASURES

Methods for containment:	Containment of this material should not be necessary.
Methods for cleanup:	Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic. Dispose of in accordance with Local, State, Federal and Provincial regulations.

SECTION 7 : HANDLING and STORAGE

Handling:	Handle with adequate ventilation for nuisance dust.
Storage:	No special storage conditions required.
Hygiene Practices:	Wear suitable gloves and eye/face protection.

SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	General dilution ventilation and/or local exhaust ventilation should be provided as necessary to maintain exposures below occupational exposure limits.
Eye/Face Protection:	Always WEAR SAFETY GLASSES or some type of eye protection when grinding.
Skin Protection Description:	Protective gloves. Long sleeved shirt and long pants.
Respiratory Protection:	When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.
Other Protective:	Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations).
General Hygiene Considerations:	Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Avoid getting dust into boots and gloves through wrist bands and pant tucks.

EXPOSURE GUIDELINES

Guideline OSHA	Guideline ACGIH	Quebec Canada	Ontario Canada	Alberta Canada
	TLV-TWA: 10 mg/m3 as zirconium compounds			
PEL-TWA: 15 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R)	TLV-TWA: 10 mg/m3 Inhalable fraction (I) TLV-TWA: 3 mg/m3 Respirable fraction (R)	VEMP-TWA: 10 mg/m3 Total particulate/dust (T) VEMP-TWA: 5 mg/m3 Respirable fraction (R)		
PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T)	TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)	OEL-TWA: 10 mg/m3
Mexico	British Columbia Canada			
MPE-PPT: 0.1 mg/m3 Respirable fraction (R)	OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3			
	PEL-TWA: 15 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T) Mexico MPE-PPT: 0.1 mg/m3	TLV-TWA: 10 mg/m3 as zirconium compounds PEL-TWA: 15 mg/m3 Total particulate/dust (T) TLV-TWA: 10 mg/m3 TLV-TWA: 3 mg/m3 Respirable fraction (R) PEL-TWA: 5 mg/m3 Respirable fraction (R) TLV-TWA: 3 mg/m3 Respirable fraction (R) PEL-TWA: 5 mg/m3 Total particulate/dust (T) TLV-TWA: 10 mg/m3 Respirable fraction (R) Mexico British Columbia Canada MPE-PPT: 0.1 mg/m3 Respirable fraction (R) OEL-TWA: 3 mg/m3 Respirable fraction (R) MPE-PPT: 0.1 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3	TLV-TWA: 10 mg/m3 as zirconium compounds VEMP-TWA: 10 mg/m3 Total particulate/dust (T) PEL-TWA: 15 mg/m3 Total particulate/dust (T) TLV-TWA: 10 mg/m3 TLV-TWA: 3 mg/m3 Respirable fraction (R) VEMP-TWA: 10 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R) TLV-TWA: 10 mg/m3 Respirable fraction (R) VEMP-TWA: 10 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T) TLV-TWA: 10 mg/m3 Respirable fraction (R) Mexico British Columbia Canada VEMP-TWA: 10 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3	TLV-TWA: 10 mg/m3 as zirconium compounds VEMP-TWA: 10 mg/m3 Total particulate/dust PEL-TWA: 15 mg/m3 Total particulate/dust TLV-TWA: 10 mg/m3 Inhalable fraction (I) TLV-TWA: 3 mg/m3 Respirable fraction (R) VEMP-TWA: 10 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R) TLV-TWA: 10 mg/m3 Respirable fraction (R) VEMP-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T) TLV-TWA: 10 mg/m3 TLV-TWA: 10 mg/m3 VEMP-TWA: 10 mg/m3 Total particulate/dust (T) Mexico British Columbia Canada OEL-TWA: 3 mg/m3 Respirable fraction (R) MPE-PPT: 0.1 mg/m3 Respirable fraction (R) OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance:	Solid article.
Odor:	Odorless.
Flash Point:	Does not apply.
Auto Ignition Temperature:	Not determined.

SECTION 10 : STABILITY and REACTIVITY

Chemical Stability:	Stable under normal conditions.
Hazardous Polymerization:	Hazardous polymerization does not occur.
Conditions to Avoid:	Keep away from heat, sparks, or open flame.
Special Decomposition Products:	In use, dust and decomposing odors may be generated. In most cases, the material removed from the workplace will be significantly greater than the sandpaper components. Coolants may produce other decomposition products. Thermal decomposition may produce trace amounts of ammonia and formaldehyde.

SECTION 11 : TOXICOLOGICAL INFORMATION

Acute Toxicity:	This product has not been tested for its toxicity.
Zirconium dioxide :	
RTECS Number:	ZH8800000
<u>Calcium Silicate</u> :	
RTECS Number:	ZC9750000
Aluminum Oxide, Non-fibrous:	
RTECS Number:	BD1200000
Inhalation:	Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema; Related to Chronic Data - death] (RTECS)
Phenol formaldehyde polymer :	
RTECS Number:	SM8542500
Skin:	Administration onto the skin - Rat LD50 : >2 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)
Ingestion:	Oral - Rat LD50 : >5 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

SECTION 12 : ECOLOGICAL INFORMATION						
Ecotoxicity:	No ecotoxicity data was found for the product.					
SECTION 13 : DISPOSAL CONSIDERATIONS						
Waste Disposal:	Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.					
SECTION 14 : TRANSPOR	T INFORMATION					
DOT Shipping Name:	Not regulated as hazardous material for transportation.					

	DOT Shipping Name:	Not regulated as hazardous material for transportation.
	DOT UN Number:	Not regulated as hazardous material for transportation.
	IATA Shipping Name:	Not regulated as hazardous material for transportation.
	Canadian Shipping Name:	This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).
_		

SECTION 15 : REGULATORY INFORMATION

Inventory Status

Г

TSCA Inventory

Τ

1	Callaua DOL		1	
		Status		
Zirconium dioxide	Listed	Listed		
Aluminum Oxide, Non-fibrous	Listed	Listed		
Phenol formaldehyde polymer	Listed	Listed		

Aluminum Oxide, Non-fibrous :

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

Zirconium dioxide :	
EC Number:	215-227-2
<u>Calcium Silicate :</u>	
EC Number:	237-772-5
Aluminum Oxide, Non-fibrous :	
EC Number:	215-691-6

State Right To Know

	ΡΑ	МА	LΩ	
Zirconium dioxide		Listed		
Aluminum Oxide, Non-fibrous	Listed	Listed	Listed: NJ Hazardous List; Substance Number: 2891	

SECTION 16 : ADDITIONAL INFORMATION

MSDS Creation Date: MSDS Revision Date: August 15, 2009

July 01, 2013

Copyright© 1996-2013 Actio Corporation. All Rights Reserved.