

#### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Coated Abrasive** 

MSDS Manufacturer Number: CA\_All

Manufacturer Name: Saint-Gobain Abrasives, Inc. 1 New Bond Street Address:

Worcester, MA 01615 General Phone Number:

508-795-5000

Emergency Phone Number: 508-795-5000

MSDS Creation Date: MSDS Revision Date:

Website:

www.Nortonabrasives.com August 15, 2009

July 01, 2013



HMIS				
Health Hazard	1			
Fire Hazard	0			
Reactivity	0			
Personal Protection	х			

#### SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.	
Inorganic fluorides	Not Applicable	5 - 10 by weight		
Calcium Silicate	13983-17-0	1 - 5 by weight	237-772-5	
Zirconium dioxide	1314-23-4	5 - 10 by weight	215-227-2	
Aluminum Oxide, Non-fibrous	1344-28-1	10 - 30 by weight	215-691-6	
Phenol formaldehyde polymer	9003-35-4	10 - 30 by weight		
Paper - Processed Cellulose	9004-34-6	30 - 60 by weight	232-674-9	

# SECTION 3: HAZARDS IDENTIFICATION

Potential Health Effects:

Eye: Dust may cause slight irritation.

Skin: Dust from this product may cause temporary mechanical irritation.

Inhalation: Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract.

Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal Ingestion: irritation and disturbances.

Chronic Health Effects: Chronic health effects are not expected as long as good hygiene and proper safety precautions are

practiced.

Phenol formaldehyde polymer

Chronic Health Effects: Dust generated from intended use may contain trace amounts of phenol and formaldehyde which

under excessive exposure may cause skin sensitization and airway obstruction.

### SECTION 4: FIRST AID MEASURES

Inhalation:

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of

the eyes by separating the eyelids with fingers.
Get medical attention, if irritation or symptoms of overexposure persists.

Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists. Skin Contact:

If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist,

get medical attention

Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal blockage does not occur. If symptoms persist, call a physician. Ingestion:

UPC Number: 66261138591 CA AI

#### SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties: Non Flammable. Flash Point: Does not apply. Auto Ignition Temperature: Not determined. Lower Flammable/Explosive Limit: Not available. Upper Flammable/Explosive Limit: Not available.

Extinguishing Media: Use any extinguishing media appropriate for the surrounding fires.

Unsuitable Media: None.

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or Protective Equipment:

equivalent) and full protective gear.

NFPA Ratings:

NFPA Health: NFPA Flammability: 0 NFPA Reactivity:

NFPA Other:

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

Methods for containment: Containment of this material should not be necessary.

Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic. Methods for cleanup:

Dispose of in accordance with Local, State, Federal and Provincial regulations.

### SECTION 7: HANDLING and STORAGE

Handling: Handle with adequate ventilation for nuisance dust.

Storage: No special storage conditions required.

Hygiene Practices: Wear suitable gloves and eye/face protection.

# SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: General dilution ventilation and/or local exhaust ventilation should be provided as necessary to

maintain exposures below occupational exposure limits

Eye/Face Protection: Always WEAR SAFETY GLASSES or some type of eye protection when grinding.

Skin Protection Description:

Protective gloves. Long sleeved shirt and long pants.

Respiratory Protection: When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.

Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations).

Handle in accordance with good industrial hygiene and safety practice. General Hygiene Considerations:

Remove and wash contaminated clothing before re-use.

Avoid getting dust into boots and gloves through wrist bands and pant tucks.

#### EXPOSURE GUIDELINES

Other Protective:

Ingredient	Guideline OSHA	Guideline NIOSH	Guideline ACGIH	Quebec Canada	Ontario Canada
Inorganic fluorides	PEL-TWA 2.5 mg/m3	REL-TWA 2.5 mg/m3	TLV-TWA 2.5 mg/m3		
Calcium Silicate	PEL-TWA: 15 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R)		TLV-TWA: 10 mg/m3 Inhalable fraction (I) TLV-TWA: 3 mg/m3 Respirable fraction (R)	VEMP-TWA: 10 mg/m3 Total particulate/dust (T) VEMP-TWA: 5 mg/m3 Respirable fraction (R)	
Zirconium dioxide			TLV-TWA: 10 mg/m3 as zirconium compounds		
Aluminum Oxide, Non- fibrous	PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T)		TLV-TWA: 10 mg/m3	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Paper - Processed Cellulose	PEL-TWA: 15 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3	REL-TWA: 10 mg/m3 Total particulate/dust (T) REL-TWA: 5 mg/m3 Respirable	TLV-TWA: 10 mg/m3	VEMP-TWA: 10 ppm Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)

	Respirable fraction (R)	fraction (R)		
Ingredient	Alberta Canada	Mexico	British Columbia Canada	
Aluminum Oxide, Non- fibrous	OEL-TWA: 10 mg/m3	MPE-PPT: 0.1 mg/m3 Respirable fraction (R)	OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-STEL: 20 mg/m3 Total particulate/dust (T)	
Paper - Processed Cellulose	OEL-TWA: 10 mg/m3	LMPE-PPT: 10 mg/m3 LMPE-CT: 20 mg/m3	OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 Total particulate/dust (T)	

#### SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Solid article. Odorless. Odor: Flash Point: Does not apply. Auto Ignition Temperature: Not determined.

#### SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Hazardous polymerization does not occur. Conditions to Avoid: Keep away from heat, sparks, or open flame.

Special Decomposition Products: In use, dust and decomposing odors may be generated. In most cases, the material removed from

the workplace will be significantly greater than the sandpaper components. Coolants may produce other decomposition products.

Thermal decomposition may produce trace amounts of ammonia and formaldehyde.

#### SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity: This product has not been tested for its toxicity.

Aluminum Oxide, Non-fibrous

ACGIH: A4 Not Classifiable as a Human Carcinogen

NIOSH: No Data OSHA: No Data IARC: No Data NTP: No Data

<u>Calcium Silicate</u>:

RTECS Number: ZC9750000

Zirconium dioxide:

RTECS Number: ZH8800000

**Aluminum Oxide, Non-fibrous:** 

RTECS Number: BD1200000

Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema; Related to Chronic Data - death] (RTECS) Inhalation:

Phenol formaldehyde polymer:

RTECS Number: SM8542500

Skin: Administration onto the skin - Rat LD50 : >2 gm/kg [Details of toxic effects not reported other than

lethal dose value ] (RTECS)

Ingestion:  $Oral-Rat\ LD50: > 5\ gm/kg\ [Details\ of\ toxic\ effects\ not\ reported\ other\ than\ lethal\ dose\ value\ ]$ 

(RTECS)

Paper - Processed Cellulose :

RTECS Number: FJ5691460

Inhalation - Rat LC50: >5800 mg/m3/4H [Details of toxic effects not reported other than lethal dose value] (RTECS) Inhalation:

Ingestion: Oral - Rat LD50: >5 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

# SECTION 12: ECOLOGICAL INFORMATION

### SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

## SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not regulated as hazardous material for transportation.

DOT UN Number: Not regulated as hazardous material for transportation.

IATA Shipping Name: Not regulated as hazardous material for transportation.

Canadian Shipping Name: This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).

## SECTION 15: REGULATORY INFORMATION

**Inventory Status** 

	EINECS Number	Canada DSL	TSCA Inventory	
			Status	
Calcium Silicate			Listed	
Zirconium dioxide		Listed	Listed	
Aluminum Oxide, Non-fibrous		Listed	Listed	
Phenol formaldehyde polymer		Listed	Listed	
Paper - Processed Cellulose	232-674-9	Listed	Listed	

Canada Reg. Status: Controlled - Class: D2B

Controlled - Class: D2B
This product has been classified in accordance with the hazard criteria of the Controlled Products
Regulations and the MSDS contains all of the information required by the Controlled Products

Regulations.

<u>Aluminum Oxide, Non-fibrous</u>:

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

<u>Calcium Silicate</u>:

EC Number: 237-772-5

Zirconium dioxide:

EC Number: 215-227-2

Aluminum Oxide, Non-fibrous:

EC Number: 215-691-6

<u>Paper - Processed Cellulose</u>:

EC Number: 232-674-9

State Right To Know

	RI	MN	IL	PA	MA
Zirconium dioxide					Listed
Aluminum Oxide, Non-fibrous	Listed	Listed	No Data	Listed	Listed
Paper - Processed Cellulose				Listed	Listed

	ŊĴ		
Aluminum Oxide, Non-fibrous	Listed: NJ Hazardous List; Substance Number: 2891		

# SECTION 16: ADDITIONAL INFORMATION

MSDS Creation Date: August 15, 2009
MSDS Revision Date: July 01, 2013

Copyright© 1996-2013 Actio Corporation. All Rights Reserved.