

#### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**Coated Abrasive** Product Name: MSDS Manufacturer Number: 983595\_CA\_All

Manufacturer Name: Saint-Gobain Abrasives, Inc. 1 New Bond Street Address: Worcester, MA 01615

General Phone Number: 508-795-5000 Emergency Phone Number: 508-795-5000

Website: www.Nortonabrasives.com MSDS Creation Date: December 15, 2010 MSDS Revision Date: July 01, 2013



HMIS	
Health Hazard	1
Fire Hazard	0
Reactivity	0
Personal Protection	х

#### SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
Silicon carbide	409-21-2	30.0 - 60 by weight	206-991-8
Cotton	No Data	10.0 - 30 by weight	
Phenol formaldehyde polymer	9003-35-4	30.0 - 60 by weight	

## SECTION 3: HAZARDS IDENTIFICATION

Potential Health Effects:

Eve: Dust may cause slight irritation.

Skin: Dust from this product may cause temporary mechanical irritation.

Inhalation: Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract. Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal

Ingestion:

Chronic Health Effects: Chronic health effects are not expected as long as good hygiene and proper safety precautions are

practiced

Phenol formaldehyde polymer

Chronic Health Effects: Dust generated from intended use may contain trace amounts of phenol and formaldehyde which

under excessive exposure may cause skin sensitization and airway obstruction.

SECTION 4: FIRST AID MEASURES

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Eye Contact:

Get medical attention, if irritation or symptoms of overexposure persists.

Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists. Skin Contact:

Inhalation: If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist,

get medical attention.

Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to Ingestion:

make sure intestinal blockage does not occur. If symptoms persist, call a physician.

Note to Physicians: No information available.

#### SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties: Non Flammable. Flash Point: Does not apply. Auto Ignition Temperature: Not determined Lower Flammable/Explosive Limit: Not available. Upper Flammable/Explosive Limit: Not available.

Extinguishing Media: Use any extinguishing media appropriate for the surrounding fires.

Unsuitable Media: None.

Protective Equipment: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or

equivalent) and full protective gear.

NFPA Ratings:

NFPA Health: NFPA Flammability: 0 NFPA Reactivity:

NFPA Other:

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

Methods for containment: Containment of this material should not be necessary.

Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic. Methods for cleanup:

Dispose of in accordance with Local, State, Federal and Provincial regulations.

#### SECTION 7: HANDLING and STORAGE

Handling: Handle with adequate ventilation for nuisance dust.

Storage: No special storage conditions required.

Hygiene Practices: Wear suitable gloves and eye/face protection.

### SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls: General dilution ventilation and/or local exhaust ventilation should be provided as necessary to

maintain exposures below occupational exposure limits

Eye/Face Protection: Always WEAR SAFETY GLASSES or some type of eye protection when grinding.

Skin Protection Description: Protective gloves.

Long sleeved shirt and long pants.

When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. Respiratory Protection:

A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended. Other Protective:

Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations).

General Hygiene Considerations:

Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Avoid getting dust into boots and gloves through wrist bands and pant tucks.

## **EXPOSURE GUIDELINES**

Ingredient	Guideline OSHA	Guideline A CGIH	Quebec Canada	Ontario Canada	Alberta Canada
Silicon carbide	PEL-TWA: 15 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R)	TLV-TWA: 10 mg/m3 Inhalable fraction (I) TLV-TWA: 3 mg/m3 Respirable fraction (R) TLV-TWA: 0.1 f/cc Respirable fraction (R)	VEMP-TWA: 10 mg/m3 Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T) OEL-TWAEV: 3 mg/m3 Respirable fraction (R) OEL-TWAEV: 10 mg/m3 Inhalable fraction (I) OEL-TWAEV: 0.1 f/cc Respirable fraction (R)	OEL-TWA: 10 mg/m3
Ingredient	Mexico	British Columbia Canada			
Silicon carbide	LMPE-PPT: 10 mg/m3 LMPE-CT: 20 mg/m3	OEL-TWA: 10 mg/m3 Inhalable fraction (I) OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 0.1 f/cc Respirable fraction (R)			

### SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Solid article. Odor: Odorless. Flash Point: Does not apply. Auto Ignition Temperature: Not determined.

#### SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Hazardous polymerization does not occur. Conditions to Avoid: Keep away from heat, sparks, or open flame.

In use, dust and decomposing odors may be generated.In most cases, the material removed from the workplace will be significantly greater than the sandpaper components. Coolants may produce other decomposition products. Special Decomposition Products:

#### SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity: This product has not been tested for its toxicity.

Silicon carbide:

RTECS Number: VW0450000 Inhalation: No Data

Phenol formaldehyde polymer:

RTECS Number: SM8542500

Administration onto the skin - Rat LD50 : >2 gm/kg [Details of toxic effects not reported other than lethal dose value ] (RTECS) Skin:

Ingestion: Oral - Rat LD50 : >5 gm/kg [Details of toxic effects not reported other than lethal dose value ]

(RTECS)

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

## SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

## SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not regulated as hazardous material for transportation. DOT UN Number: Not regulated as hazardous material for transportation.

IATA Shipping Name: Not regulated as hazardous material for transportation.

Canadian Shipping Name: This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).

# SECTION 15: REGULATORY INFORMATION

**Inventory Status** 

	Canada DSL	TSCA Inventory		
	Junuar 202	Status		
Silicon carbide	Listed	Listed		
Phenol formaldehyde polymer	Listed	Listed		

#### Silicon carbide:

EC Number: 206-991-8

State Right To Know

	PA	MA		
Silicon carbide	Listed	Listed		

# SECTION 16: ADDITIONAL INFORMATION

MSDS Creation Date: December 15, 2010
MSDS Revision Date: July 01, 2013

Copyright© 1996-2013 Actio Corporation. All Rights Reserved.

Coated Abrasive Revision: 07/01/2013