

## SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Coated Abrasive** MSDS Manufacturer Number: 983617\_CA\_All

Manufacturer Name: Saint-Gobain Abrasives, Inc. 1 New Bond Street Address:

Worcester, MA 01615

General Phone Number: 508-795-5000 Emergency Phone Number: 508-795-5000

Website: www.Nortonabrasives.com

MSDS Creation Date: August 15, 2009 MSDS Revision Date: July 01, 2013



HMIS				
Health Hazard	1			
Fire Hazard	0			
Reactivity	0			
Personal Protection	x			

## SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.	
Sulfates/Sulfides	No Data	10.0 - 30 by weight		
Garnet	1302-62-1	30.0 - 60 by weight		
Urea-formaldehyde polymer	9011-05-6	10.0 - 30 by weight		
Animal Glue	No Data	5.0 - 10 by weight		
Paper - Processed Cellulose	9004-34-6	10.0 - 30 by weight	232-674-9	
Garnet Urea-formaldehyde polymer Animal Glue	1302-62-1 9011-05-6 No Data	30.0 - 60 by weight 10.0 - 30 by weight 5.0 - 10 by weight	232-674-9	

# SECTION 3: HAZARDS IDENTIFICATION

Potential Health Effects:

Eye: Dust may cause slight irritation.

Skin: Dust from this product may cause temporary mechanical irritation.

Inhalation: Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract.

Ingestion: Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances.

Chronic Health Effects: Chronic health effects are not expected as long as good hygiene and proper safety precautions are

Urea-formaldehyde polymer

Chronic Health Effects: For products containing Urea/Formaldehyde resin, dust generated from intended use may contain trace

amounts of formaldehyde which under excessive exposure may cause skin sensitization and airway

obstruction.

## SECTION 4: FIRST AID MEASURES

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers.

Get medical attention, if irritation or symptoms of overexposure persists. Eve Contact:

Skin Contact: Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Inhalation: If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist,

get medical attention.

Ingestion: Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to

make sure intestinal blockage does not occur. If symptoms persist, call a physician.

Note to Physicians: No information available.

## SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties: Non Flammable Flash Point: Does not apply. Auto Ignition Temperature: Not determined. Lower Flammable/Explosive Limit: Not available. Upper Flammable/Explosive Limit: Not available.

Extinguishing Media: Use any extinguishing media appropriate for the surrounding fires.

Unsuitable Media:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or Protective Equipment:

equivalent) and full protective gear.

NFPA Ratings:

NFPA Health: NFPA Flammability: 0 NFPA Reactivity:

NFPA Other:

## SECTION 6: ACCIDENTAL RELEASE MEASURES

Containment of this material should not be necessary. Methods for containment:

Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic. Methods for cleanup:

Dispose of in accordance with Local, State, Federal and Provincial regulations.

## SECTION 7: HANDLING and STORAGE

Handling: Handle with adequate ventilation for nuisance dust.

Storage: No special storage conditions required.

Hygiene Practices: Wear suitable gloves and eye/face protection.

## SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

**Engineering Controls:** General dilution ventilation and/or local exhaust ventilation should be provided as necessary to

maintain exposures below occupational exposure limits

Skin Protection Description: Protective gloves.

Long sleeved shirt and long pants.

When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators.

A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended. Respiratory Protection:

Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations).

Always WEAR SAFETY GLASSES or some type of eye protection when grinding.

General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice.

Remove and wash contaminated clothing before re-use. Avoid getting dust into boots and gloves through wrist bands and pant tucks.

## **EXPOSURE GUIDELINES**

Eye/Face Protection:

Other Protective:

Ingredient	Guideline OSHA	Guideline NIOSH	Guideline ACGIH	Quebec Canada	Ontario Canada
Paper - Processed Cellulose	PEL-TWA: 15 mg/m3 Total particulate/dust (T) PEL-TWA: 5 mg/m3 Respirable fraction (R)	REL-TWA: 10 mg/m3 Total particulate/dust (T) REL-TWA: 5 mg/m3 Respirable fraction (R)	TLV-TWA: 10 mg/m3	VEMP-TWA: 10 ppm Total particulate/dust (T)	OEL-TWAEV: 10 mg/m3 Total particulate/dust (T)
Ingredient	Alberta Canada	Mexico	British Columbia Canada		
Paper - Processed Cellulose	OEL-TWA: 10 mg/m3	LMPE-PPT: 10 mg/m3 LMPE-CT: 20 mg/m3	OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 Total particulate/dust (T)		

## SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Coated Abrasive

Physical State Appearance: Solid article. Odor: Odorless. Flash Point: Does not apply. Auto Ignition Temperature: Not determined.

## SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Hazardous polymerization does not occur. Conditions to Avoid: Keep away from heat, sparks, or open flame.

Special Decomposition Products: In use, dust and decomposing odors may be generated. In most cases, the material removed from

the workplace will be significantly greater than the sandpaper components.

Coolants may produce other decomposition products.
Thermal decomposition may produce trace amounts of ammonia and formaldehyde.

## SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity: This product has not been tested for its toxicity.

<u>Urea-formaldehyde polymer</u>:

RTECS Number: YU1610000

Eye: Eye - Rabbit Standard Draize test.: 100 uL/24H [severe] (RTECS)

Skin:

Administration onto the skin - Rabbit Standard Draize test.: 500 mg/24H [severe] Administration onto the skin - Rat LD50 : >2100 mg/kg [Details of toxic effects not reported other than

lethal dose value] (RTECS)

 $Inhalation - Rat\ LC50: > 167\ mg/m3/4H\ [Details\ of\ toxic\ effects\ not\ reported\ other\ than\ lethal\ dose$ Inhalation:

value] (RTECS)

Oral - Rat LD50 : 8394 mg/kg [Details of toxic effects not reported other than lethal dose value] Oral - Mouse LD50 : 6361 mg/kg [Details of toxic effects not reported other than lethal dose value] Ingestion:

(RTECS)

Paper - Processed Cellulose:

RTECS Number: FJ5691460

Inhalation: Inhalation - Rat LC50: >5800 mg/m3/4H [Details of toxic effects not reported other than lethal dose

value] (RTECS)

Ingestion: Oral - Rat LD50: >5 gm/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

# SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

## SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not regulated as hazardous material for transportation.

DOT UN Number: Not regulated as hazardous material for transportation.

IATA Shipping Name: Not regulated as hazardous material for transportation.

Canadian Shipping Name: This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).

## SECTION 15: REGULATORY INFORMATION

Coated Abrasive

Revision: 07/01/2013

**Inventory Status** 

	EINECS Number	Canada DSL	TSCA Inventory	
			Status	
Urea-formaldehyde polymer		Listed	Listed	
Paper - Processed Cellulose	232-674-9	Listed	Listed	

EC Number: 232-674-9

State Right To Know

	PA	MA		
Paper - Processed Cellulose	Listed	Listed		

# SECTION 16: ADDITIONAL INFORMATION

MSDS Creation Date: August 15, 2009
MSDS Revision Date: July 01, 2013

Copyright© 1996-2013 Actio Corporation. All Rights Reserved.