

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Coated Abrasive**

MSDS Manufacturer Number: CA_All

Manufacturer Name: Saint-Gobain Abrasives, Inc.

Address:


1 New Bond Street Worcester, MA 01615 508-795-5000

General Phone Number: Emergency Phone Number: 508-795-5000

Website:

www.Nortonabrasives.com January 24, 2011

MSDS Creation Date: MSDS Revision Date: July 01, 2013



| HMIS | | | |
|------------------------|---|--|--|
| Health Hazard | 1 | | |
| Fire Hazard | 0 | | |
| Reactivity | 0 | | |
| Personal Protection | x | | |
| | | | |

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS# | Ingredient Percent | EC Num. |
|-----------------------------|-----------|--------------------|-----------|
| Cotton | No Data | 1 - 5 by weight | |
| Urea-formaldehyde polymer | 9011-05-6 | 1 - 5 by weight | |
| Sulfates/Sulfides | No Data | 1 - 5 by weight | |
| Aluminum Oxide, Non-fibrous | 1344-28-1 | 60 - 100 by weight | 215-691-6 |

SECTION 3: HAZARDS IDENTIFICATION

Potential Health Effects:

Dust may cause slight irritation. Eve:

Skin: Dust from this product may cause temporary mechanical irritation.

Inhalation: Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract. Ingestion: Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal

irritation and disturbances.

Chronic Health Effects: Chronic health effects are not expected as long as good hygiene and proper safety precautions are

Urea-formaldehyde polymer

For products containing Urea/Formaldehyde resin, dust generated from intended use may contain trace amounts of formaldehyde which under excessive exposure may cause skin sensitization and airway Chronic Health Effects:

obstruction.

SECTION 4: FIRST AID MEASURES

Skin Contact:

Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Eye Contact:

Get medical attention, if irritation or symptoms of overexposure persists.

Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Inhalation: If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist,

get medical attention.

Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal blockage does not occur. If symptoms persist, call a physician. Ingestion:

Note to Physicians: No information available.

> Coated Abrasive Revision: 07/01/2013

SECTION 5: FIRE FIGHTING MEASURES

Flammable Properties: Non Flammable. Flash Point: Does not apply. Auto Ignition Temperature: Not determined. Lower Flammable/Explosive Limit: Not available. Upper Flammable/Explosive Limit: Not available.

Extinguishing Media: Use any extinguishing media appropriate for the surrounding fires.

Unsuitable Media:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or Protective Equipment:

equivalent) and full protective gear.

NFPA Ratings:

NFPA Health: NFPA Flammability: 0 NFPA Reactivity: 1

NFPA Other:

SECTION 6: ACCIDENTAL RELEASE MEASURES

Methods for containment: Containment of this material should not be necessary.

Methods for cleanup: Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic

Dispose of in accordance with Local, State, Federal and Provincial regulations.

SECTION 7: HANDLING and STORAGE

Handling: Handle with adequate ventilation for nuisance dust.

Storage: No special storage conditions required.

Hygiene Practices: Wear suitable gloves and eye/face protection.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

General dilution ventilation and/or local exhaust ventilation should be provided as necessary to **Engineering Controls:**

maintain exposures below occupational exposure limits.

Eye/Face Protection: Always WEAR SAFETY GLASSES or some type of eye protection when grinding.

Skin Protection Description:

Protective gloves. Long sleeved shirt and long pants.

Respiratory Protection: When workers are facing airborne particulate/dust concentrations above the exposure limit they must

use appropriate certified respirator A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended.

Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations). Other Protective:

General Hygiene Considerations:

Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Avoid getting dust into boots and gloves through wrist bands and pant tucks.

EXPOSURE GUIDELINES

| Ingredient | Guideline OSHA | Guideline A CGIH | Quebec Canada | Ontario Canada | Alberta Canada |
|---------------------------------|---|---|---|--|-------------------|
| Aluminum Oxide, Non- fibrous | PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T) | TLV-TWA: 10 mg/m3 | VEMP-TWA: 10 mg/m3 Total particulate/dust (T) | OEL-TWAEV: 10 mg/m3 Total particulate/dust (T) | OEL-TWA: 10 mg/m3 |
| Ingredient | Mexico | British Columbia Canada | | | |
| Aluminum Oxide, Non- fibrous | | OEL-TWA: 3 mg/m3 Respirable fraction (R) OEL-TWA: 10 mg/m3 OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-STEL: 20 mg/m3 Total particulate/dust (T) | | | |

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Solid article. Odor: Odorless. Flash Point: Does not apply. Auto Ignition Temperature: Not determined.

SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under normal conditions.

Hazardous Polymerization: Hazardous polymerization does not occur. Conditions to Avoid: Keep away from heat, sparks, or open flame.

In use, dust and decomposing odors may be generated. In most cases, the material removed from the workplace will be significantly greater than the sandpaper components. Special Decomposition Products:

Coolants may produce other decomposition products.

Thermal decomposition may produce trace amounts of ammonia and formaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute Toxicity: This product has not been tested for its toxicity.

Urea-formaldehyde polymer:

YU1610000 RTECS Number:

Eye - Rabbit Standard Draize test.: 100 uL/24H [severe] (RTECS) Eve:

Skin:

Administration onto the skin - Rabbit Standard Draize test.: 500 mg/24H [severe] Administration onto the skin - Rat LD50 : >2100 mg/kg [Details of toxic effects not reported other than

lethal dose value] (RTECS)

Inhalation: Inhalation - Rat LC50 : >167 mg/m3/4H [Details of toxic effects not reported other than lethal dose

value] (RTECS)

Oral - Rat LD50 : 8394 mg/kg [Details of toxic effects not reported other than lethal dose value] Oral - Mouse LD50 : 6361 mg/kg [Details of toxic effects not reported other than lethal dose value] Ingestion:

(RTECS)

<u>Aluminum Oxide, Non-fibrous</u>:

RTECS Number: BD1200000

Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema; Related to Chronic Data - death] (RTECS) Inhalation:

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not regulated as hazardous material for transportation. DOT UN Number: Not regulated as hazardous material for transportation.

IATA Shipping Name: Not regulated as hazardous material for transportation.

Canadian Shipping Name: This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).

SECTION 15: REGULATORY INFORMATION

Inventory Status

| | Canada DSL | TSCA Inventory | | |
|-----------------------------|------------|----------------|--|--|
| | | Status | | |
| Urea-formaldehyde polymer | Listed | Listed | | |
| Aluminum Oxide, Non-fibrous | Listed | Listed | | |

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

<u>Aluminum Oxide, Non-fibrous</u>:

EC Number: 215-691-6

State Right To Know

| | PA | MA | NJ. | |
|-----------------------------|--------|--------|---|--|
| Aluminum Oxide, Non-fibrous | Listed | Listed | Listed: NJ Hazardous List; Substance Number: 2891 | |

SECTION 16: ADDITIONAL INFORMATION

MSDS Creation Date: January 24, 2011
MSDS Revision Date: July 01, 2013

 $\label{local_conversion} \mbox{Copyright} \mbox{@ 1996-2013 Actio Corporation. All Rights Reserved.}$

Coated Abrasive Revision: 07/01/2013