SAINT-GOBAIN

SECTION 1 : PRODUCT AND COMPANY IDENTIFICATION

Product Name: MSDS Manufacturer Number: CA_All Address:

General Phone Number: Emergency Phone Number: 508-795-5000 Website: MSDS Creation Date:August 15, 20MSDS Revision Date:July 01, 2013

Coated Abrasive Manufacturer Name: Saint-Gobain Abrasives, Inc. 1 New Bond Street Worcester, MA 01615 508-795-5000 www.Nortonabrasives.com August 15, 2009



SECTION 2 : COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CA S# | Ingredient Percent | EC Num. |
|----------------------------------|------------|--------------------|-----------|
| Nylon | No Data | 30 - 60 by weight | |
| Melamine Formaldehyde | 9003-08-1 | 1 - 5 by weight | |
| Polyurethane resin | 67700-43-0 | 10 - 30 by weight | |
| Titanium dioxide | 13463-67-7 | 0 - 1 by weight | 236-675-5 |
| Lithium stearate | 4485-12-5 | 1 - 5 by weight | 224-772-5 |
| Talc, Magnesium silicate hydrate | 14807-96-6 | 1 - 5 by weight | 238-877-9 |
| Aluminum Oxide, Non-fibrous | 1344-28-1 | 10 - 30 by weight | 215-691-6 |
| | | | |

SECTION 3 : HAZARDS IDENTIFICATION

Potential Health Effects:

| Eye: | Dust may cause slight irritation. |
|-------------------------|--|
| Skin: | Dust from this product may cause temporary mechanical irritation. |
| Inhalation: | Dusts from this product may cause mechanical irritation of the nose, throat and respiratory tract. |
| Ingestion: | Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances. |
| Chronic Health Effects: | Chronic health effects are not expected as long as good hygiene and proper safety precautions are practiced. |

SECTION 4 : FIRST AID MEASURES

| Eye Contact: | Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Get medical attention, if irritation or symptoms of overexposure persists. |
|---------------------|--|
| Skin Contact: | Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists. |
| Inhalation: | If dust from cutting or drilling is inhaled, remove the affected person to fresh air. If symptoms persist, get medical attention. |
| Ingestion: | Accidental ingestion of this material is unlikely. If this does occur, watch person for several days to make sure intestinal blockage does not occur. If symptoms persist, call a physician. |
| Note to Physicians: | No information available. |

SECTION 5 : FIRE FIGHTING MEASURES

| Flammable Properties: | Non Flammable. |
|----------------------------------|--|
| Flash Point: | Does not apply. |
| Auto Ignition Temperature: | Not determined. |
| Lower Flammable/Explosive Limit: | Not available. |
| Upper Flammable/Explosive Limit: | Not available. |
| Extinguishing Media: | Use any extinguishing media appropriate for the surrounding fires. |
| Unsuitable Media: | None. |
| Protective Equipment: | As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. |
| | |
| NFPA Ratings: | |

| NFPA Health: | 1 |
|--------------------|---|
| NFPA Flammability: | 0 |
| NFPA Reactivity: | 1 |
| NFPA Other: | |

SECTION 6 : ACCIDENTAL RELEASE MEASURES

| Methods for containment: | Containment of this material should not be necessary. |
|--------------------------|---|
| Methods for cleanup: | Shovel or sweep up for re-use or disposal. Avoid creating dusty conditions. Evaluate residue to determine if it is a hazardous waste by characteristic. Dispose of in accordance with Local, State, Federal and Provincial regulations. |

SECTION 7 : HANDLING and STORAGE

| Handling: | Handle with adequate ventilation for nuisance dust. |
|--------------------|---|
| Storage: | No special storage conditions required. |
| Hygiene Practices: | Wear suitable gloves and eye/face protection. |

SECTION 8 : EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

| Engineering Controls: | General dilution ventilation and/or local exhaust ventilation should be provided as necessary to maintain exposures below occupational exposure limits. |
|---------------------------------|--|
| Eye/Face Protection: | Always WEAR SAFETY GLASSES or some type of eye protection when grinding. |
| Skin Protection Description: | Protective gloves. Long sleeved shirt and long pants. |
| Respiratory Protection: | When workers are facing airborne particulate/dust concentrations above the exposure limit they must use appropriate certified respirators. A properly fitted NIOSH approved disposable N 95 type dust respirator or better is recommended. |
| Other Protective: | Use of this product may create elevated sound levels. Hearing protection should be worn where required (see OSHA 29 CFR 1910.134 and other applicable regulations). |
| General Hygiene Considerations: | Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Avoid getting dust into boots and gloves through wrist bands and pant tucks. |

EXPOSURE GUIDELINES

| Ingredient | Guideline OSHA | Guideline ACGIH | Quebec Canada | Ontario Canada | Alberta Canada |
|---|---|---|---|--|--|
| Titanium dioxide | | TLV-TWA: 10 mg/m3 | VEMP-TWA: 10 mg/m3 Total particulate/dust (T) | OEL-TWAEV: 10 mg/m3 Total particulate/dust (T) | OEL-TWA: 10 mg/m3 Total particulate/dust (T) |
| Talc, Magnesium silicate hydrate | PEL-TWA: 20 mppcf | TLV-TWA: 2 mg/m3 Respirable fraction (R) TLV-TWA: 1 mg/m3 Respirable fraction (R) | VEMP-TWA: 3 mg/m3 Respirable fraction (R) | OEL-TWAEV: 2 f/cc Respirable fraction (R) | OEL-TWA: 2 mg/m3 Respirable fraction (R) |
| Aluminum Oxide, Non- fibrous | PEL-TWA: 5 mg/m3 Respirable fraction (R) PEL-TWA: 15 mg/m3 Total particulate/dust (T) | TLV-TWA: 10 mg/m3 | VEMP-TWA: 10 mg/m3 Total particulate/dust (T) | OEL-TWAEV: 10 mg/m3 Total particulate/dust (T) | OEL-TWA: 10 mg/m3 |
| Ingredient | Mexico | British Columbia | | | |
| | | Canada | | | |
| Titanium dioxide | MPE-PPT: 0.1 mg/m3 Respirable fraction (R) | Canada OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-TWA: 3 mg/m3 Respirable fraction (R) | | | |
| Titanium dioxide Talc, Magnesium silicate hydrate | Respirable fraction (R) | OEL-TWA: 10 mg/m3 Total particulate/dust (T) OEL-TWA: 3 mg/m3 | | | |

SECTION 9 : PHYSICAL and CHEMICAL PROPERTIES

| Physical State Appearance: | Solid article. |
|----------------------------|-----------------|
| Odor: | Odorless. |
| Flash Point: | Does not apply. |
| Auto Ignition Temperature: | Not determined. |

SECTION 10 : STABILITY and REACTIVITY

| Chemical Stability: | Stable under normal conditions. |
|---------------------------------|---|
| Hazardous Polymerization: | Hazardous polymerization does not occur. |
| Conditions to Avoid: | Keep away from heat, sparks, or open flame. |
| Special Decomposition Products: | In use, dust and decomposing odors may be generated. In most cases, the material removed from the workplace will be significantly greater than the sandpaper components. Coolants may produce other decomposition products. Thermal decomposition may produce trace amounts of ammonia and formaldehyde. |

SECTION 11 : TOXICOLOGICAL INFORMATION

| Acute | Toxicity | <i></i> |
|-------|----------|---------|
| | | |

This product has not been tested for its toxicity.

| Aluminum Oxide, Non-fibrous : | |
|---|--|
| ACGIH: | A4 Not Classifiable as a Human Carcinogen |
| NIOSH: | No Data |
| OSHA: | No Data |
| IARC: | No Data |
| NTP: | No Data |
| <u>Titanium dioxide</u> : | |
| RTECS Number: | XR2275000 |
| Skin: | Skin - Human Standard Draize test. : 300 ug/3D-I - [mild] (RTECS) |
| Inhalation: | Inhalation - Rat TCLo - Lowest published toxic concentration: 1 mg/kg - [Lungs, Thorax, or Respiration - Other changes Biochemical - Metabolism (Intermediary) - Effect on inflammation or mediation of inflammation] (RTECS) |
| Ingestion: | Oral - Rodent rat TDLo - Lowest published toxic dose: 60 gm/kg - [Gastrointestinal - Hypermotility, diarrhea Gastrointestinal - Other changes] (RTECS) |
| Lithium stearate : | |
| RTECS Number: | W14370000 |
| Ingestion: | Oral - Rat LD50: 15 gm/kg [Behavioral - Somnolence (general depressed activity) Behavioral - Changes in motor activity (specific assay) Skin and Appendages - Hair] (RTECS) |
| <u>Talc, Magnesium silicate hydrate :</u> | |
| RTECS Number: | WW2710000 |
| Aluminum Oxide, Non-fibrous : | |
| RTECS Number: | BD1200000 |
| Inhalation: | Inhalation - Rat TCLo: 200 mg/m3/5H/28W (Intermittent) [Lungs, Thorax, or Respiration - Structural or functional change in trachea or bronchi; Lungs, Thorax, or Respiration - Chronic pulmonary edema; Related to Chronic Data - death] (RTECS) |

SECTION 12 : ECOLOGICAL INFORMATION

Ecotoxicity:

Waste Disposal:

No ecotoxicity data was found for the product.

SECTION 13 : DISPOSAL CONSIDERATIONS

Use standard landfill methods consistent with applicable Federal, State, Provincial and local laws.

SECTION 14 : TRANSPORT INFORMATION

| DOT Shipping Name: | Not regulated as hazardous material for transportation. |
|---------------------|---|
| DOT UN Number: | Not regulated as hazardous material for transportation. |
| | |
| IATA Shipping Name: | Not regulated as hazardous material for transportation. |

Canadian Shipping Name: This product is Not Regulated under the Transportation of Dangerous Goods Act. (CAN).

SECTION 15 : REGULATORY INFORMATION

Inventory Status

| | Canada DSL | TSCA Inventory | | |
|----------------------------------|------------|----------------|--|--|
| | | Status | | |
| Titanium dioxide | Listed | Listed | | |
| Lithium stearate | Listed | Listed | | |
| Talc, Magnesium silicate hydrate | Listed | Listed | | |
| Aluminum Oxide, Non-fibrous | Listed | Listed | | |

Aluminum Oxide, Non-fibrous :

Canada IDL: Identified under the Canadian Hazardous Products Act Ingredient Disclosure List: 0.1%.50(1298)

| <u>Titanium dioxide :</u> | |
|------------------------------------|-----------|
| EC Number: | 236-675-5 |
| Lithium stearate : | |
| EC Number: | 224-772-5 |
| Talc, Magnesium silicate hydrate : | |
| EC Number: | 238-877-9 |
| Aluminum Oxide, Non-fibrous : | |
| EC Number: | 215-691-6 |

State Right To Know

| | RI | MN | IL | PA | МА |
|----------------------------------|--------|--------|---------|--------|--------|
| Titanium dioxide | | | | Listed | Listed |
| Talc, Magnesium silicate hydrate | | | | Listed | Listed |
| Aluminum Oxide, Non-fibrous | Listed | Listed | No Data | Listed | Listed |

| | Γ | | |
|-----------------------------|---|--|--|
| Titanium dioxide | No Data | | |
| Aluminum Oxide, Non-fibrous | Listed: NJ Hazardous List; Substance Number: 2891 | | |

SECTION 16 : ADDITIONAL INFORMATION

MSDS Creation Date: MSDS Revision Date: August 15, 2009

July 01, 2013

Copyright© 1996-2013 Actio Corporation. All Rights Reserved.