

Product Number: 25176

Order Abbreviation: F72T12/CW/HO

General Description: 85W, 72"MOL, T12 HO (800 mA) rapid start fluorescent lamp, Cool Whitephosphor, 4200K color temperature, 60 CRI



*** Full Case Required**

Product Information

Abbrev. With Packaging Info.	F72T12CWHO 15/CS 1/SKU
Actual Length (in)	69.909
Actual Length (mm)	1775.69
Average Rated Life (hr)	12000
Base	Recessed Double Contact
Bulb	T12
Color Rendering Index (CRI)	60
Color Temperature/CCT (K)	4200
Diameter (in)	1.593
Diameter (mm)	40.46
Industry Standards	ANSI C78.81 - 2001
Initial Lumens at 25C	6250
Mean Lumens at 25C	5063
Mean Lumens at 35C	5063
Nominal Length (in)	72.000
Nominal Length (mm)	1828.80
Nominal Wattage (W)	85.00

Footnotes

- May be operated at 100 watts (1000MA) same as F84T12/HO.
- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- Average life rating at 12 hours operation per start is 18,000 hours.
- Mean lumens are measured at 40% of average rated lamp life.
- The distance between any parts of the lamp and any conductive surface of the luminaire should not be less than 3 mm (applies to all high frequency ballasted systems).
- The lamp should not be in contact with any surface of the luminaire (applies to either high frequency or 60Hz ballasted systems).