

TY™ ENCAPSULATED END BRUSHES

TY polymer supports each wire working point to provide maximum work with minimum pressure. The unique shapes and characteristics of TY encapsulated end brushes make them ideal for unusual applications.

TY ENCAPSULATED HOLLOW CENTER END BRUSH - STANDARD DUTY

Small diameter tools that provide fast, positive cleaning action in corners and other hard-to-reach places.

Applications: Burr Removal, Rubber Flash, Weld Scale, Rust, Paint

Brush Dia.	Overall Length	Fill Dia.	Fill Material	Trim Length	Shank Dia.	Max RPM	Item No.
3/8	2-1/2	0.006	Steel	1	1/4		30558
3/8	2-1/2	0.0104	Steel	1	1/4		30559
1/2	2-5/8	0.005	Stainless Steel	1	1/4	18000	30615
1/2	2-5/8	0.006	Steel	1	1/4	18000	30600
1/2	2-5/8	0.0104	Steel	1	1/4	18000	30602
1/2	2-5/8	0.020	Steel	1	1/4	18000	30604
3/4	2-5/8	0.006	Steel	1	1/4	15000	30605
3/4	2-5/8	0.0104	Stainless Steel	1	1/4	15000	30619
3/4	2-5/8	0.0104	Steel	1	1/4	15000	30607
3/4	2-5/8	0.020	Steel	1	1/4	15000	30609
1	2-5/8	0.006	Steel	1	1/4	13000	30610
1	2-5/8	0.0104	Stainless Steel	1	1/4	13000	30622
1	2-5/8	0.0104	Steel	1	1/4	13000	30612
1	2-5/8	0.020	Steel	1	1/4	13000	30614



Note: As a safety precaution, shank must be fully inserted into the chuck or collet and tightened securely.

TY ENCAPSULATED FLARED END BRUSH - HEAVY DUTY

Preflared and bonded, with rigid elastomer supporting steel and stainless steel wire fill.

Applications: Weld Prep, Weld Cleaning, Confined Area General Cleaning

Brush Dia.	Fill Dia.	Fill Material	Inner Dia.	Shank Dia.	Max RPM	Item No.
1-3/4	0.006	Steel	1/2	1/4	25000	30650
1-3/4	0.0104	Stainless Steel	1/2	1/4	25000	30655
1-3/4	0.0104	Steel	1/2	1/4	25000	30651
1-3/4	0.020	Steel	1/2	1/4	25000	30653
2	0.006	Steel	3/4	1/4	20000	30658
2	0.0104	Stainless Steel	3/4	1/4	20000	30663
2	0.0104	Steel	3/4	1/4	20000	30659
2	0.020	Steel	3/4	1/4	20000	30661
2-3/4	0.006	Steel	1	1/4	15000	30666
2-3/4	0.0104	Stainless Steel	1	1/4	15000	30671
2-3/4	0.0104	Steel	1	1/4	15000	30667
2-3/4	0.020	Steel	1	1/4	15000	30669



Note: As a safety precaution, shank must be fully inserted into the chuck or collet and tightened securely.