

# Cable Connectors

## For Armored Cable & Flexible Metal Conduit

### Type C & Type 24

#### Straight Squeeze Connectors

##### Use:

To ground and secure Armored Cable and Flexible Metal Conduit to boxes and enclosures.

##### Features:

- Male hub threads - NPS.
- Available with insulated throat.
- Furnished with locknuts.

##### Materials/Finish:

Malleable Iron/Zinc Electroplated

##### Third Party Certification:



UL Listed: E-11852

C-5 through C-8:

UL Listed for armored cable.

UL Listed: E-11853


C-8, 24-34 through 24-300:

UL Listed for flexible metal conduit


UL Listed flexible metal conduit fittings are suitable for use in Hazardous Location under NEC 501-4(b), Class I, Div. II, and suitable as a grounding means under NEC 350-5.




CSA Certified: 009795: Armored Cable



Type C-5  
End Stopped



Type C-8 — Type 24-125  
Center Stopped



Type 24-150 — Type 24-300  
Center Stopped

Trade Size (inches)	Catalog Number	Insulated Throat Catalog Number	Dimensions in Inches			Flex. Opening
			Body Length	Thread Length	Max. Width	
$\frac{3}{8}$ ( $\frac{1}{2}$ KO)	C-5		$\frac{9}{16}$	$\frac{7}{16}$	$1\frac{1}{8}$	$\frac{1}{2} - \frac{19}{32}$
$\frac{1}{2}$	C-8	C-8T	$\frac{15}{16}$	$\frac{1}{2}$	$1\frac{9}{16}$	$\frac{25}{32} - \frac{15}{16}$
$\frac{3}{4}$	24-34	24-34T	$1\frac{1}{8}$	$\frac{1}{2}$	$1\frac{3}{4}$	$\frac{29}{32} - 1\frac{5}{64}$
1	24-100	24-100T	$1\frac{3}{16}$	$\frac{9}{16}$	$2\frac{3}{16}$	$1\frac{9}{32} - 1\frac{7}{16}$
$1\frac{1}{4}$	24-125	24-125T	$1\frac{1}{4}$	$\frac{5}{8}$	$2\frac{1}{2}$	$1\frac{7}{16} - 1\frac{5}{8}$
$1\frac{1}{2}$	24-150	24-150T	$1\frac{1}{8}$	$1\frac{1}{16}$	$2\frac{3}{8}$	$1\frac{5}{8} - 1\frac{7}{8}$
2	24-200	24-200T	2	$\frac{3}{4}$	$3\frac{5}{16}$	$2\frac{3}{16} - 2\frac{3}{8}$
$2\frac{1}{2}$	24-250	24-250T	$2\frac{1}{16}$	$\frac{15}{16}$	$4\frac{1}{16}$	$2\frac{45}{64} - 2\frac{3}{64}$
3	24-300	24-300T	$2\frac{1}{4}$	$\frac{15}{16}$	$4\frac{5}{8}$	$3\frac{1}{8} - 3\frac{1}{2}$

### Type C-1

#### Set-Screw Connector

##### Use:

To ground and secure Armored Cable to boxes and enclosures.

##### Features:

- Male hub threads (NPS)
- Cable stop.
- UL Listed for armored cable.
- Furnished with locknuts.

##### Materials/Finish:

Malleable Iron/Zinc Plated

##### Third Party Certification:




UL Listed: 11852



CSA Certified: 9795

Trade Size (inches)	Catalog Number	Body Length	Dimensions in Inches		
			Thread Length	Max. Width	Flex. Opening
$\frac{3}{8}$ ( $\frac{1}{2}$ KO)	C-1Z	$\frac{9}{16}$	$\frac{13}{32}$	1	$\frac{27}{64} - \frac{5}{8}$



Type C-1Z

UL Listed flexible metal conduit fittings are suitable for use in Hazardous Location under NEC 501-4(b) Class I, Div. II, and suitable as a grounding means under NEC 350-5.

##### Applicable Third Party Standards:

UL Standard: 514B

CSA Standard C22.2 No. 18

Fed. Spec: W-F-406E

NEMA: FB-1