

# Reducing Bushings

## Type RB

### Flush Type Reducers

#### Use:

To reduce the trade size of a tapped hole or hub.

#### Features:

- Tapered threads (NPT)
- Smooth internal bushing protects conductors.
- Threaded for Rigid Conduit or IMC.

#### Material/Finish:

##### RB-320S to RB-330S

Steel/Zinc Electroplated

##### RB-331 to RB-357

Malleable Iron/Zinc Electroplated

##### RB-321A to RB-357A

Copper-free Aluminum/Natural Finish

#### Third Party Certification:



UL Listed: E-34997

##### RB-321S through RB-330S

##### RB-321A through RB-330A

Class I, Div. 1, 2, Groups A, B, C, D

Class I, Zone 1, 2, Groups IIA, IIB, IIC

Class II, Div. 1, 2, Groups E, F, G

Class III

##### RB-331 through RB-357

##### RB-331A through RB-357A

Class I, Div. 1, 2, Groups B, C, D

Class I, Zone 1, 2, Groups IIA, IIB + H<sub>2</sub>

Class II, Div. 1, 2, Groups E, F, G

Class III



CSA Certified: 009795

#### Applicable Third Party Standards:


UL Standard: 886

CSA Standard: C22.2 No. 30

NEC Articles 500-503 & 505

Trade Size (inches)	Steel/Iron Catalog Number	Aluminum Catalog Number	Dim. in Inches Body Length
1/2 - 3/8	RB-320S*		
3/4 - 1/2	RB-321S	RB-321A	23/32
1 - 3/4	RB-322S	RB-322A	23/32
1 - 1/2	RB-323S	RB-323A	23/32
1 1/4 - 1/2	RB-324S	RB-324A	13/16
1 1/4 - 3/4	RB-325S	RB-325A	13/16
1 1/4 - 1	RB-326S	RB-326A	13/16
1 1/2 - 1 1/4	RB-327S	RB-327A	13/16
1 1/2 - 1	RB-328S	RB-328A	13/16
1 1/2 - 3/4	RB-329S	RB-329A	13/16
1 1/2 - 1/2	RB-330S	RB-330A	13/16
2 - 1 1/2	RB-331	RB-331A	7/8
2 - 1 1/4	RB-332	RB-332A	7/8
2 - 1	RB-333	RB-333A	7/8
2 - 3/4	RB-334	RB-334A	7/8
2 - 1/2	RB-335	RB-335A	7/8
2 1/2 - 2	RB-336	RB-336A	1
2 1/2 - 1 1/2	RB-337	RB-337A	1
2 1/2 - 1	RB-339	RB-339A	1
3 - 1 1/2	RB-340	RB-340A	1 1/4
3 - 2	RB-341	RB-341A	1 1/4
3 - 2 1/2	RB-342	RB-342A	1 1/4
3 1/2 - 3	RB-349	RB-349A	1 3/8
3 1/2 - 2 1/2	RB-350	RB-350A	1 3/8
4 - 2	RB-351	RB-351A	1 1/2
4 - 2 1/2	RB-355	RB-355A	1 1/2
4 - 3	RB-356	RB-356A	1 1/2
4 - 3 1/2	RB-357	RB-357A	1 1/2

\* Not UL Listed — Non-Hazardous



Type RB