

# Gold Seal Strain Relief Connectors

## Type SR

### Straight Strain Relief

#### Features:

- Tapered threaded male hub NPT
- Watertight/Oiltight
- PVC grommets
- Rated at 90°C

#### Material/Finish:

Malleable Iron/Zinc Plated

#### Third Party Certification:




UL Listed: E-11857



CSA Certified: 9795

#### Note:

1. Gold Seal connectors available with insulated throat, consult factory.
2. For multi-hole applications, consult factory.



Type SR-502

Catalog Number	Cable Range (in.)		Hub Size (inches)	Throat I.D.	Dimensions in Inches		
	Min.	Max.			Body Length	Thread Length	Max. Dia.
SR-502	.100	.200	½	.52	1½	¾	1⅞
SR-503	.200	.300	½	.52	1½	¾	1⅞
SR-504	.300	.400	½	.52	1½	¾	1⅞
SR-505	.400	.500	½	.61	1⅜	¾	1⅞
SR-505-55	.455	.555	½	.61	1⅜	¾	1⅞
SR-506	.500	.600	½	.61	1⅜	¾	1⅞
•SR-507	.600	.700	½	.61	1⅜	¾	1⅞
SR-752	.100	.200	¾	.76	1⅜	¾	1⅞
SR-753	.200	.300	¾	.76	1⅜	¾	1⅞
SR-754	.300	.400	¾	.76	1⅜	¾	1⅞
SR-755	.400	.500	¾	.76	1⅜	¾	1⅞
SR-756	.500	.600	¾	.76	1⅜	¾	1⅞
SR-757	.600	.700	¾	.76	1⅜	¾	1⅞
SR-758	.700	.800	¾	.80	1¼	¾	1⅞
•SR-759	.800	.900	¾	.80	1¼	¾	1⅞
•SR-7510	.900	1.000	¾	.80	1¼	¾	1⅞
SR-1002	.100	.200	1	.96	1¼	¾	1⅞
SR-1003	.200	.300	1	.96	1¼	¾	1⅞
SR-1004	.300	.400	1	.96	1¼	¾	1⅞
SR-1005	.400	.500	1	.96	1¼	¾	1⅞
SR-1006	.500	.600	1	.96	1¼	¾	1⅞
SR-1007	.600	.700	1	.96	1¼	¾	1⅞
SR-1008	.700	.800	1	.96	1¼	¾	1⅞
SR-1009	.800	.900	1	.96	1¼	¾	1⅞
•SR-10010	.900	1.000	1	.96	1¼	¾	1⅞
•SR-10012	1.000	1.200	1	.96	1¼	¾	1⅞
SR-12510	.900	1.000	1¼	1.20	1¾	¾	2⅞
SR-12512	1.000	1.200	1¼	1.20	1¾	¾	2⅞
•SR-12514	1.200	1.400	1¼	1.22	1¾	¾	2⅞
SR-15012	1.000	1.200	1½	1.50	1⅞	¾	2⅞
SR-15014	1.200	1.400	1½	1.50	1⅞	¾	2⅞
•SR-15016	1.400	1.600	1½	1.56	1⅞	¾	3
•SR-15018	1.600	1.800	1½	1.56	1⅞	¾	3
SR-20014	1.200	1.400	2	1.93	2⅞	¾	3
SR-20016	1.400	1.600	2	1.93	2⅞	¾	3
SR-20018	1.600	1.800	2	1.93	2⅞	¾	3
SR-25018	1.500	1.800	2½	2.44	2½	1⅞	4⅞
SR-25021	1.800	2.100	2½	2.44	2½	1⅞	4⅞
SR-25024	2.100	2.400	2½	2.44	2½	1⅞	4⅞
SR-30018	1.500	1.800	3	2.44	2½	1⅞	4⅞
SR-30021	1.800	2.100	3	2.44	2½	1⅞	4⅞
SR-30024	2.100	2.400	3	2.44	2½	1⅞	4⅞

\*Remove enough jacket to get conductors through Throat I.D.