




# Wrenches

## OPEN END WRENCHES

- Satin finish provides corrosion resistance and a slip resistant grip.
- 15° angle heads.
- Special heat-treated alloy steel permits slim shanks for strength and durability.
- Standard open end configuration.



Product ID No.	 in.	B	C	D	B1	C1	D1	L	Weight lbs.	ASME Spec.
J3016	3/16" x 1/4"	17/64"	1/2"	5/32"	1/4"	7/16"	5/32"	3-7/8"	0.04 lbs.	ASME B107.100
J3018	1/4" x 5/16"	3/8"	21/32"	3/16"	19/64"	35/64"	5/32"	4-31/64"	0.07 lbs.	ASME B107.100
J3020	5/16" x 3/8"	7/16"	25/32"	13/64"	3/8"	41/64"	13/64"	5-1/8"	0.09 lbs.	ASME B107.100
J3021	3/8" x 7/16"	23/64"	29/32"	7/22"	7/16"	25/32"	7/32"	5-3/4"	0.12 lbs.	ASME B107.100
J3025	7/16" x 1/2"	19/32"	1-1/32"	1/4"	29/32"	29/32"	1/4"	6-3/8"	0.19 lbs.	ASME B107.100
J3026	1/2" x 9/16"	43/64"	1-3/16"	17/64"	19/32"	1-1/32"	17/64"	7"	0.23 lbs.	ASME B107.100
J3030	9/16" x 5/8"	3/4"	1-17/64"	9/32"	11/16"	1-5/32"	9/32"	7-5/8"	0.28 lbs.	ASME B107.100
J3031	5/8" x 3/4"	29/32"	1-37/64"	5/16"	47/64"	1-5/32"	5/16"	8-9/16"	0.39 lbs.	ASME B107.100
J3034	5/8" x 11/16"	53/64"	1-13/32"	5/16"	3/4"	1-9/32"	5/16"	8-1/4"	0.35 lbs.	ASME B107.100
J3035	11/16" x 3/4"	29/32"	1-37/64"	21/64"	53/64"	1-13/32"	21/64"	8-7/8"	0.47 lbs.	ASME B107.100
J3037	11/16" x 25/32"	57/64"	1-37/64"	21/64"	53/64"	1-13/32"	21/64"	8-7/8"	0.46 lbs.	ASME B107.100
J3039	3/4" x 7/8"	1-1/16"	1-25/32"	11/32"	29/32"	1-37/64"	11/32"	9-1/2"	0.60 lbs.	ASME B107.100
J3040	13/16" x 7/8"	1-3/64"	1-25/32"	23/64"	63/64"	1-21/32"	23/64"	10-1/8"	0.62 lbs.	ASME B107.100
J3045	15/16" x 1"	1-13/64"	2-1/64"	13/32"	1-1/8"	1-29/32"	13/32"	11-1/2"	0.92 lbs.	ASME B107.100
J3050	1-1/16" x 1-1/8"	1-23/64"	2-17/64"	29/64"	1-9/32"	2-5/32"	29/64"	12-5/8"	1.24 lbs.	ASME B107.100
J3051	1-1/16" x 1-1/4"	1-31/64"	2-33/64"	15/32"	1-9/32"	2-5/32"	15/32"	13-9/16"	1.47 lbs.	ASME B107.100
J3055	1-1/4" x 1-5/16"	1-9/16"	2-21/32"	33/64"	1-31/64"	2-33/64"	33/64"	14-1/2"	1.87 lbs.	ASME B107.100
J3060	1-3/8" x 1-7/16"	1-23/32"	2-57/64"	35/64"	1-41/64"	2-23/32"	35/64"	15-3/4"	2.59 lbs.	ASME B107.100
J3070	1-1/2" x 1-5/8"	1-15/16"	3-17/64"	39/64"	1-25/32"	2-61/64"	39/64"	17"	3.31 lbs.	ASME B107.100
J3075	1-11/16" x 1-13/16"	2-3/16"	3-41/64"	45/64"	2"	3-25/64"	45/64"	18-1/2"	4.71 lbs.	ASME B107.100
J3080	1-7/8" x 2"	2-3/8"	4-1/32"	49/64"	2-11/64"	3-41/64"	45/64"	20"	6.38 lbs.	ASME B107.100

