



R14

R16

S11

T6.5

T8

T10

A21

BR30

R20

A19

GENERAL PURPOSE LAMPS

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Description	Class & Filament	Avg Rated Life (hrs)	Lumens Beam Angle CBCP	LCL (in)	MOL (in)			
40	R14	Med	14819	●	40R14/RP	120	6	Reflector Mini Flood	C, C-9	1500	185		2.25			
	R16	Med	14821	●	40R16/FL/RP	120	6	Reflector Mini Flood	C, C-9	1500			3.88			
	S11	Intermediate	13595	●☀	40S11N	120	120	Clear Hi Intensity	C, C-7A	500	440	1.63	2.31			
			13607	●☀	40S11N/BL	120	12	Clear Hi Intensity	C, C-7A	500	440	1.63	2.31			
			13644	●☀	40S11N/BL/2/12	120	12	Clear Hi Intensity	C, C-7A	500	440	1.63	2.31			
			13640	●☀	40S11N/NEO/BULK	120	6000	Neodymium doped Hi Intensity	C, C-7A	500		1.63	2.31			
	T6.5	Intermediate	18096	☀ ₁₃₀	40T6.5/2	120	60	Clear Appliance	C, C-8	1000	365		5.50			
			18497	☀	40T6.5/CL/BL/10PK	120	10	Clear Appliance	C, C-8	1000	365		5.50			
			18152	☀	40T6.5/CL/BL/6PK	120	6	Clear Appliance	C, C-8	1000	365		5.50			
	T8	Intermediate	18358	☀	40T8N/NEODYMIUM	120	6000	Neodymium Doped Appliance	B, C-7A	1000	300	1.31	2.63			
	T10	Med	18650	●☀	40T10	120	60	Clear	B, C-8	1000	420		5.63			
			18493	●☀	40T10/CL/BL/6PK	120	6	Clear	B, C-8	1000	420		5.63			
			18652	●☀	40T10	130	60	Clear	B, C-8	1000	420		5.63			
			18494	●☀	40T10/IF/BL/6PK	120	6	Inside Frost	B, C-8	1000	415		5.63			
			18669	●☀	40T10/IF	130	60	Inside Frost	B, C-8	1000	415		5.63			
45 95 140	A21	3 CONTACT Med	18048	●▼	45/140A21/W/ES/RP	120	12	Soft White 3-way Energy Saver	C, CC-8	1200	540lm 1300lm 1840lm	3.38	5.31			
45	BR30	Med	15103	●☀ _{2,46,57,155}	45BR30/FL/RP	120	6	Reflector Flood	C, CC-6	2000	350lm 170 cd 60°		5.38			
			R20	Med	15677	● _{2,46,68,155}	45R20/DAY/1/6/RP	120	6	Daylight Reflector	C, C-9	2000	215lm 360 cd 45°		3.94	
				15697	● _{2,46,68,155}	45R20	120	60	Reflector Flood	C, C-9	2000	295lm 490 cd 45°		3.94		
				14997	● _{2,46,68,155}	45R20/RP/2/12	120	12	Reflector Flood	C, C-9	2000	295lm 490 cd 45°		3.94		
				15670	● _{2,46,68,155}	45R20/RP	120	6	Reflector Flood	C, C-9	2000	295lm 490 cd 45°		3.94		
				15699	● _{2,46,68,105,136,155}	45R20	130	60	Reflector Flood	C, C-9	2000	490 cd 45°		3.94		
				<i>@ 120_volts, approximate 40 watts, 220 lumens, 5000 hours.</i>												
				15676	● _{2,46,68,105,136,155}	45R20/CVP	130	6	Reflector Flood	C, C-9	2000	490 cd 45°		3.94		
				<i>@ 120_volts, approximate 40 watts, 220 lumens, 5000 hours.</i>												
		Med Brass		15698	_{2,46,68,155}	45R20/DL/RP	120	6	Double Life Reflector Flood	C, C-9	4000	260 430 cd 45°		3.94		
50	A19	Med	11096	●	50A/RS/4/144/RP	120	144	Inside Frost Rough Service	C	1000	510					
			14070	●	50A/RS/2/RP	120	24	Inside Frost Rough Service	C	1000	510					
			11393	●	50A/RS	250	120	Inside Frost Rough Service	C, C-22	1000	450	2.50	4.44			