



GENERAL PURPOSE LAMPS

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Description	Class & Filament	Avg Rated Life (hrs)	Lumens CBCP	Beam Angle (in)	LCL (in)	MOL (in)	
50	A19	Med	11397	●	50A	250	120	Inside Frost	B, CC-7A	1000	490	2.50	4.44		
			11428	●	50A	277	120	Inside Frost	B, CC-7A	1000	475	2.50	4.44		
	Med Brass		11118	116	50A/RS/SL	120	120	Safeline Rough Service	C, C-9	1000	490	2.50	3.94		
			11068	133	50A19/RS	75	120	Inside Frost Rough Service Train	C, C-9	1000	505	2.50	3.94		
50 100 150	A21	3 CONTACT Med	18110	●▼	50/150/DAY/1/12	120	12	Daylight 3-way	C, CC-8	1200	460lm 1170lm 1630lm	3.38	5.31		
			18168	●▼	50/150A21DL/SW/1/48	120	48	Soft White Double Life 3-way	C, CC-8	2400	540lm 1400lm 1940lm	3.38	5.31		
			18044	●▼	50/150A21/DL/SW/RP	120	12	Soft White Double Life 3-way	C, CC-8	2400	540lm 1400lm 1940lm	3.38	5.31		
			18457	●▼	50/150A21/W/2/48	120	48	Soft White 3-Way	C, CC-8	1200	640lm 1570lm 2210lm	3.38	5.31		
			18028	●▼	50/150A/W/DIYPACK	120	48	Soft White 3-way	C, CC-8	1200	640lm 1570lm 2210lm	3.38	5.31		
			18458	●▼	50/150A21/W/2PK/12	120	12	Soft White 3-Way	C, CC-8	1200	640lm 1570lm 2210lm	3.38	5.31		
			18060	●▼	50/150A21/W/RP	120	12	Soft White 3-way	C, CC-8	1200	640lm 1570lm 2210lm	3.38	5.31		
			18726	●▼	50/150A21/SPK/RP	120	12	Soft Pink 3-way	C, CC-8	1200		3.38	5.31		
			19404	●▼	50/250A21/W/RP	120	12	Soft White Reading Light 3-way	C, CC-8	1200	640lm 3300lm 3940lm	3.38	5.31		
50	A21	Med Brass	11572	⊗	50A21	12	24	Inside Frost RV-Marine	C, C-6	1000	865	3.88	4.94		
			11567	⊗	50A21/RP	12	12	Inside Frost RV-Marine	C, C-6	1000	865	3.88	4.94		
			11603	⊗	50A21	34	12	Inside Frost Train	C, C-9	1000	800	3.44	4.94		
	ER30 Med		15102	● _{2,155}	50ER30	120	24	Elliptical Reflector Flood	C, CC-6	2000	350lm 800 cd 30°		6.38		
			15110	● _{2,155}	50ER30/RP	120	6	Elliptical Reflector Flood	C, CC-6	2000	350lm 800 cd 30°		6.38		
			15107	● _{2,136,155,159}	50ER30	130	24	Elliptical Reflector Flood	C, CC-6	2000	320lm 730 cd 30°		6.38		
	<i>@ 120_volts, approximate 44 watts, 240 lumens, 5000 hours</i>														
	R20 Med		15231	● _{2,46,68,107,155}	50R20/DAY/1/6/RP	120	6	Daylight Reflector	C, C-9	2000	240lm 400 cd 45°		3.94		
			14831	● _{2,46,68,107,155}	50R20	120	60	Reflector Flood	C, C-9	2000	330lm 550 cd 45°		3.94		
			14914	● _{2,46,68,107,155}	50R20/2PK	120	48	Reflector Flood	C, C-9	2000	330lm 550 cd 45°		3.94		
		14998	● ₁₀₇	50R20/RP/2/12	120	12	Reflector Flood	C, C-9	2000	330lm 550 cd 45°		3.94			