



GENERAL PURPOSE LAMPS

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Description	Class & Filament	Avg Rated Life (hrs)	Lumens Beam Angle CBCP	LCL (in)	MOL (in)
50	R20	Med	14833	● _{2,46,68,107,155}	50R20/RP	120	6	Reflector Flood	C, C-9	2000	330lm 550 cd 45°		3.94
			14832	● _{2,46,68,107,136,155,158}	50R20	130	60	Reflector Flood	C, C-9	2000	330lm 550 cd 45°		3.94
			<i>@ 120_volts, approximate 44 watts, 250 lumens, 5000 hours</i>										
			14844	● _{2,46,68,107,136,155,158}	50R20/CVP	130	6	Reflector Flood	C, C-9	2000	330lm 550 cd 45°		3.94
			<i>@ 120_volts, approximate 44 watts, 250 lumens, 5000 hours</i>										
			14846	● _{2,46,68,136,155}	50R20/PINK	130	60	Pink Reflector	C, C-9	2000	420lm		3.94
		Med Brass	15346	● _{2,46,68,107,155}	50R20/DL/1/48	120	48	Double Life Reflector Flood	C, C-9	4000	290lm 480 cd 45°		3.94
			14943	● _{2,46,68,107,155}	50R20/DL/RP	120	6	Double Life Reflector Flood	C, C-9	4000	290lm 480 cd 45°		3.94
			14834	● _{2,46,68,155}	50R20/PINK	120	60	Pink Reflector	C, C-9	2000			3.94
			14842	● _{2,46,68,155}	50R20/GRO	120	6	Spot-GRO Reflector	C, C-9	2000			3.94
52	A19	Med	11392	● _{104,136}	60A/52/W/ES/4PK	120	48	Soft White Energy Saver	C, CC-8	1000	715	3.13	4.44
			10893	● _{104,136}	60A/52/CL/SS	130	48	Clear SuperSaver	C, CC-8	1000	740	3.13	4.44
			<i>@ 120_volts, approximate 46 watts, 560 lumens, 2500 hours.</i>										
			11376	● _{136,164}	60A/52/SS	120	48	Standard Frost SuperSaver	C, CC-8	1000	750	3.13	4.44
			11380	● _{136,164}	60A/52/SS	130	48	Standard Frost SuperSaver	C, CC-8	1000	710	3.13	4.44
			<i>@ 120_volts, approximate 46 watts, 540 lumens, 2500 hours</i>										
		Med Brass	11384	● _{136,163}	60A/52/SS/XL	120	48	Standard SuperSaver XL	C, CC-8	2500	620	3.13	4.44
			11388	● _{136,163}	60A/52/SS/XL	130	48	Standard SuperSaver XL	C, CC-8	2500	610	3.13	4.44
			<i>@ 120_volts, approximate 46 watts, 460 lumens, 6250 hours</i>										
58	A19	Med Brass	11149	●	58A19/62	120	120	Clear Street Lighting Group Replacement	C, C-9	3000	630	2.88	4.25
60	A15	Candelabra	10777	●	60A15C/SW/FAN/2/12/BL	120	12	Soft White Ceiling Fan Light	C, C-9	1000	510	1.94	3.38
			10894	●	60A15C/CL/FAN/2/12/BL	120	12	Clear Ceiling Fan Light	C, C-9	1000	560	1.94	3.38
		Med	10162	●	60A15/DAY/FAN/BL/2/24	120	24	Daylight Fan	C, C-9	1000	340	2.38	3.50
			10868	●	60A15/DL/SW/BL/2/24	120	24	Soft White Double Life Fan Light	C, C-9	2000	510	2.38	3.50
			10885	●	60A15/SW/FAN/2/12/BL	120	12	Soft White Double Life Fan Light	C, C-9	1000	680	2.38	3.50
			10048	●	60A15/CL/DL/FAN/RP	120	24	Clear Double Life Fan Light	C, C-9	2000	530	2.38	3.50
			10024	●	60A15/CL/DL/FAN/BL/2/24	120	24	Clear Double Life Fan Light	C, C-9	2000	530	2.38	3.50
			10040	●	60A15/CL/DL/FAN/2/12/BL	120	12	Clear Double Life Fan Light	C, C-9	2000	530	2.38	3.50
			11005	●	60A15/SW/FAN/2PK	120	24	Soft White Ceiling Fan	C, C-9	1000	680	2.38	3.50
			10842	●	60A15/SW/FAN/BL/2/24	120	24	Soft White Ceiling Fan	C, C-9	1000	680	2.38	3.50
			10841	●	60A15/CL/FAN/BL/2/24	120	24	Clear Ceiling Fan Light	C, C-9	1000	700	2.38	3.50