



BR30, BR40



PAR38



A19

GENERAL PURPOSE LAMPS

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Description	Class & Filament	Avg Rated Life (hrs)	Lumens Beam Angle CBCP	LCL (in)	MOL (in)
65	BR30	Med Brass	15177	2,46,57,155	65BR30/DL/FL/RP	120	6	Double Life Reflector Flood	C, CC-6	4000	510lm 300 cd 60°		5.38
	BR40	Med	15360	46,57,155	65BR/FL/24	120	24	Reflector Flood	C, CC-6	2000	580lm 390 cd 60°		6.50
			15678	46,57,155	65BR/FL/RP	120	6	Reflector Flood	C, CC-6	2000	580lm 390 cd 60°		6.50
			15679	46,57,106,136,155	65BR/CVP	130	6	Reflector Flood	C, CC-6	2000	540lm 390 cd 60°		6.50
			<i>@ 120_volts, approximate 57 watts, 410 lumens, 5000 hours.</i>										
	Med Brass		15332	46,57,155	65BR/DL/FL/RP	120	6	Double Life Reflector Flood	C, CC-6	4000	510lm 335 cd 60°		6.50
	PAR38	Med Skt	13804		65PAR/SP	120	15	Spot Super Saver	C, CC-6	1750	715lm 5500 cd 12°		5.31
			13802		65PAR/FL	120	15	Flood Super Saver	C, CC-6	1750	715lm 1700 cd 30°		5.31
			13805	136,173	65PAR/FL	130	15	Flood Super Saver	C, CC-6	1750	715lm 1700 cd 30°		5.31
			<i>@ 120_volts, approximate 57 watts, 540 lumens, 4375 hours</i>										
67	A19	Med	11394		75A/67/W/ES/4PK	120	48	Soft White Energy Saver	C, CC-8	750	1040	3.13	4.44
			11377		75A/67/SS	120	48	Standard Frost SuperSaver	C, CC-8	750	1050	3.13	4.44
			11381	136,175	75A/67/SS	130	48	Standard Frost SuperSaver	C, CC-8	750	1020	3.13	4.44
			<i>@ 120_volts, approximate 59 watts, 780 lumens, 1875 hours</i>										
	Med Brass		11385	108	75A/67/SSXL	120	48	Standard Frost SuperSaver XL	C, CC-8	2500	880	3.13	4.44
			11389	108,136,174	75A/67/SSXL	130	48	Standard Frost SuperSaver XL	C, CC-8	2500	860	3.13	4.44
			<i>@ 120_volts, approximate 59 watts, 660 lumens, 6250 hours</i>										
75	A19	Med	10863		75A/DAY/4/160/RP	120	160	Daylight	C, CC-8	750	850	3.13	4.44
			10865		75A/DAY/RP/4/48	120	48	Daylight	C, CC-8	750	850	3.13	4.44
			11102		75A/DAY/RP/2/24	120	24	Daylight	C, CC-8	750	850	3.13	4.44
			10776	102,136	75A/DAY/RP/4/48	130	48	Daylight	C, CC-8	750	850	3.13	4.44
			<i>@ 120_volts, approximate 66 watts, 650 lumens, 1875 hours.</i>										
			11331		75A/W/DL/SW/4PK/RP	120	48	Soft White Double Life	C, CC-8	1500	1055	3.13	4.44
			11337		75A/DL/SW/2PK/RP	120	24	Soft White Double Life	C, CC-8	1500	1055	3.13	4.44
			11175		75A/CL/DL/RP	120	24	Clear Double Life	C, CC-8	1500	1085	3.13	4.44
			13001		75A/RS/2/RP	120	24	Inside Frost Rough Service	C, C-9	1000	818	2.88	4.44
			12579		75A/RS/RP/1	120	12	Inside Frost Rough Service	C, C-9	1000	818	2.88	4.44
			12586	136,179	75A/RS/RP/1	130	24	Inside Frost Rough Service	C, C-9	1000	818	2.88	4.44
			<i>@ 120_volts, approximate 66 watts, 620 lumens, 2500 hours</i>										