



A21



A23



BR38



PAR38




PAR38 Side Prong



PAR46



PS25



T10

GENERAL PURPOSE LAMPS

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Description	Class & Filament	Avg Rated Life (hrs)	Lumens Beam Angle CBCP	LCL (in)	MOL (in)
150	A21	Med	13101	●	150A21/W/RP	120	12	Soft White	C, CC-8	750	2640	3.88	5.31
			13125	●	150A21/CL/RP	120	12	Clear Utility Light	C, CC-8	750	2780	3.88	5.31
			13148	● ^{12,136}	150A21/CL <i>@ 120_volts, approximate 132 watts, 2030 lumens, 1875 hours</i>	130	48	Clear	C, CC-8	750	2730	3.88	5.31
			13141	●	150A21	120	48	Standard Frost	C, CC-8	750	2740	3.88	5.31
			13165	●	150A21/IF/RP	120	12	Standard Frost Utility Light	C, CC-8	750	2740	3.88	5.31
			13153	● ^{12,136}	150A21 <i>@ 120_volts, approximate 132 watts, 2030 lumens, 1875 hours</i>	130	48	Standard Frost	C, CC-8	750	2670	3.88	5.31
			13177	108	150A21/99/XL	120	48	Standard Frost Excel	C, CC-8	2500	2225	3.88	5.31
			13178	10,108,136	150A21/99/XL <i>@ 120_volts, approximate 132 watts, 1690 lumens, 6250 hours</i>	130	48	Standard Frost Excel	C, CC-8	2500	2225	3.88	5.31
A23	Med	15241	●	150A23/RS	120	48	Inside Frost Rough Service	C, C-17	1000	2090	4.38	6.06	
		15243	● ^{7,136}	150A23/RS <i>@ 120_volts, approximate 132 watts, 1590 lumens, 2500 hours</i>	130	48	Inside Frost Rough Service	C, C-17	1000	2090	4.38	6.06	
		13041	●	150A23	120	48	Inside Frost	C, CC-8	750	2810	4.63	6.06	
BR38	Med Brass	15608	★ ^{2,107,119,155}	150/OPAR/FL	120	12	Outdoor Reflector Economy Flood	C, CC-6	2000	1350lm 45°		5.31	
PAR38	Med Skt	13921	★ ^{8,119}	150PAR/SP <i>@ 120_volts, approximate 132 watts, 1660 lumens, 1875 hours</i>	130	15	Spot	C, CC-6	750	2175lm 18000 cd 12°		5.31	
		13922	★ ^{8,119}	150PAR/FL <i>@ 120_volts, approximate 132 watts, 1660 lumens, 1875 hours</i>	130	15	Flood	C, CC-6	750	2175lm 4500 cd 30°		5.31	
		13853	★ ¹⁸⁸	150PAR/3FL	120	12	Compact Flood	C, CC-6	2000	2175lm 4000 cd 30°		4.31	
PAR46	Med Side Prong	15375	★ ^{67,117,188}	150PAR46/3NSP 125-	125	12	Narrow Spot	C, CC-2V	2000	1500lm 17500 cd 8x12 VH		4.00	
	Screw Term	15190	★ ^{67,188}	150PAR46	130	12	Clear Mine Headlamp	C, C-13	1000	1250lm 8x15 VH		3.75	
PS25	Med	15276	● ¹⁰⁸	150PS25/IF	120	60	Inside Frost	C, C-9	1000	2340	5.25	6.94	
		15282	● ^{9,108,136}	150PS25 <i>@ 120_volts, approximate 132 watts, 1770 lumens, 1875 hours</i>	130	60	Inside Frost	C, C-9	750	2330	5.25	6.94	
	Med Brass	15293	116	150PS25/SL	120	60	Safeline Rhinocoat (Shatter Protected)	C, C-9	1000	2200	5.25	6.94	
		15300	116	150PS25/RS/SL	120	60	Safeline Rough Service	C, C-17	1000	2145	4.38	5.94	
		15431	5,108,136	150PS25/99/XL <i>@ 120_volts, approximate 132 watts, 1420 lumens, 6250 hours</i>	130	60	Inside Frost Excel-Line	C, C-9	2500	1870	5.25	6.94	
T10	S14s	19690	▽	LN150 125-130	125	16	Opal White LINSTRA 1604	B, C-8	1000	930		39.38	
175	PAR38	Med Skt	13836	★ ^{24,46,155}	175W/PAR38/HEAT	120	15	Hard Glass PAR Heat Lamp	C, CC-6	5000			5.31
			13840	★ ^{24,46,155}	175 PAR38/HEAT/RED	120	15	Hard Glass PAR Heat Lamp with Red Lens	C	5000			
200	A21	Med	13103	●	200A21/W/1RP	120	12	Soft White	C, CC-8	750	3650	3.88	5.31