



A21

A23

PAR46

PAR56

PS25

PS30

BR38

BR40

GENERAL PURPOSE LAMPS

Watts	Bulb	Base	Product Number	Symbols & Footnotes	Ordering Abbreviation	Volts	Pkg Qty	Description	Class & Filament	Avg Rated Life (hrs)	Lumens Beam Angle CBCP	LCL (in)	MOL (in)
200	A21	Med	13107	●	200A21	120	24	Soft White Recessed Ceiling	C, CC-8	750	3650	3.88	5.31
			15476	●	200A21/CL/RP	120	12	Clear Utility Light	C, CC-8	750	3880	3.88	5.31
			15491	● _{21,136}	200A21/CL <i>@ 120_volts, approximate 176 watts, 2860 lumens, 1875 hours</i>	130	48	Clear	C, CC-8	750	3880	3.88	5.31
			15499	●	200A21/RP	120	12	Standard Frost Utility Light	C, CC-8	750	3850	3.88	5.31
			15543	● _{21,136}	200A21 <i>@ 120_volts, approximate 176 watts, 2860 lumens, 1875 hours</i>	130	48	Standard Frost	C, CC-8	750	3760	3.88	5.31
		Med Brass	15555	● _{22,136}	200A21/99/XL <i>@ 120_volts, approximate 176 watts, 2220 lumens, 6750 hours</i>	125	48	Standard Frost Excel	C, CC-8	2500	2910	3.88	5.31
A23	Med		15458	● _{15,136}	200A23/RS	130	48	Inside Frost Rough Service <i>@ 120_volts, approximate 176 watts, 2220 lumens, 2500 hours</i>	C, C-17	1000	2920	4.38	5.88
			15505	●	200A23	120	48	Inside Frost	C, CC-8	750	3930	4.63	6.06
PAR46	Med Side Prong		15191	★ ₁₈₈	200PAR46/3NSP	120	12	Narrow Spot	C, CC-13	2000	2270lm 31000 cd 8x12 VH		4.00
			15194	★ ₁₈₈	200PAR46/3MFL	120	12	Med Flood	C, CC-13	2000	2270lm 11500 cd 15x25 VH		4.00
			15196	★ ₁₈₈	200PAR46/3MFL 125-	125	12	Med Flood	C, CC-13	2000	2270lm 11500 cd 15x25 VH		4.00
PAR56	Mog End Prong		15007	★ _{57,117,188}	200PAR56/MFL	120	12	Med Flood Clear	C, CC-13	2000	2270lm 15000 cd 15x20 VH		5.00
			14968	★	200PAR56	30	12	Locomotive Headlamp	C, CC-8	500	3700lm 27000 cd 9x9 VH		4.50
PS25	Med		15600	● _{20,136}	200PS25 <i>@ 120_volts, approximate 176 watts, 2820 lumens, 1875 hours</i>	130	60	Inside Frost	C, CC-6	750	3700	5.25	6.94
			15818	● _{17,136}	200PS25/99/XL <i>@ 120_volts, approximate 176 watts, 2360 lumens, 6250 hours</i>	130	60	Inside Frost Excel-Line	C, CC-6	2500	3000	5.25	6.94
PS30	Med		15675	● _{16,136}	200PS/23	130	60	Inside Frost Rough Service <i>@ 120_volts, approximate 176 watts, 2350 lumens, 2500 hours</i>	C, C-9	1000	3080	6.00	8.06
			15653	● _{18,136}	200PS/IF <i>@ 120_volts, approximate 176 watts, 2710 lumens, 1875 hours</i>	130	60	Inside Frost	C, C-9	750	3560	6.00	8.06
			15820	●	200/CL	277	60	Clear	C, C-9	1000	2360	6.00	8.06
			15687	116	200PS/23/SL	120	60	Safeline Rough Service	C, C-9	1000	3080	6.00	8.06
			15648	116	200PS/SL	120	60	Safeline	C, C-9	1000	3080	6.00	8.06
			15725	14,136	200PS/CL/99/XL <i>@ 120_volts, approximate 176 watts, 2190 lumens, 6250 hours</i>	130	60	Clear Excel-Line	C, C-9	2500	2875	6.00	8.06
202	PS25	Med Brass	15581	57	202PS25/CL	125	60	Clear Street Lighting Group Replacement	C, C-9	6000	2750	5.25	6.94
250	BR38	Med Brass	14661	★ _{25,46,136}	250K/BR38/FL <i>@ 120_volts, approximate 220 watts, 2360 lumens, 10000 hours</i>	125	12	Reflector Flood Krypton	C, CC-6	4000	3100		5.81
			14665	● _{24,46,57,155}	250BR40	120	12	Reflector IR Heat Lamp Clear	C, CC-6	5000			6.50
	BR40	Med	14664	● _{24,46,57,155}	250BR40/1	120	6	Reflector IR Heat Lamp Clear	C, CC-6	5000			6.50