


11C43


Female Metric S - Swivel - 90° Elbow - (24° Cone with O-Ring)
ISO 12151-2 - SWE



# Part Number	Thread		Hose I.D. inch	A		E		W		B	
	inch	mm		inch	mm	inch	mm	mm	inch	mm	
11C43-8-4	8	M16x1,5	1/4	1.83	46	1.26	32	19	1.41	36	
11C43-10-4	10	M18x1,5	1/4	2.45	62	1.34	34	22	1.71	43	
11C43-12-5	12	M20x1,5	5/16	2.30	58	1.22	31	24	1.51	38	
11C43-12-6	12	M20x1,5	3/8	2.36	60	1.22	31	24	1.42	36	
11C43-14-6	14	M22x1,5	3/8	2.35	60	1.48	38	27	1.35	34	
11C43-16-8	16	M24x1,5	1/2	2.83	72	1.75	44	30	1.46	37	
11C43-20-10	20	M30x2	5/8	3.45	88	2.17	55	36	2.04	52	
11C43-25-12	25	M36x2	3/4	3.74	95	2.17	55	46	2.22	56	
11C43-30-16	30	M42x2	1	4.45	113	2.64	67	50	2.64	67	
11C43-38-20 ^M	38	M52x2	1-1/4	5.67	144	2.87	73	60	2.99	76	

1D943

Male BSP Parallel Pipe - Rigid - (60° Cone)
ISO 228-1




# Part Number	Thread inch	Hose I.D. inch	A		H mm	B	
			inch	mm		inch	mm
1D943-4-4	1/4x19	1/4	1.77	45	19	0.91	23
1D943-6-5	3/8x19	5/16	2.13	54	22	1.22	31
1D943-6-6	3/8x19	3/8	2.13	54	22	1.22	31
1D943-8-6	1/2x14	3/8	2.36	60	27	1.22	31
1D943-8-8	1/2x14	1/2	2.44	62	27	1.10	28
1D943-12-12	3/4x14	3/4	2.76	70	32	1.18	30
1D943-16-16	1x11	1	3.23	82	41	1.38	35

When used in a port, a bonded seal must be used. See Accessories Section for more information.

19243

Female BSP Parallel Pipe - Swivel - (60° Cone)
ISO 228-1



# Part Number	Thread inch	Hose I.D. inch	A		C		W mm	B	
			inch	mm	inch	mm		inch	mm
19243-2-4	1/8x28	1/4	1.61	41	0.20	5	14	0.67	17
19243-4-4	1/4x19	1/4	1.95	50	0.22	6	19	1.20	30
19243-6-4	3/8x19	1/4	1.73	44	0.26	7	22	0.79	20
19243-6-6	3/8x19	3/8	2.35	60	0.26	7	22	1.32	34
19243-6-8	3/8x19	1/2	2.17	55	0.26	7	22	0.79	20
19243-8-6	1/2x14	3/8	2.01	51	0.28	7	27	0.87	22
19243-8-8	1/2x14	1/2	2.72	69	0.28	7	27	1.46	37
19243-10-8	5/8x14	1/2	2.80	71	0.37	9	30	1.54	39
19243-10-10	5/8x14	5/8	2.99	76	0.37	9	30	1.55	39
19243-12-10	3/4x14	5/8	3.11	79	0.35	9	36	1.67	42
19243-12-12	3/4x14	3/4	3.19	81	0.35	9	36	1.75	44
19243-16-16	1x11	1	3.67	93	0.44	11	41	2.05	52
19243-20-20	1-1/4	1-1/4	3.11	79	0.41	11	50	1.26	32

When measuring overall length to the end of the nut, B+C dimensions must be used to calculate cut-off allowance.