


10691N-RD – SAE (JIC) 37° female swivel UNF swivel nut




MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
For stainless steel (AISI 316) please add **C** to the
Part No. Example: 10691N-5-5**C**-RD.
Other materials available on request.

Part No. #	DN size mm inch				Connection type		A mm	B mm	J inch	Max. WP MPa
					Thread size 	Tube OD inch 				
10691N-4-4-RD	5	-04	4.8	3/16	7/16 - 20UNF	1/4	34	21	9/16	41.0
10691N-5-5-RD	6	-05	6.4	1/4	1/2 - 20UNF	5/16	38	22	5/8	41.0
10691N-6-6-RD	8	-06	7.9	5/16	9/16 - 18UNF	3/8	41	24	11/16	34.5
10691N-8-8-RD	10	-08	10.3	13/32	3/4 - 16UNF	1/2	45	27	7/8	34.5
10691N-10-10-RD	12	-10	12.7	1/2	7/8 - 14UNF	5/8	49	30	1	34.5
10691N-12-12-RD	16	-12	15.9	5/8	1 1/16 - 12UNF	3/4	53	33	1 1/4	34.5
10691N-16-16-RD	22	-16	22.2	7/8	1 5/16 - 12UNF	1	58	33	1 1/2	27.5

NOTE RD series without hexagonal ferrule.

10691N – SAE (JIC) 37° female swivel UNF swivel nut



MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
For stainless steel (AISI 316) please add **C** to the
Part No. Example: 10691N-6-6**C**.
Other materials available on request.

Part No. #	DN size mm inch				Connection type		A mm	B mm	H inch	J inch	Max. WP MPa
					Thread size 	Tube OD inch 					
10691N-4-4	5	-04	4.8	3/16	7/16 - 20UNF	1/4	36	22	3/8	9/16	41.0
10691N-5-5	6	-05	6.4	1/4	1/2 - 20UNF	5/16	40	24	7/16	5/8	41.0
10691N-6-6	8	-06	7.9	5/16	9/16 - 18UNF	3/8	41	25	1/2	11/16	34.5
10691N-8-8	10	-08	10.3	13/32	3/4 - 16UNF	1/2	48	30	11/16	7/8	34.5
10691N-10-10	12	-10	12.7	1/2	7/8 - 14UNF	5/8	52	33	13/16	1	34.5
10691N-12-12	16	-12	15.9	5/8	1 1/16 - 12UNF	3/4	54	33	1	1 1/4	34.5
10691N-16-16	22	-16	22.2	7/8	1 5/16 - 12UNF	1	62	40	1 1/4	1 1/2	27.5
10691N-20-20	28	-20	28.6	1 1/8	1 5/8 - 12UNF	1 1/4	76	46	1 5/8	2	20.0