


10655 – SAE (JIC) 37° female swivel

UNF swivel nut



MATERIAL Galvanised steel with transparent Cr(VI)-free plating.
For stainless steel (AISI 316) please add **C** to the Part No. Example: 10655-4-3**C**.
Other materials available on request.

Part No. #	DN size			mm		inch		Connection type		A mm	B mm	H mm	J mm	Max. WP MPa
	Thread size	Tube OD inch	mm	inch	mm	inch	mm	inch						
10655-4-2	3	-02	3.2	1/8	7/16 - 20UNF	1/4	44	27	13	16	41.0			
10655-4-3	5	-03	4.8	3/16	7/16 - 20UNF	1/4	55	30	16	17	41.0			
10655-5-3	5	-03	4.8	3/16	1/2 - 20UNF	5/16	57	32	16	17	41.0			
10655-4-4	6	-04	6.4	1/4	7/16 - 20UNF	1/4	65	33	17	17	41.0			
10655-5-4	6	-04	6.4	1/4	1/2 - 20UNF	5/16	65	33	16	17	41.0			
10655-6-4	6	-04	6.4	1/4	9/16 - 18UNF	3/8	67	35	17	19	34.5			
10655-5-5	8	-05	7.9	5/16	1/2 - 20UNF	5/16	65	33	16	17	41.0			
10655-6-5	8	-05	7.9	5/16	9/16 - 18UNF	3/8	65	33	16	19	34.5			
10655-8-5	8	-05	7.9	5/16	3/4 - 16UNF	1/2	68	37	19	22	34.5			
10655-6-6	10	-06	9.5	3/8	9/16 - 18UNF	3/8	69	33	19	19	34.5			
10655-8-6	10	-06	9.5	3/8	3/4 - 16UNF	1/2	72	35	19	24	34.5			
10655-6-8	12	-08	12.7	1/2	9/16 - 18UNF	3/8	76	35	22	19	34.5			
10655-8-8	12	-08	12.7	1/2	3/4 - 16UNF	1/2	79	38	22	22	34.5			
10655-10-8	12	-08	12.7	1/2	7/8 - 14UNF	5/8	82	41	22	27	34.5			
10655-12-8	12	-08	12.7	1/2	1 1/16 - 12UNF	3/4	83	42	27	32	34.5			
10655-12-12	20	-12	19.0	3/4	1 1/16 - 12UNF	3/4	88	42	30	32	34.5			
10655-16-16	25	-16	25.4	1	1 5/16 - 12UNF	1	104	44	36	38	27.5			

55 series