





1KU43 Female Metric - Swivel Straight (30° Flare)





# Part Number	 Thread		 Hose		A		H	W	B	
					inch	mm	mm	mm	inch	mm
	mm	inch	inch	mm	mm	mm	mm	inch	mm	
1KU43-10-10	M24X1,5	-10	5/8	-10	3.23	82	32	32	1.80	46
1KU43-12-12	M30x1,5	-12	3/4	-12	3.38	86	36	36	1.95	50
1KU43-16-16	M33x1,5	-16	1	-16	3.93	100	41	41	2.33	59
1KU43-20-20	M36X1,5	-20	1-1/4	-20	4.15	105	46	46	2.50	64
1KU43-24-24	M42X1,5	-24	1-1/2	-24	4.07	103	55	55	2.75	70

1MU43 Female Metric - Swivel Straight (30° Flare)

Note: Japanese Fittings - Female Swivel 30° Flare with Metric Threads. Some Japanese equipment use 30° flare fittings with metric threads. The combination of the 1MU43 and 1MU71 fittings in sizes up to -8 and the 1XU43 and 1XU71 in sizes -10 and larger, all 30° flared fitting size requirements are available.



# Part Number	 Thread		 Hose		A		H	W	B	
					inch	mm	mm	mm	inch	mm
	mm	inch	inch	mm	mm	mm	mm	inch	mm	
1MU43-4-4	M14x1,5	-4	1/4	-4	2.08	53	19	19	1.12	28
1MU43-4-6+	M14x1,5	-4	3/8	-6	2.35	60	19	19	1.35	34
1MU43-4-8+	M14x1,5	-4	1/2	-8	2.56	65	22	22	1.30	33
1MU43-6-4	M18x1,5	-6	1/4	-4	2.19	56	24	24	1.46	37
1MU43-6-6	M18x1,5	-6	3/8	-6	2.32	59	24	24	1.43	36
1MU43-8-6+	M22x1,5	-8	3/8	-6	2.62	67	27	27	1.59	40
1MU43-8-8	M22x1,5	-8	1/2	-8	2.72	69	27	27	1.37	35
1MU43-8-10+	M22x1,5	-8	5/8	-10	3.03	77	27	27	1.58	40
1MU43-32-32+	M60X2	-32	2	-32	4.50	114	70	70	2.72	69

+ Non-Standard