

Parker Pneumatic

Female-Female Pipe Ends XV500P



Pipe thread	Flow dia.	Part number
1/4	.375	XV500P-4
3/8	.375	XV500P-6
1/2*	.500	XV500P-8
3/4**	.685	XV500P-12
1**	.875	XV500P-16

Female Pipe Ends, Lever Handle, Mini Ball Valve MV200



Pipe thread	Flow dia.	Part number
1/8	.31	MV200-2
1/4	.31	MV200-4
3/8	.31	MV200-6
1/2	.39	MV200-8

Male-Female Pipe Ends, Compact Handle, Mini Ball Valve MV608



Pipe thread	Flow dia.	Part number
1/8	.20	MV608-2
1/4	.31	MV608-4
3/8	.31	MV608-6
1/2	.39	MV608-8

Female Pipe Ends, Compact Handle, Mini Ball Valve MV609



Pipe thread	Flow dia.	Part number
1/8	.24	MV609-2
1/4	.31	MV609-4
3/8	.31	MV609-6
1/2	.39	MV609-8
3/8x1/4	.31	MV609-6-4

Female Pipe Ends, Panel Mount XV502SS



Pipe thread	Flow dia.	Part number
1/4	.380	XV502SS-4
3/8	.380	XV502SS-6
1/2	.500	XV502SS-8
3/4	.790	XV502SS-12
1	1.000	XV502SS-16
1-1/4	1.250	XV502SS-20
1-1/2	1.500	XV502SS-24
2	2.000	XV502SS-32

Most popular. For technical information see CD

Accessories

Ball and Plug Valves, Drain Cocks

Male Pipe to Male Pipe Plug Valve PV607



Pipe thread	Flow dia.	Part number
1/8	.200	PV607-2
1/4	.200	PV607-4

Female Pipe to Male Pipe Plug Valve PV608



Pipe thread	Flow dia.	Part number
1/8	.200	PV608-2
1/4	.200	PV608-4

Female Pipe to Female Pipe Plug Valve PV609



Pipe thread	Flow dia.	Part number
1/8	.200	PV609-2
1/4	.200	PV609-4

Internal Seal Drain Cock DC602

Temperature Range: -65° to 250°F



Pipe thread	Part number
1/8	DC602-2
1/4	DC602-4

External Seal Drain Cock DC604

Temperature Range: -25° to 250°F



Pipe thread	Part number
1/8	DC604-2*
1/4	DC604-4
3/8	DC604-6*

* When assembled handle wings are down facing

