









CAT #	DESCRIPTION	BATTERIES	COLORS	LIGHT SOURCE	LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	APPROVALS
2410	StealthLite™ 2410 Recoil™ LED 	4 AA ALKALINE (included)	■ BLACK ■ YELLOW	Recoil™ LED	 72 LUMENS	 7h 15min	 102m	<b>ETL</b> Class I II III Div. 1 Grps. ABCDEFG Operating Temp. Class T4 <b>IEC Ex</b> ITS.09.0017X Ex ia IIC T4, Ga, Ex ia IIIC T83°C Da IP66

CONFIGURATIONS		SPECIFICATIONS	
2410C	StealthLite™ 2410 Recoil™ LED Flashlight (Carded)	• Master Pack 6 ea.	• Length: 7" (17.8 cm)
2410PLC	StealthLite™ 2410 Recoil™ LED Flashlight (yellow only) w/ Photoluminescent Shroud (Carded)	• Master Pack 6 ea.	• Length: 7" (17.8 cm)





ACCESSORIES		SPECIFICATIONS	
2413PL	Photoluminescent Shroud	Master Pack 1 ea.	

See pages 24 & 25 for additional accessories

CAT #	DESCRIPTION	BATTERIES	COLORS	LIGHT SOURCE	LIGHT OUTPUT	RUNTIME	WATERPROOF/ SUBMERSIBLE	APPROVALS
2410N	NEMO™ 2410 Recoil™ LED 	4 AA ALKALINE (included)	■ BLACK ■ SOLAR YELLOW ■ BLUE	Recoil™ LED	 72 LUMENS	 7h 15min	 100m	N/A

CONFIGURATIONS		SPECIFICATIONS	
2410N	NEMO™ 2410 Recoil™ LED Flashlight (Carded)	• Master Pack 6 ea.	• Length: 7" (17.8 cm)

See pages 24 & 25 for additional accessories

CAT #	DESCRIPTION	BATTERIES	COLORS	LIGHT SOURCE	LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	APPROVALS
2430	MityLite™ 2430 	4 AA ALKALINE (included)	■ BLACK ■ YELLOW	INCANDESCENT	 70 LUMENS	 2h 15min	 104m	<b>UL</b> Listed 4S67/E184884 Class I, Div. 2; Gp.C, D T2A (265°)

CONFIGURATIONS		SPECIFICATIONS	
2430C	MityLite™ 2430 Flashlight (Carded)	• Master Pack 6 ea.	• Length: 6.5" (16.5 cm)

ACCESSORIES		SPECIFICATIONS	
2424	MityLite™ 2430 Xenon Lamp Module	Master Pack 6 ea.	WT.: 4.3 oz.

See pages 24 & 25 for additional accessories