

















CAT #	DESCRIPTION	BATTERIES	COLORS	LIGHT SOURCE	LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	APPROVALS
1800	 PeliLite™ 1800	2 C ALKALINE (not included)	■ BLACK ■ ORANGE ■ YELLOW	INCANDESCENT	 FL1 STANDARD 21 LUMENS	 FL1 STANDARD 7h	 FL1 STANDARD 131m	<b>CSA</b> Class I, Div. 2; Gp ABCD, T3C / Class II; Div. 2; Gp G. <b>FM</b> Class I, Div. 2; Gp. ABCD / Class II; Div. 2; Gp. G; T4 <b>UL</b> Listed 4S67/E184884 Class I, Div. 2; Gp. D / Class I; Zone 2; Gp. IIA; T3
<b>CONFIGURATIONS</b>		<b>SPECIFICATIONS</b>						
1800C	PeliLite™ 1800 Flashlight (Carded)	• Master Pack 6 ea. • Length: 6" (15.2 cm) • WT: 2.9 oz. (0.08 kg)						
<b>ACCESSORIES</b>		<b>SPECIFICATIONS</b>						
1804	PeliLite™ 1800 Xenon Lamp Module	• Master Pack 6 ea. • WT.: 5.8 oz.						

CAT #	DESCRIPTION	BATTERIES	COLORS	LIGHT SOURCE	LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	APPROVALS
1820	 Pocket Sabre™ 1820	2 C ALKALINE (included in select packaging)	■ BLACK ■ ORANGE ■ YELLOW	INCANDESCENT	 FL1 STANDARD 22 LUMENS	 FL1 STANDARD 6h 45min	 FL1 STANDARD 146m	<b>CSA</b> Class I, Div. 2; Gp ABCD, T4; Class II; III, Div. 2; Gp FG -35° +40°C. <b>FM</b> Class I, Div. 2; Gp. ABCD; T4 / Class II, III; Div. 2; Gp. FG. <b>UL</b> Listed 4S67/E184884 Class I, Div. 2 Gps.D, T2D. <b>IEC Ex</b> Ex ib e IIC T3 IP67 IEC Ex TSA 06.0021X
<b>CONFIGURATIONS</b>		<b>SPECIFICATIONS</b>						
1820C	Pocket Sabre™ 1820 Flashlight (Carded)	• Master Pack 6 ea. • Length: 5.83" (14.8 cm) • WT: 3.3 oz. (0.09 kg)						
<b>ACCESSORIES</b>		<b>SPECIFICATIONS</b>						
1804	Pocket Sabre™ 1820 Lamp Module	• Master Pack 6 ea. • WT.: 5.8 oz.						

CAT #	DESCRIPTION	BATTERIES	COLORS	LIGHT SOURCE	LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	APPROVALS
1830	 L4™ 1830 LED	3 AAAA ALKALINE (included)	■ BLACK ■ YELLOW ■ MOSSY OAK	LED	 FL1 STANDARD 5 LUMENS	 FL1 STANDARD 32h	 FL1 STANDARD 13m	<b>FM</b> Class I, Div. 1 Gp. CD T4A / Class I, Div. 2 Gp. ABCD T4A
<b>CONFIGURATIONS</b>		<b>SPECIFICATIONS</b>						
1830C	L4™ 1830 LED Flashlight (Carded)	• Master Pack 6 ea. • Length: 6.2" (15.7 cm) • WT: 0.56 oz. (0.02 kg)						
1830MOCC	L4™ 1830MOC LED Flashlight (Carded)	• Master Pack 6 ea. • Length: 6.2" (15.7 cm) • WT: 0.56 oz. (0.02 kg)						
<b>ACCESSORIES</b>		<b>SPECIFICATIONS</b>						
1839	3 Pack AAAA Batteries	• Master Pack 6 ea.						

CAT #	DESCRIPTION	BATTERIES	COLORS	LIGHT SOURCE	LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	APPROVALS
1900	 MityLite™ 1900	2 AAA ALKALINE (included)	■ BLACK ■ ORANGE ■ YELLOW ■ BLUE □ WHITE ■ NEON GREEN ■ MOSSY OAK	INCANDESCENT	 FL1 STANDARD 11 LUMENS	 FL1 STANDARD 1h 30min	 FL1 STANDARD 45m	<b>ETL</b> Class I, Div. 1, GP C,D, T3C CONFORMS TO STD UL 783 <b>CSA</b> Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G. <b>IEC Ex</b> Ex ib e IIC T4 IP67 IEC Ex TSA 06.0021X
<b>CONFIGURATIONS</b>		<b>SPECIFICATIONS</b>						
1900C	MityLite™ 1900 Flashlight (Carded)	• Master Pack 6 ea. • Length: 4.09" (10.4 cm) • WT: 0.75 oz. (0.02 kg)						
1900M	MityLite™ 1900 Flashlight Merchandiser Display	• Master Pack 1 ea.						
1900T	MityLite™ 1900 Flashlight (Clear Gift Tube)	• Master Pack 12 ea.						
1900MOCC	MityLite™ 1900MOC Flashlight (Carded)	• Master Pack 6 ea. • Length: 4.09" (10.4 cm) • WT: 0.75 oz. (0.02 kg)						
<b>ACCESSORIES</b>		<b>SPECIFICATIONS</b>						
1904	MityLite™ 1900 Lamp Module	• Master Pack 6 ea. • WT.: 4.6 oz.						