



CAT #	DESCRIPTION	BATTERIES	COLORS	LIGHT SOURCE	LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	APPROVALS
1960	MityLite™ 1960 LED 	2 AAA ALKALINE (included)	■ BLACK ■ YELLOW	LED	FL1 STANDARD 24 LUMENS	FL1 STANDARD 3h	FL1 STANDARD 51m	N/A


CONFIGURATIONS		SPECIFICATIONS	
1960C	MityLite™ 1960 LED Flashlight (Carded)		<ul style="list-style-type: none"> • Master Pack 6 ea. • Length: 5.48" (13.9 cm) • WT: 1.1 oz. (0.03 kg)

See pages 24 & 25 for additional accessories

CAT #	DESCRIPTION	BATTERIES	COLORS	LIGHT SOURCE	LIGHT OUTPUT	RUNTIME	WATERPROOF/ SUBMERSIBLE	APPROVALS
1960N	NEMO™ 1960 LED 	2 AAA ALKALINE (included)	■ BLACK ■ SOLAR YELLOW ■ BLUE	LED	FL1 STANDARD 24 LUMENS	FL1 STANDARD 3h	FL1 STANDARD 100m	N/A


CONFIGURATIONS		SPECIFICATIONS	
1960NC	NEMO™ 1960 LED Flashlight (Carded)		<ul style="list-style-type: none"> • Master Pack 6 ea. • Length: 5.48" (13.9 cm) • WT: 1.1 oz. (0.03 kg)

See pages 24 & 25 for additional accessories

CAT #	DESCRIPTION	BATTERIES	COLORS	LIGHT SOURCE	LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	APPROVALS
1965	MityLite™ 1965 LED 	2 AAA ALKALINE (included)	■ BLACK ■ YELLOW	LED	FL1 STANDARD 21 LUMENS	FL1 STANDARD 4h	FL1 STANDARD 51m	CE Ex II 1 GD Ex ia IIC T4 Ga Ex iaD 20 IP65 T90°C Da IEC Ex IECEx TRC10.0005X - II 1 GD Ex ia IIC T4 Ga Ex iaD 20 IP65 T90°C SGS Class I II III Div. 1 Grps. ABCDEFG T4 QPS Class I II III Div. 1 Grps. ABCDEFG T4

CONFIGURATIONS		SPECIFICATIONS	
1965C	MityLite™ 1965 LED Flashlight (Carded)		<ul style="list-style-type: none"> • Master Pack 6 ea. • Length: 5.48" (13.9 cm) • WT: 1.1 oz. (0.03 kg)

See pages 24 & 25 for additional accessories

CAT #	DESCRIPTION	BATTERIES	COLORS	LIGHT SOURCE	LIGHT OUTPUT	RUNTIME	BEAM DISTANCE	APPROVALS
2000	SabreLite™ 2000 	3 C ALKALINE (not included)	■ BLACK ■ ORANGE ■ YELLOW	INCANDESCENT	FL1 STANDARD 53 LUMENS	FL1 STANDARD 5h	FL1 STANDARD 158m	CSA Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G. FM Class I, II, Div. 2; Gp. ABCD/G, T3C. UL Listed 4S67/E184884 Class I, Div. 1; Gp.C, D / Class I; Zone 1; Gp.IIA; IIB; T3C IEC Ex IEC Ex TSA 06.0021X Ex ib e IIC T4 IP67

CONFIGURATIONS		SPECIFICATIONS	
2000C	SabreLite™ 2000 Flashlight (Carded)		<ul style="list-style-type: none"> • Master Pack 6 ea. Assorted Packs available - 2 black, 2 yellow, 2 orange. • Length: 7.79" (19.8 cm) • WT: 5.31 oz. (0.15 kg)

2000 PLC	SabreLite™ 2000 Flashlight (yellow only) w/ Photoluminescent Shroud (Carded)		<ul style="list-style-type: none"> • Master Pack 6 ea. • Length: 7.79" (19.8 cm) • WT: 5.31 oz. (0.15 kg)
----------	--	--	---

ACCESSORIES		SPECIFICATIONS	
2003PL	Photoluminescent Shroud		Master Pack 1 ea.
2004	SabreLite™ 2000 Lamp Module		Master Pack 6 ea. WT.: 6.0 oz.
8052OR	Traffic Wand (Orange)		N/A
8052YW	Traffic Wand (Yellow)		N/A