

DTS 3461 (NEMA 3R/4) | DTS 3481 (NEMA 4/4X)

- suitable for the food and beverage industry and outdoor applications
- high protection system IP 56, maintenance-free in most applications
- maintains a UL tested NEMA type 3R/4 seal against the enclosure
- condenser with 3 mm fin spacing, highly effective protection against strongly contaminated ambient air
- large distance between intake and exhaust vents, safe circulation within the electrical enclosure due to long passage of air, therefore hot spots are eliminated
- integrated condensate evaporation system
- fully coated heat-exchangers and tubing



| PRODUCT | | DTS 3461 (NEMA 3R/4) | DTS 3481 (NEMA 4/4X) | |
|--|----------|--|--|---------|
| ARTICLE NO. | SC | 13385036355 | 13385036158 | Unit |
| DATA | | | | |
| Rated voltage ±10 % | | AC 50 60 400 460 3~ | | Hz V |
| Cooling capacity according to EN 14511 | A35/A35 | 3970 | 3970 | W |
| | A35/A50 | 2755 | 2755 | |
| Power consumption | A35/A35 | 1979 | | A |
| Current consumption | A35/A35 | 2.5 | | |
| Starting current | A35/A35 | 3.6 | | |
| Unimpeded airflow (free flow) | internal | 2157 | | m³/h |
| | external | 705 | | |
| Pre fuse T | | 15 | | A |
| Type of connection | | spring-type terminal included with plug | | |
| Noise level according to EN ISO 3741 | | < 69 | | dB (A) |
| Weight (without packaging) | | 87 | | kg |
| Ambient temperature | | - 4 ... + 55 + 20... + 131 | | °C °F |
| Control range (adjustable) | | + 25 ... + 45 + 77 ... + 113; factory setting + 35 + 95 | | |
| Refrigerant | R134a | 1100 | | g |
| Duty cycle | | 100 | | % |
| Condensate management | | integrated condensate evaporation system with safety overflow | | |
| Protection system according to NEMA type | 3R/4 | towards the electrical enclosure if used as intended by the manufacturer | - | |
| | 4/4X | - | towards the electrical enclosure if used as intended by the manufacturer | |
| | 1 | towards the surroundings if used as intended by the manufacturer | | |
| Design | housing | galvanised sheet steel | stainless steel 304 | |
| | cover | galvanised electrostatically powder coated (200 °C) | stainless steel 304 | |
| Colour | | RAL 7035 different colours available on request | - | |


For additional information to ensure the accurate setting of the motor protection switch, please see technical specific data sheet. This information is included with the delivery of the unit or can be found at www.pfannenber.com.

| ACCESSORIES | Piece | ARTICLE NUMBER |
|-------------------|-------|----------------|
| Condensate bottle | 1 | 18314000100 |
| Filter kit | 1 | 18881500010 |

For additional models, options and voltages visit www.pfannenberg.com or contact us directly.



Cooling capacity performance curves



Dimensions

| | X | Y | Z | A | B | C | D | E | F | G | H | I | J | K | L | M |
|----|-----|------|-----|-----|-----|-----|-----|------|-----|-----|----|-----|-----|-----|-----|----|
| mm | 406 | 1440 | 405 | 590 | 285 | 160 | 310 | 32.5 | 216 | 280 | 26 | 350 | 175 | 280 | 340 | 20 |

Mounting holes \varnothing 8 mm

DTS 3461 | DTS 3481

