

## EXHAUST FILTERS

### PFA 20.000 EMC

- Snap fastener without screws
- Simple filter mat exchange
- With integrated foam seal to enclosure
- W x H x D: 145 x 145 x 31 mm
- Cut-out dimensions: 126 x 126 mm
- Colour: RAL 7035



|                                                            |                                                                       |                              |
|------------------------------------------------------------|-----------------------------------------------------------------------|------------------------------|
| Design (housing and protection against accidental contact) | made of injection-moulded thermoplastic, self-extinguishing, UL 94 VO |                              |
| EMC screen                                                 | stainless steel                                                       |                              |
| Approvals                                                  | UL, cUL, CE, (on request: GOST)                                       |                              |
| <b>Version</b>                                             | <b>IP 54</b>                                                          | <b>IP 55</b>                 |
| System of protection (EN 60529 / UL 50)                    | NEMA type 12 - standard filter                                        | NEMA type 12 - fluted filter |
| Filter mat quality class                                   | G 3                                                                   | G 4                          |
| <b>Article no.</b>                                         | 11920001055                                                           | 11920003055                  |
| <b>Article no.</b> Spare filter mats (5 pieces)            | 18611600030                                                           | 18611600034                  |

### PFA 30.000 EMC

- Snap fastener without screws
- Simple filter mat exchange
- With integrated foam seal to enclosure
- W x H x D: 202 x 202 x 40 mm
- Cut-out dimensions: 178 x 178 mm
- Colour: RAL 7035



|                                                            |                                                                       |                              |
|------------------------------------------------------------|-----------------------------------------------------------------------|------------------------------|
| Design (housing and protection against accidental contact) | made of injection-moulded thermoplastic, self-extinguishing, UL 94 VO |                              |
| EMC screen                                                 | stainless steel                                                       |                              |
| Approvals                                                  | UL, cUL, CE, (on request: GOST)                                       |                              |
| <b>Version</b>                                             | <b>IP 54</b>                                                          | <b>IP 55</b>                 |
| System of protection (EN 60529 / UL 50)                    | NEMA type 12 - standard filter                                        | NEMA type 12 - fluted filter |
| Filter mat quality class                                   | G 3                                                                   | G 4                          |
| <b>Article no. *</b>                                       | 11930001055                                                           | 11930003055                  |
| <b>Article no.</b> Spare filter mats (5 pieces)            | 18611600031                                                           | 18611600035                  |

### PFA 40.000 EMC

- Snap fastener without screws
- Simple filter mat exchange
- With integrated foam seal to enclosure
- W x H x D: 252 x 252 x 44 mm
- Cut-out dimensions: 224 x 224 mm
- Colour: RAL 7035



|                                                            |                                                                       |                              |
|------------------------------------------------------------|-----------------------------------------------------------------------|------------------------------|
| Design (housing and protection against accidental contact) | made of injection-moulded thermoplastic, self-extinguishing, UL 94 VO |                              |
| EMC screen                                                 | stainless steel                                                       |                              |
| Approvals                                                  | UL, cUL, CE, (on request: GOST)                                       |                              |
| <b>Version</b>                                             | <b>IP 54</b>                                                          | <b>IP 55</b>                 |
| System of protection (EN 60529 / UL 50)                    | NEMA type 12 - standard filter                                        | NEMA type 12 - fluted filter |
| Filter mat quality class                                   | G 3                                                                   | G 4                          |
| <b>Article no. *</b>                                       | 11940001055                                                           | 11940003055                  |
| <b>Article no.</b> Spare filter mats (5 pieces)            | 18611600032                                                           | 18611600036                  |

### PFA 60.000 EMC

- Snap fastener without screws
- Simple filter mat exchange
- With integrated foam seal to enclosure
- W x H x D: 202 x 202 x 40 mm
- Cut-out dimensions: 292 x 292 mm
- Colour: RAL 7035



|                                                            |                                                                       |                              |
|------------------------------------------------------------|-----------------------------------------------------------------------|------------------------------|
| Design (housing and protection against accidental contact) | made of injection-moulded thermoplastic, self-extinguishing, UL 94 VO |                              |
| EMC screen                                                 | stainless steel                                                       |                              |
| Approvals                                                  | UL, cUL, CE, (on request: GOST)                                       |                              |
| <b>Version</b>                                             | <b>IP 54</b>                                                          | <b>IP 55</b>                 |
| System of protection (EN 60529 / UL 50)                    | NEMA type 12 - standard filter                                        | NEMA type 12 - fluted filter |
| Filter mat quality class                                   | G 3                                                                   | G 4                          |
| <b>Article no. *</b>                                       | 11960002055                                                           | 11960003055                  |
| <b>Article no.</b> Spare filter mats (5 pieces)            | 18611600033                                                           | 18611600037                  |