

## 8mm Head Drive Pins

### PRODUCT DESCRIPTION

Drive Pins with a 8mm head are designed for permanently fastening a fixture to concrete, some types of masonry, and A36 or A572 structural steel. The pins are manufactured with a 0.145" diameter shank in various lengths. Knurled shank designs are available to increase performance in steel base materials. A 8mm plastic washer is mounted over the point to retain the drive pin in the fastener guide of the tool providing centered guidance during the driving operation.

### FASTENERS SIZES

#### 8mm Head Drive Pins

Cat. No.	Shank Length	Shank Diameter	Standard Box	Standard Carton	Wt./100
50180	16mm (K)- 5/8"	0.145"	100	5,000	0.4
50182	19mm (K)- 3/4"	0.145"	100	5,000	0.5
50184	22mm - 7/8"	0.145"	100	5,000	0.6
50186	27mm - 1"	0.145"	100	5,000	0.7
50188	32mm - 1 1/4"	0.145"	100	1,000	0.8
50190	37mm - 1 1/2"	0.145"	100	1,000	0.9
50192	42mm - 1 5/8"	0.145"	100	1,000	1.0
50194	47mm - 1 7/8"	0.145"	100	1,000	1.1
50196	52mm - 2"	0.145"	100	1,000	1.3
50198	57mm - 2 1/4"	0.145"	100	1,000	1.4
50200	62mm - 2 1/2"	0.145"	100	1,000	1.5
50202	72mm - 2 7/8"	0.145"	100	1,000	1.6

(K) = knurled



#### 8mm Head Drive Pins with Top Hat

These pins are used primarily for applications fastening drywall track to concrete or steel. They are assembled with a metal top hat to provide faster insertion into the driving tool with reduced possibility of pricking a finger during loading and to provide extra bearing surface against the drywall track.

Cat. No.	Shank Length	Shank Diameter	Standard Box	Standard Carton	Wt./100
50210	16mm (K)-5/8"	0.145"	100	5,000	0.6
50214	22mm - 7/8"	0.145"	100	5,000	0.7
50216	27mm - 1"	0.145"	100	5,000	0.8

(K) = knurled



#### 8mm Head Diameter Drive Pins with Top Hat – Master Pack

Cat. No.	Shank Length	Shank Diameter	Standard Box	Std. Carton	Wt./100
51700	16mm (K)-5/8"TH	0.145"	1,000	5,000	0.6
51750	22mm 7/8" TH	0.145"	1,000	5,000	0.7

## 8mm Head Drive Pins with Washers

### FASTENERS SIZES

#### 8mm Head Drive Pins with 1" Washer

To provide resistance to pullover, these pins are available with preassembled 14 gage (0.075") metal washers in various diameters. Resistance to pullover is increased by the additional bearing surface provided by the washer.

Cat. No.	Shank Length	Shank Diameter	Standard Box	Standard Carton	Wt./100
50220	27mm - 1"	0.145"	100	1,000	2.5
50222	32mm - 1 1/4"	0.145"	100	1,000	2.5
50224	37mm - 1 1/2"	0.145"	100	1,000	2.6
50226	52mm - 2"	0.145"	100	1,000	2.9
50228	62mm - 2 1/2"	0.145"	100	1,000	3.1
50230	72mm - 2 7/8"	0.145"	100	1,000	3.3

