

Page No.

Hollow-Set Dropin Internally Threaded Expansion Anchor PRODUCT DESCRIPTION

The Hollow-Set Dropin anchor is designed for anchoring in hollow base materials such as hollow concrete block and precast hollow core plank. It can also be used in solid base materials.

Precast plank or concrete masonry blocks often have a maximum outer wall thickness of 1-1/2". During the drilling process, spalling on the back side of the wall often decreases the wall thickness, leaving only 1" or less for anchoring. The Hollow-Set Dropin is designed to perform in this environment, where most conventional style anchors will not function properly.

GENERAL APPLICATIONS AND USES

- Anchoring to Concrete Block
- Fastening to Precast Hollow Core Plank
 Fire Sprinkler
- Suspending ConduitCable Trays and Strut
- Pipe Supports
- Suspended Lighting
- Removable Anchorage

FEATURES AND BENEFITS

- + Internally threaded anchor for easy bolt removability and service work
- + Unique expansion design allows for anchoring in thin-walled base materials such as hollow concrete block and precast hollow core plank
- + Versatile setting options allows for hollow or solid base materials
- + Tested in accordance with ASTM E488 and AC01 criteria

APPROVALS AND LISTINGS

FM Global (Factory Mutual) - File No. 15219/1952, 3/8", 1/2" and 5/8" diameters. Pipe hanger components for automatic sprinkler systems Underwriters Laboratories (UL) File EX 1289 (Hanger, Pipe), 3/8", 1/2" and 5/8".

GUIDE SPECIFICATIONS

CSI Divisions: 03151-Concrete Anchoring, 04081-Masonry Anchorage and 05090-Metal Fastenings. Dropin anchors shall be Hollow-Set Dropin as supplied by Powers Fasteners, Inc., Brewster, NY.



Hollow-Set Dropin

ANCHOR MATERIALS

SECTION CONTENTS

General Information 1

Installation Specifications 2

Material Specifications 2

Performance Data...... 3

Zamac Alloy Anchor Body with Carbon Steel Cone or Type 304 Stainless Steel Cone

ROD/ANCHOR SIZE RANGE (TYP.)

1/4" to 5/8" diameter

SUITABLE BASE MATERIALS

Normal-Weight Concrete Precast Hollow Core Plank Hollow Concrete Masonry (CMU) Brick Masonry



Hollow-Set Dropin

INSTALLATION SPECIFICATIONS

	Rod/Anchor Diameter, d					
Dimension	1/4"	5/16"	3/8"	1/2"	5/8"	
ANSI Drill Bit Size, <i>d_{bit}</i> (in.)	3/8	5/8	5/8	3/4	1	
Maximum Tightening Torque, T _{max} (ftlbs)	3-4	5-7	8-10	15-20	30-40	
Thread Size (UNC)	1/4-20	5/16-18	3/8-16	1/2-13	5/8-11	
Overall Anchor Length (in.)	7/8	1-5/16	1-5/16	1-3/4	2	
Sleeve Length (in.)	5/8	15/16	15/16	1-1/4	1-1/2	
Thread Length In Cone (in.)	3/8	5/8	5/8	3/4	1	

Installation Guidelines for Hollow Base Materials

In hollow base materials, drill through into the cell or void. The tolerances of the drill bit used must meet the requirements of ANSI Standard B212.15.



Blow the hole clean of dust and other materials. Do not expand the anchor prior to installation. Insert cone end and tap flush to surface.



Position fixture, insert bolt and tighten. The bolt should engage a minimum of 2/3 of the anchor threads. The anchor can also be expanded using



a Hollow-Set Tool. (If Hollow-Set Tool is used, thread anchor onto tool prior to tapping into anchor hole. When flush with surface, turn tool clockwise to tighten. Release tool from set anchor by turning counterclockwise. Fixture can then be attached).

Installation Guidelines for Solid Base Materials

Drill a hole into the base material to the required embedment depth. The tolerances of the drill bit used must meet the requirements of ANSI Standard B212.15.



Blow the hole clean of dust and other materials. Insert the anchor into the hole. Position the setting tool in the anchor.



Using the Solid Tool, set the anchor by driving the Zamac sleeve over the cone using several sharp hammer blows. Be sure the anchor is at the required embedment



depth, so that anchor threads do not protrude above the surface of the base material. Position the fixture, insert bolt or threaded rod and tighten.

MATERIAL SPECIFICATIONS

Anchor Component	Carbon Steel	Stainless Steel	
Anchor Body	Zamac Alloy	Zamac Alloy	
Cone	AISI C 1008	Type 304 Stainless Steel	
Plating (Cone)	ASTM B633, SC1, Type III (Fe/Zn 5)	N/A	

PERFORMANCE DATA

Ultimate Load Capacities for Hollow-Set Dropin in Normal-Weight Concrete^{1,2,3}

Rod/	Min. Drill		Minimum Concrete Compressive Strength (f' _c)						
Anchor Diameter	Embed. Depth	Bit Diameter	2,000 psi	(13.8 MPa)	4,000 psi	(27.6 MPa)	6,000 psi (41.4 MPa)	
d in. (mm)	<i>h</i> _v in. (mm)	d _{bit} in.	Tension Ibs. (kN)	Shear Ibs. (kN)	Tension Ibs. (kN)	Shear Ibs. (kN)	Tension Ibs. (kN)	Shear Ibs. (kN)	
1/4	3/4 (19.1)	3/8	760 (3.4)	1,200 (5.4)	1,140 (5.1)	1,200 (5.4)	1,440 (6.5)	1,200 (5.4)	
(6.4)	7/8 (22.2)		880 (4.0)	1,440 (6.5)	1,145 (5.2)	1,440 (6.5)	2,045 (9.2)	1,440 (6.5)	
5/16	1 (25.4)	5/8	1,120 (5.0)	1,980 (8.9)	1,680 (7.6)	1,980 (8.9)	2,200 (9.9)	1,980 (8.9)	
(7.9)	1 1/2 (38.1)		2,205 (9.9)	2,740 (12.3)	2,775 (12.5)	2,740 (12.3)	4,825 (21.7)	2,740 (12.3)	
3/8	1 (25.4)	5/8	1,370 (6.2)	2,550 (11.5)	2,070 (9.3)	2,550 (11.5)	2,290 (10.3)	2,550 (11.5)	
(9.5)	1 1/2 (38.1)		2,445 (11.0)	3,145 (14.2)	2,800 (12.5)	3,145 (14.2)	5,085 (22.9)	3,145 (14.2)	
1/2 (12.7)	1 1/2 (38.1)	3/4	2,140 (9.6)	4,020 (18.1)	4,025 (18.1)	4,020 (18.1)	7,285 (32.8)	4,020 (18.1)	
	2 (50.8)		2,780 (12.5)	4,020 (18.1)	4,375 (19.7)	4,020 (18.1)	9,455 (42.5)	4,020 (18.1)	
5/8 (15.9)	2 1/4 (57.2)	1	5,725 (25.8)	6,400 (28.8)	9,410 (42.3)	6,400 (28.8)	10,500 (46.6)	6,400 (28.8)	

1. Tabulated load values are applicable to anchors with carbon and stainless steel cones. 2. Tabulated load values are for anchors installed in concrete. Concrete compressive strength must be at the specified minimum at the time of installation.

3. Ultimate load capacities must be reduced by a minimum safety factor of 4.0 or greater to determine allowable working load. Consideration of safety factors of 20 or higher may be necessary depending upon the application such as life safety, overhead and in sustained tensile loading applications.

Allowable Load Capacities for Hollow-Set Dropin in Normal-Weight Concrete^{1,2,3,4}

Rod/	Min. Drill		Minimum Concrete Compressive Strength (f'c)						
Anchor Diameter	Embed. Depth	Bit	2,000 psi	(13.8 MPa)	4,000 psi	(27.6 MPa)	6,000 psi	(41.4 MPa)	
<i>d</i> in. (mm)	<i>h</i> v in. (mm)	d _{bit} in.	Tension Ibs. (kN)	Shear Ibs. (kN)	Tension Ibs. (kN)	Shear Ibs. (kN)	Tension Ibs. (kN)	Shear Ibs. (kN)	
1/4 (19.1) (6.4) 7/8 (22.2)	3/4 (19.1)	3/8	190 (0.9)	300 (1.4)	285 (1.3)	300 (1.4)	360 (1.6)	300 (1.4)	
	7/8 (22.2)		220 (1.0)	360 (1.6)	285 (1.3)	360 (1.6)	510 (2.3)	360 (1.6)	
5/16	1 (25.4)	5/8	280 (1.3)	495 (2.2)	420 (1.9)	495 (2.2)	550 (2.5)	495 (2.2)	
(7.9)	1 1/2 (38.1)		550 (2.5)	685 (3.0)	695 (3.1)	685 (3.0)	1,205 (5.4)	685 (3.0)	
3/8	1 (25.4)	5/8	345 (1.6)	640 (2.9)	520 (2.3)	640 (2.9)	575 (2.6)	640 (2.9)	
(9.5)	1 1/2 (38.1)		610 (2.7)	785 (3.5)	700 (3.0)	785 (3.5)	1,270 (5.7)	785 (3.5)	
1/2	1 1/2 (38.1)	3/4	535 (2.4)	1,005 (4.5)	1,005 (4.5)	1,005 (4.5)	1,820 (8.2)	1,005 (4.5)	
(12.7)	2 (50.8)		695 (3.1)	1,005 (4.5)	1,095 (4.9)	1,005 (4.5)	2,365 (10.6)	1,005 (4.5)	
5/8 (15.9)	2 1/4 (57.2)	1	1,430 (6.4)	1,600 (7.2)	2,355 (10.6)	1,600 (7.2)	2,625 (11.7)	1,600 (7.2)	

1. Tabulated load values are applicable to anchors with carbon and stainless steel cones.

2. Allowable load capacities listed are calculated using and applied safety factor of 4.0. Consideration of safety factors of 20 or higher may be necessary depending upon the application such as life a nonvoir construct and construct and construct and applications.
Linear interpolation may be used to determine allowable loads for intermediate embedments and compressive strengths.
Allowable load capacities are multiplied by reduction factors found in the Design Criteria section when anchor spacing or edge distances are less than critical distances.

d

1 1/2

PERFORMANCE DATA

Ultimate and Allowable Load Capacities for Hollow-Set Dropin in Hollow Core Plank^{1,2}

Rod/ Anchor	Minimum Embedment	Drill Bit	Minimum Concrete Compressive Strengt f' _c ≥ 5,000 psi (34.5 MPa)				
Diameter	Depth	Diameter	Ultima	te Load	Allowab	le Load ²	
d in. (mm)	<i>h</i> _v in. (mm)	d _{bit} in.	Tension Ibs. (kN)	Shear Ibs. (kN)	Tension Ibs. (kN)	Shear Ibs. (kN)	
1/4 (6.4)	7/8 (22.2)	3/8	1,190 (5.4)	1,440 (6.5)	300 (1.4)	360 (1.6)	
5/16 (7.9)	1 (25.4)	5/8	2,280 (10.3)	2,740 (12.3)	570 (2.6)	685 (3.1)	
3/8	1 (25.4)	5/8	2,525 (11.4)	2,740 (12.3)	630 (2.8)	685 (3.1)	
(9.5)	1 1/2 (38.1)	5/8	3,620 (16.3)	3,145 (14.2)	905 (4.1)	785 (3.5)	
1/2 (12.7)	1 1/4 (31.8)	3/4	5,420 (24.4)	5,580 (25.1)	1,355 (6.1)	1 ,395 (6.3)	
5/8 (15.9)	1 1/2 (38.1)	1	6,560 (29.2)	8,320 (37.4)	1,640 (7.3)	2,080 (9.4)	



Ultimate and Allowable Load Capacities for Hollow-Set Dropin in Hollow Concrete Masonry^{1,2,3}

Rod/	Minimum	Drill Bit	f'n	osi (10.4 MF	Pa)	
Diameter	Depth	Diameter	Ultima	te Load	Allowab	le Load ²
d in. (mm)	<i>h</i> _v in. (mm)	d _{bit} in.	Tension Ibs. (kN)	Shear Ibs. (kN)	Tension Ibs. (kN)	Shear Ibs. (kN)
1/4	7/8*	3/8	530	1,575	105	315
(6.4)	(22.2)		(2.4)	(7.1)	(0.5)	(1.4)
5/16	1*	5/8	1,035	1,815	205	365
(7.9)	(25.4)		(4.7)	(8.2)	(0.9)	(1.6)
3/8	1*	5/8	1,225	2,485	245	495
(9.5)	(25.4)		(5.5)	(11.2)	(1.1)	(2.2)
1/2	1 1/4*	3/4	1,790	3,655	360	730
(12.7)	(31.8)		(8.1)	(16.4)	(1.6)	(3.3)
5/8	1 1/2*	1	1, 790	3,740	360	750
(15.9)	(38.1)		(8.1)	(16.8)	(1.6)	(3.4)

1. Tabulated load values are applicable to anchors with carbon and stainless steel cones.

2. Tabulated load values are for anchors installed in minimum 6-inch wide, minimum Grade N, Type II, lightweight, medium-weight or normal-weight concrete masonry units conforming to ASTM C 90. Mortar must be minimum Type N. Masonry cells may be

and a set of the set

$ _{\mathcal{L}}^{-2}$	1215		2/4	h.
1.1			j	1
				1
				Ľ,
E.L				
	Carlos P	Sec 1		¥.

HOLLOW SET DROPIN (TYP)



PERFORMANCE DATA

Minimum End Distance

Ultimate and Allowable Load Capacities for Hollow-Set Dropin in Solid Clay Brick Masonry^{1,2,3,4}

Rod/	Rod/ Minimum		Minimum	Structural Brick Masonry $f'_m \ge 1,500 \text{ psi} (10.4 \text{ MPa})$				
Anchor Diameter	Embed. Depth	Edge Distance	End Distance	Ultimat	te Load	Allowal	ole Load	
d in. (mm)	<i>h</i> v in. (mm)	in. (mm)	in. (mm)	Tension Ibs. (kN)	Shear Ibs. (kN)	Tension Ibs. (kN)	Shear Ibs. (kN)	
1/4 (6.4)	7/8 (22.2)	6 (152.4)		880 (4.0)	1,640 (7.4)	175 (0.8)	330 (1.5)	
5/16 (9.5)	1 1/4 (31.8)	8 (203.2)		1,460 (6.6)	2,230 (10.0)	290 (1.3)	445 (2.0)	
3/8 (12.7)	1 1/4 (31.8)	8 (203.2)	<mark>8</mark> (203.2)	1,860 (8.4)	2,980 (13.4)	370 (1.7)	595 (2.7)	
1/2 (15.9)	1 1/2 (38.1)	10 (254.0)		3,240 (14.6)	4,230 (19.0)	650 (2.9)	845 (3.8)	
5/8 (19.1)	2 1/4 (57.2)	12 (304.8)		4,680 (21.1)	6,420 (28.9)	935 (4.2)	1,605 (7.2)	

1. Tabulated load values are for anchors with carbon or stainless steel cones.

Tabulated load values are for anchors installed in multiple wythe, minimum Grade SW, solid clay brick masonry walls conforming to 2. ASTM C 62. Mortar must be minimum Type N. Masonry compressive strength must be at the specified minimum at the time of installation ($f'm \ge 1,500$ psi).

3. Allowable load capacities listed are calculated using and applied safety factor of 5.0. Consideration of safety factors of 20 or higher

may be necessary depending upon the application such as life safety, and in sustained tensile loading applications. 4. The tabulated values are for anchors installed at a minimum of 16 anchor diameters on center for 100 percent capacity. Spacing distances may be reduced to 8 anchor diameters on center provided the capacities are reduced by 50 percent. Linear interpolation may be used for intermediate spacing.

DESIGN CRITERIA (ALLOWABLE STRESS DESIGN

Combined Loading

Minimum Edge Distance

For anchors loaded in both shear and tension, the combination of loads should be proportioned as follows:

$$\left(\frac{N_u}{N_n}\right) + \left(\frac{V_u}{V_n}\right) \le 1$$

Where: N_u = Applied Service Tension Load N_n = Allowable Tension Load V_{u} = Applied Service Shear Load V_n = Allowable Shear Load

Load Adjustment Factors for Spacing and Edge Distances¹

Anchor Installed in Normal-Weight Concrete							
Anchor Dimension	Load Type	Critical Distance (Full Anchor Capacity)	Critical Load Factor	Minimum Distance (Reduced Capacity)	Minimum Load Factor		
Spacing (s)	Tension and Shear	$S_{cr} = 3.0 h_V$	$F_{N_S} = F_{V_S} = 1.0$	$s_{min} = 1.5 h_V$	$F_{N_S} = F_{V_S} = 0.50$		
Edgo Distanco (c)	Tension	$c_{cr} = 14d$	$F_{N_{C}} = 1.0$	c _{min} = 8d	$F_{N_{C}} = 0.80$		
Luge Distance (C)	Shear	$C_{cr} = 14d$	$F_{V_{C}} = 1.0$	c _{min} = 8d	$F_{V_{C}} = 0.50$		

1. Allowable load values found in the performance data tables are multiplied by reduction factors when anchor spacing or edge distances are less than critical distances. Linear interpolation is allowed for intermediate anchor spacing and edge distances between critical and minimum distances. When an anchor is affected by both reduced spacing and edge distance, the spacing and edge reduction factors must be combined (multiplied). Multiple reduction factors for anchor spacing and edge distance may be required depending on the anchor group configuration.

Powers USA: (800) 524-3244 or (914) 235-6300



Hollow-Set Dropin

DESIGN CRITERIA (ALLOWABLE STRESS DESIGN)

Load Adjustment Factors for Normal-Weight Concrete

	Spacing, Tension (F _{NS}) & Shear (F _{VS})								
Dia	. (in.)	1/4	5/16	3/8	1/2	5/8			
h _v (in.)	7/8	1 1/2	1 1/2	2	2 1/4			
Scr	(in.)	2 5/8	4 1/2	4 1/2	6	6 3/4			
Smi	n (in.)	1 3/8	2 1/4	2 1/4	3	3 3/8			
	1 3/8	0.50							
	2 1/4	0.86	0.50	0.50					
es)	2 5/8	1.00	0.58	0.58					
چ ا	3		0.67	0.67	0.50				
E.	3 3/8		0.75	0.75	0.56	0.50			
5	4		0.89	0.89	0.67	0.59			
ci.	4 1/2		1.00	1.00	0.75	0.67			
ba	5				0.83	0.74			
l o	6				1.00	0.89			
	6 3/4					1.00			

Notes: For anchors loaded in tension and shear, the critical spacing (s_{cr}) is equal to 3 embedment depths $(3 h_v)$ at which the anchor achieves 100% of load. Minimum spacing (s_{min}) is equal to 1.5 embedment depths $(1.5 h_v)$ at which the anchor achieves 50% of load.



Notes: For anchors loaded in tension, the critical edge distance (c_{cr}) is equal to 14 anchor diameters (14*d*) at which the anchor achieves 100% of load. Minimum edge distance (c_{min}) is equal to 8 anchor diameters (8*d*) at which the anchor achieves 80% of load.



Notes: For anchors loaded in shear, the critical edge distance (c_{cr}) is equal to 14 anchor diameters (14*d*) at which the anchor achieves 100% of load. Minimum edge distance (c_{min}) is equal to 8 anchor diameters (8*d*) at which the anchor achieves 50% of load.



	Edge Distance, Tension (<i>F_{NC}</i>)								
Dia	. (in.)	1/4	5/16	3/8	1/2	5/8			
C _{cr}	(in.)	3 1/2	4 3/8	5 1/4	7	8 3/4			
Cmi	n (in.)	2	2 1/2	3	4	5			
	2	0.80							
	2 1/2	0.87	0.80						
es)	3	0.93	0.85	0.80					
ĥ	3 1/2	1.00	0.91	0.84					
Ē	4		0.96	0.89	0.80				
e,	4 3/8		1.00	0.92	0.83				
and	5			0.98	0.87	0.80			
ist	5 1/4			1.00	0.88	0.81			
D a	6				0.93	0.85			
dge	7				1.00	0.91			
ш	8					0.96			
	8 3/4					1.00			

	Edge Distance, Shear (<i>F_{VC}</i>)									
Dia	. (in.)	1/4	5/16	3/8	1/2	5/8				
Ccr	(in.)	3 1/2	4 3/8	5 1/4	7	8 3/4				
Cmi	n (in.)	2	2 1/2	3	4	5				
	2	0.50								
	2 1/2	0.67	0.50							
es)	3	0.83	0.63	0.50						
15	3 1/2	1.00	0.77	0.61						
E.	4		0.90	0.72	0.50					
je j	4 3/8		1.00	0.81	0.56					
a l	5			0.94	0.67	0.50				
ist	5 1/4			1.00	0.71	0.53				
G.	6				0.83	0.63				
gg	7				1.00	0.77				
۳.	8					0.90				
	8 3/4					1.00				



ANCHORS

ORDERING INFORMATION

Hollow-Set Dropin with Carbon Steel Cone

Catalog Number	Rod/Anchor Diameter	Drill Diameter	Overall Length	Sleeve Length	Std. Box	Std. Ctn.	Wt./ 100
9320	1/4"	3/8"	7/8"	5/8"	100	1,000	1-3/4
9330	5/16"	5/8"	1-5/16"	15/16"	50	500	5-1/2
9340	3/8"	5/8"	1-5/16"	15/16"	50	300	5-1/2
9350	1/2"	3/4"	1-3/4"	1 1/4"	50	250	9-1/2
9360	5/8"	1"	2"	1 1/2"	25	125	21



Hollow-Set Dropin with Stainless Steel Cone

Catalog Number	Rod/Anchor Diameter	Drill Diameter	Overall Length	Sleeve Length	Std. Box	Std. Ctn.	Wt./ 100
9420	1/4"	3/8"	7/8"	5/8"	100	1,000	1-3/4
9440	3/8"	5/8"	1-5/16"	15/16"	100	500	5-1/2

Setting Tool for Solid Base Materials

Catalog Number	Size	Standard Box	Standard Carton
9322	1/4"	1	1
9342	5/16" and 3/8"	1	1
9352	1/2 "	1	1
9362	5/8"	1	1



Setting Tool for Hollow Base Materials*

Catalog Number	Size	Standard Box	Standard Carton
9323	1/4"	1	1
9333	5/16"	1	1
9343	3/8 "	1	1
9353	1/2 "	1	1
9363	5/8"	1	1



d

* Hollow set tool for hollow block and clay brick masonry base materials.

© 2011 Powers Fasteners, Inc. All Rights Reserved. Dropin is a trademark of Powers Fasteners, Inc. For the most current product information please visit www.powers.com.

7