



- PRECISION BRAND Music Wire is spring tempered and made from high carbon steel alloy
- High tensile strength and high fatigue resistance
- Applications include springs, wire forms, control linkages, armature binding, ceramic cutting and a variety of industrial uses
- Most wire is available in **cut-and-straightened** lengths and in bulk quantities as a special order.

- PRECISION BRAND Stainless Steel Wire is spring tempered, full hard, 300 series stainless steel wire
- Excellent corrosion resistant qualities and smooth finish
- Same applications as Music Wire
- All packaged wire is shrink wrapped and bar coded. .006" to .078" are packaged in easy to use pull-type dispenser boxes.

Music Wire

Stainless Steel

Diameter		Approx. Feet Per lb.	Tensile Strength (ksi) min.-max.	Music Wire		Tensile Strength (ksi) min.-max.	1 lb. UPC No.
Decimal	Metric (mm)			1 lb. UPC No.	1/4 lb. UPC No.		
.006	.152	10,404	415-459	21006	21206	325-355	29006
.007	.178	7,644	407-449	21007	21207	325-355	29007
.008	.203	5,853	399-441	21008	21208	325-355	29008
.009	.229	4,624	393-434	21009	21209	325-355	29009
.010	.254	3,746	387-428	21010	21210	320-350	29010
.011	.279	3,096	382-422	21011	21211	318-348	29011
.012	.305	2,601	377-417	21012	21212	316-346	29012
.013	.330	2,217	373-412	21013	21213	314-344	29013
.014	.356	1,911	369-408	21014	21214	312-342	29014
.016	.406	1,464	362-400	21016	21216	308-338	29016
.018	.457	1,156	356-393	21018	21218	304-334	29018
.020	.508	937	350-387	21020	21220	300-330	29020
.022	.559	774	345-382	21022	21222	296-326	29022
.024	.610	651	341-377	21024	21224	292-322	29024
.026	.660	555	337-373	21026	21226	291-320	29026
.029	.737	446	331-367	21029	21229	285-315	29029
.031	.787	390	328-363	21031	21231	285-315	29031
.033	.838	344	325-360	21033	21233	282-310	29033
.035	.889	306	322-357	21035	21235	280-308	29035
.037	.940	274	319-354	21037	21237	280-308	29037
.039	.991	247	316-351	21039	21239	275-304	29039
.041	1.041	223	314-348	21041	21241	275-304	29041
.043	1.092	203	311-344	21043	21243	272-300	29043
.045	1.143	185	309-342	21045	21245	272-300	29045
.047	1.194	170	307-340	21047	21247	-	-
.0475	1.207	166	-	-	-	267-295	29047
.049	1.245	156	304-337	21049	21249	-	-
.050	1.270	150	-	-	-	267-295	29050
.051	1.295	144	303-335	21051	21251	265-293	29051
.055	1.397	124	300-331	21055	21255	261-289	29055
.059	1.499	108	296-327	21059	21259	258-285	29059
.0625	1.588	97	-	-	-	258-285	29062

Sizes continued on next page.