


3/8" DRIVE HIGH STRENGTH MAGNETIC IMPACT SOCKETS - 6 POINT




| INCH | 6 | Nut End Outside Diameter (in) (B) | Drive End Outside Diameter (in) (C) | Nut Depth (in) (D) | Overall Length (in) (L) | Weight (lbs) |
|------|---------|-----------------------------------|-------------------------------------|--------------------|-------------------------|--------------|
| 1/4 | J7208HF | 7/16 | 11/16 | 11/64 | 1-3/32 | 0.07 |
| 5/16 | J7210HF | 1/2 | 11/16 | 3/16 | 1-3/32 | 0.08 |
| 3/8 | J7212HF | 39/64 | 11/16 | 15/64 | 1-3/32 | 0.08 |
| 7/16 | J7214HF | 11/16 | 11/16 | 1/4 | 1-3/32 | 0.08 |
| 1/2 | J7216HF | 3/4 | 3/4 | 9/32 | 1-3/32 | 0.08 |
| 9/16 | J7218HF | 13/16 | 13/16 | 21/64 | 1-3/32 | 0.12 |
| 5/8 | J7220HF | 29/32 | 29/32 | 23/64 | 1-7/32 | 0.16 |

ASME B107.33M

| MM | 6 | Nut End Outside Diameter (in) (B) | Drive End Outside Diameter (in) (C) | Nut Depth (in) (D) | Overall Length (in) (L) | Weight (lbs) |
|----|----------|-----------------------------------|-------------------------------------|--------------------|-------------------------|--------------|
| 7 | J7207MHF | 31/64 | 11/16 | 11/64 | 1-3/32 | 0.08 |
| 8 | J7208MHF | 1/2 | 11/16 | 11/64 | 1-3/32 | 0.07 |
| 10 | J7210MHF | 5/8 | 11/16 | 7/32 | 1-9/64 | 0.08 |
| 11 | J7211MHF | 11/16 | 11/16 | 17/64 | 1-9/64 | 0.08 |
| 12 | J7212MHF | 47/64 | 47/64 | 9/32 | 1-9/64 | 0.09 |
| 13 | J7213MHF | 3/4 | 3/4 | 19/64 | 1-13/64 | 0.10 |
| 14 | J7214MHF | 13/16 | 13/16 | 21/64 | 1-13/64 | 0.12 |
| 15 | J7215MHF | 55/64 | 55/64 | 21/64 | 1-13/64 | 0.14 |
| 17 | J7217MHF | 1 | 1 | 25/64 | 1-1/4 | 0.20 |
| 18 | J7218MHF | 1-1/32 | 1-1/32 | 25/64 | 1-1/4 | 0.21 |

ASME B107.33

1/2" DRIVE HIGH STRENGTH MAGNETIC IMPACT SOCKETS - 6 POINT



| INCH | 6 | Nut End Outside Diameter (in) (B) | Drive End Outside Diameter (in) (C) | Nut Depth (in) (D) | Overall Length (in) (L) | Weight (lbs) |
|------|---------|-----------------------------------|-------------------------------------|--------------------|-------------------------|--------------|
| 3/8 | J7412HF | 47/64 | 15/16 | 15/64 | 1-1/2 | 0.18 |
| 7/16 | J7414HF | 45/64 | 15/16 | 1/4 | 1-1/2 | 0.19 |
| 1/2 | J7416HF | 25/32 | 15/16 | 17/64 | 1-1/2 | 0.19 |
| 9/16 | J7418HF | 7/8 | 15/16 | 21/64 | 1-1/2 | 0.20 |
| 5/8 | J7420HF | 1 | 1 | 25/64 | 1-1/2 | 0.23 |

ASME B107.2

| MM | 6 | Nut End Outside Diameter (in) (B) | Drive End Outside Diameter (in) (C) | Nut Depth (in) (D) | Overall Length (in) (L) | Weight (lbs) |
|----|----------|-----------------------------------|-------------------------------------|--------------------|-------------------------|--------------|
| 10 | J7410MHF | 41/64 | 15/16 | 7/32 | 1-1/2 | 0.19 |
| 13 | J7413MHF | 51/64 | 15/16 | 17/64 | 1-1/2 | 0.19 |
| 14 | J7414MHF | 15/16 | 15/16 | 9/32 | 1-1/2 | 0.20 |
| 15 | J7415MHF | 15/16 | 15/16 | 9/32 | 1-1/2 | 0.21 |
| 18 | J7418MHF | 1-1/16 | 1-1/16 | 13/32 | 1-1/2 | 0.27 |

ASME B107.2