



WIRE STRIPPERS - PLIERS

- › Strips 10-22 AWG (American Wire Gauge).
- › Crimps insulated and non-insulated terminals for 10-22 AWG wire.
- › Crimps non-insulated 7mm and 8mm auto ignition wire.
- › Cuts screw/bolt sizes 4-40, 5-40, 6-32, 8-32, 10-32, 10-24 and copper wire.
- › Extended length curved cutter to handle heavier wire with less force.
- › Plier nose designed to grip, bend, and pull wire.
- › Plastisol grips for added comfort.

| Product # | Overall Length (in) (L) | Weight (lbs) |
|-------------|-------------------------|--------------|
| J298 | 8-1/4 | 0.05 |



LOCK RING "HORSESHOE" WASHER PLIERS

- › For spreading both soft iron "horseshoe" lock washers used on brakes and tempered steel lock rings used on gear and bearing shafts.
- › Plastisol grips for added comfort.

| Product # | Overall Length (in) (L) | Weight (lbs) |
|--------------|-------------------------|--------------|
| J250G | 7-13/16 | 0.49 |



LOCK RING PLIERS - PARALLEL JAW

- › For removal of lock snap rings used on bearing shafts.
- › Compound leverage simplifies removal.
- › Jaw tips are indented to hold ring ends and prevent breakage.
- › Jaws spread 1-1/4".
- › Plastisol grips for added comfort.

| Product # | Overall Length (in) (L) | Weight (lbs) |
|--------------|-------------------------|--------------|
| J251G | 10-9/16 | 0.68 |



12 PIECE CONVERTIBLE RETAINING RING PLIERS SET

Product #: **J360B**

- › Convenient blow-molded carrying case includes storage for spare rings.
- › Ring range: External (Shaft) 1/4" - 3-11/32"; Internal (Bore) 3/8" - 3".
- › Weight (lbs): 4.82



| Contents | Tip Size | Tip Angle | Length (in) | Shaft Diameter (in) (External) | Bore Diameter (in) (Internal) | Weight (lbs) |
|----------|----------|-----------|-------------|--------------------------------|-------------------------------|--------------|
| J399 | .038 | 0° | 5-7/8 | 1/4 - 43/64 | 3/8 - 9/16 | 0.15 |
| J370 | .038 | 45° | 5-3/4 | 1/4 - 3/64 | 3/8 - 9/16 | 0.16 |
| J371 | .038 | 90° | 5-11/16 | 1/2 - 25/32 | 3/8 - 9/16 | 0.16 |
| J372 | .047 | 0° | 5-7/8 | 11/16 - 7/8 | 5/8 - 1 | 0.16 |
| J373 | .047 | 45° | 5-3/4 | 11/16 - 7/8 | 5/8 - 1 | 0.15 |
| J374 | .047 | 90° | 5-11/16 | 13/16 - 1 | 5/8 - 1 | 0.16 |
| J385 | .070 | 0° | 7-1/2 | 15/16 - 1-7/16 | 1-1/16 - 13/4 | 0.29 |
| J375 | .070 | 45° | 7-3/8 | 1 - 1-7/16 | 1-1/16 - 13/4 | 0.32 |
| J376 | .070 | 90° | 7-1/8 | 1 - 1/16, 2 | 1-7/16 - 2 | 0.31 |
| J377 | .090 | 0° | 9-1/4 | 1-1/2 - 3-1/2 | 1-13/16 - 3 | 0.54 |
| J378 | .090 | 45° | 9 | 1-1/2 - 3-1/2 | 1-13/16 - 3 | 0.55 |
| J379 | .090 | 90° | 8-5/8 | 1-1/2 - 1-3/4 | 1-13/16 - 3 | 0.56 |