



SOFT GRIP SCREWDRIVERS

- › Precision Tips for tight tolerance and fastener fit.
- › Custom designed handles constructed of dual materials with hard center core for strength with cushion grip for comfort and control.
- › Blades are constructed from high alloy steel for high strength and performance. Plated to resist corrosion.
- › Cushion handle tapered for easy gripping and comfort.
- › Flutes designed for better turning.



Product #	Tip Size	Tips	Shank Length (in)	Shank Type	Overall Length (in)	Weight (lbs)	ASME Spec.
J9403	3/16	Keystone Slotted	3	Round	6-3/4	0.17	ASME B107.15
J9406	5/16	Keystone Slotted	6	Round	10-13/32	0.35	ASME B107.15
J9408	3/8	Keystone Slotted	8	Round	13-1/2	0.62	ASME B107.15
J9482	#1	Phillips	3	Round	6-3/4	0.17	-
J9484	#2	Phillips	4	Round	8-11/32	0.27	-



HEX SCREWDRIVERS

- › Black oxide shank finish.
- › Precisely constructed for a truer fit with fasteners.



Product #	Tip Size (in)	Tips	Shank Length (in)	Overall Length (in)	Weight (lbs)
J88601	3/64	Hex	2-3/8	4-51/64	0.03
J88602	1/16	Hex	2-1/2	5	0.03
J88603	5/64	Hex	2-21/32	5	0.03
J88604	3/32	Hex	2-3/4	6-1/4	0.04
J88605	7/64	Hex	3	6-1/4	0.04
J88606	1/8	Hex	3-1/8	6-1/2	0.04
J88607	9/64	Hex	3-1/4	6-1/2	0.05
J88608	5/32	Hex	3-1/2	8	0.13
J88609	3/16	Hex	3-3/4	8	0.14



OFFSET SCREWDRIVERS

- › Black oxide finish.
- › Designed for use in tight spaces.



Product #	Type	Tip Width (in)	Overall Length (in)	Weight (lbs)
J361/4	Slotted	1/4	4-5/8	0.05
J365/16	Slotted	5/16	4-7/8	0.13
J363/8	Slotted	3/8	6-1/8	0.12
J341/4	Phillips	#1, #2	4-3/4	0.07
J343/8	Phillips	#3, #4	6-1/8	0.12

