

## 1/4" DRIVE SCREWDRIVER BIT SOCKETS

- › Two piece design allows replacement of worn bits.
- › Bit holders have a hex opening to hold the bit, allowing the bit holder to take the full load of torque.

	Size	Product #	Tip Thickness (in)	Bit Length (in)	Overall Length (in)	Weight (lbs)
Slotted	1/4"	⊖ <b>J4743</b>	3/64	–	1-3/16	0.05
	3/16"	⊖ <b>J4744</b>	1/32	–	1-53/64	0.05
	1/4"	⊖ <b>J4745</b>	3/64	–	1-53/64	0.06
Phillips	#1	⊕ <b>J4737</b>	–	–	1-13/64	0.04
	#2	⊕ <b>J4738</b>	–	–	1-13/64	0.05
Torx®	T10	⊗ <b>J4739-10W</b>	–	5/8	1-1/2	0.06
	T15	⊗ <b>J4739-15W</b>	–	5/8	1-1/2	0.05
	T20	⊗ <b>J4739-20W</b>	–	5/8	1-1/2	0.05
	T25	⊗ <b>J4739-25W</b>	–	5/8	1-1/2	0.05
	T27	⊗ <b>J4739-27W</b>	–	5/8	1-1/2	0.06
	T30	⊗ <b>J4739-30W</b>	–	7/8	1-3/4	0.05



## 1/4" DRIVE HEX BIT SOCKETS

- › Bit holders have a hex opening to hold the bit allowing the bit holder to take the full load of torque.
- › Made of heat-treated alloy steel.
- › Polished chrome finish.

INCH	HEX	Bit Length (in)	Overall Length (in)	Weight (lbs)
1/16	<b>J47701/16</b>	1	1-7/8	0.05
5/64	<b>J47705/64</b>	1	1-7/8	0.05
3/32	<b>J47703/32</b>	1	1-7/8	0.05
7/64	<b>J47707/64</b>	1	1-7/8	0.06
1/8	<b>J47701/8</b>	1	1-7/8	0.05
9/64	<b>J47709/64</b>	1	1-7/8	0.05
5/32	<b>J47705/32</b>	1	1-7/8	0.05
3/16	<b>J47703/16</b>	1	1-7/8	0.05
7/32	<b>J47707/32</b>	1	1-7/8	0.05
1/4	<b>J47701/4</b>	1	1-7/8	0.06
5/16	<b>J47705/16</b>	1	1-7/8	0.06



## 1/4" DRIVE BALL END HEX BIT SOCKETS

INCH	HEX	Overall Length (in)	Weight (lbs)
1/4	<b>J47701/4B</b>	1-1/2	0.05
1/8	<b>J47701/8B</b>	1-1/2	0.05
3/16	<b>J47703/16B</b>	1-1/2	0.05
3/32	<b>J47703/32B</b>	1-1/2	0.05
5/32	<b>J47705/32B</b>	1-1/2	0.05
7/32	<b>J47707/32B</b>	1-1/2	0.05
7/64	<b>J47707/64B</b>	1-1/2	0.05
9/64	<b>J47709/64B</b>	1-1/2	0.05



Torx® is a trademark of Acument Intellectual Properties, LLC